


Product Description:

Encastré LED intégrée fixe de 7W compatible RT2012, pare-feu avec driver intégré. Conception convertible pour plenum étroit (jusqu' 50 mm). Compatible tout isolant. Température de couleur disponible : 3000 et 4000 K. Colerette disponible en blanc, blanc mat, chromé et alu brossé. Pré-équipé d'une lentille de 60°. Protection plafond coupe-feu de 30, 60 et 90 minutes. Conforme aux normes EN 1365-2:2000 (résistance au feu), EN ISO 140-3:1995 et EN ISO 140-6:1998 (acoustique), EN 13141-1:2004 (ventilation).

Product Image:



Line Drawing



Product Specs:

Technology	LED	Input Voltage	220-240V AC
Lamp Base	Aucun	Positional Adjustment	Orientable
Positional Adjustment (°)	20	Number of LEDs	9
Luminaire Distribution	Direct	Lifetime L70 (hrs)	40.000
Input Frequency	50/60HZ	Dimmable	Oui
IP Rating	IP65	Fire Protection	Oui
Acoustic Rated	Oui	Operating Env. Temp. (Min) °C	-25°C
Operating Env. Temp. (Max) °C	45°C	Optic Material	PMMA
Power Factor	0.85	Overall Diameter (mm)	98
Height (mm)	103	Recess Depth (mm)	100
Length (mm)	103	Cutout Diameter (mm)	85
Weight (Kg)	0.465		

SKU Table and Ordering:

SKU Code	Wattage	Beam Angle	Lumens	Lumens/Watt	CRI	Colour	Finish Colour
AU-MPRO4MW/27	7	60	600	86	80	2700	Blanc mat
AU-MPRO4MW/30	7	60	630	90	80	3000	Blanc mat
AU-MPRO4MW/40	7	60	660	95	80	4000	Blanc mat
AU-MPRO4PC/27	7	60	600	86	80	2700	Chromé
AU-MPRO4PC/30	7	60	630	90	80	3000	Chromé
AU-MPRO4PC/40	7	60	660	95	80	4000	Chromé
AU-MPRO4SN/27	7	60	600	86	80	2700	Alu brossé
AU-MPRO4SN/30	7	60	630	90	80	3000	Alu brossé
AU-MPRO4SN/40	7	60	660	95	80	4000	Alu brossé
AU-MPRO4W/27	7	60	600	86	80	2700	Blanc
AU-MPRO4W/30	7	60	630	90	80	3000	Blanc
AU-MPRO4W/40	7	60	660	95	80	4000	Blanc

Compliance & Approvals:



Warranty:

This product has a guarantee period of 1 an. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.

UK Head Office

Apex Park
6 Little Burrow
Welwyn Garden City AL7 4SW
United Kingdom
Tel : +44 (0) 1727 83 66 11