



OMEGA 60

ACIER
STEEL

Hauteur de 5 à 10 mètres
5 to 10 meters height

Fût rond-conique en acier. 60 mm en tête, 2 rangées de crevés taraudés à 100 et 200 mm du sommet.

Round-conical steel pole. 60 mm top dia, 2 rows of threaded holes at 100 and 200 mm from top.



Dimensions

H5 m	Øa mm	Øb mm	Lp mm	Pp mm	Hp mm	cx mm	E mm	J mm
5	60	130	450	79	500	65x87	200	J 16/14x300
6	60	144	450	81	500	75x97	200	J 16/14x300
7	60	155	500	91	500	90x100	300	J 20/18x400
8	60	168	500	91	500	90x116	300	J 20/18x400
9	60	181	500	100	500	100x125	300	J 20/18x400
10	60	199	500	102	500	100x150	300	J 20/18x400

Capacités

H5 m	Kg	22 m/s		24 m/s		26 m/s		28 m/s		34 m/s		M m.daN	T daN	Lm x Hm m
		Cat II	Cat I	Cat II	Cat I	Cat II	Cat I	Cat II	Cat I	Cat II	Cat I			
5	50	0,81	0,62	0,65	0,50	0,53	0,40	0,43	0,33	0,25	0,19	443	125	0.5x0.6
6	50	0,73	0,57	0,59	0,45	0,47	0,36	0,38	0,29	0,21	0,16	565	139	0.5x0.7
7	50	0,56	0,42	0,43	0,32	0,33	0,24	0,26	0,19	0,13	0,09	615	143	0.6x0.6
8	50	0,51	0,38	0,39	0,28	0,29	0,21	0,23	0,16	0,10	0,07	746	161	0.6x0.7
9	50	0,42	0,30	0,31	0,21	0,22	0,15	0,16	0,11	0,06	-	835	168	0.6x0.7
10	50	0,42	0,31	0,31	0,22	0,22	0,16	0,16	0,11	0,06	-	1014	183	0.6x0.8



Luminaire COMATELEC

Accessoires et options
PORTE



Accessoires et options
PIED DE MÂT



Bon à savoir

Le rond-conique pour crosse, rehausse ou luminaire en top.

Tip

The round conical pole for top mounting light or accessory bracket.