

OMEGA 89

Hauteur de 4 à 12 mètres

4 to 12 meters height



Luminaire PHILIPS

Fût rond-conique en acier. 89 mm en tête, 2 rangées de crevés taraudés à 100 et 200 mm du sommet.

Round-conical steel pole. 89 mm top dia, 2 rows of threaded holes at 100 and 200 mm from top.



Dimensions

| HS m | Øa mm | Øb mm | Lp mm | Pp mm | Hp mm | cx d mm | E mm | J TS mm |
|---------|----------|----------|----------|----------|----------|------------|---------|---------------|
| 4 | 89 | 151 | 450 | 85 | 500 | 85x96 | 200 | J 16/14x300 |
| 5 | 89 | 167 | 500 | 91 | 500 | 90x110 | 300 | J 20/18x400 |
| 6 | 89 | 180 | 500 | 100 | 500 | 95x125 | 300 | J 20/18x400 |
| 7 | 89 | 198 | 500 | 102 | 500 | 95x145 | 300 | J 20/18x400 |
| 8 | 89 | 226 | 500 | 103 | 500 | 100x170 | 300 | J 20/18x400 |
| 9 | 89 | 243 | 500 | 104 | 500 | 100x185 | 300 | J 20/18x400 |
| 10 | 89 | 267 | 500 | 105 | 500 | 100x215 | 300 | J 20/18x400 |
| 12 | 89 | 256 | 600 | 140 | 500 | 135x195 | 300 | J 20/18x400 |

Capacités

| HS m | Kg | 22 m/s | | 24 m/s | | 26 m/s | | 28 m/s | | 34 m/s | | M m.daN | T daN | Lm x Hm m |
|---------|----|--------|-------|--------|-------|--------|-------|--------|-------|--------|-------|------------|----------|--------------|
| | | Cat II | Cat I | Cat II | Cat I | Cat II | Cat I | Cat II | Cat I | Cat II | Cat I | | | |
| 4 | 50 | 2,49 | 2,00 | 2,10 | 1,66 | 1,76 | 1,39 | 1,51 | 1,20 | 1,00 | 0,79 | 764 | 216 | 0.5x0.8 |
| 5 | 50 | 2,08 | 1,66 | 1,71 | 1,37 | 1,44 | 1,16 | 1,22 | 0,99 | 0,81 | 0,65 | 903 | 216 | 0.6x0.8 |
| 6 | 50 | 1,71 | 1,37 | 1,39 | 1,14 | 1,18 | 0,95 | 1,00 | 0,81 | 0,65 | 0,53 | 1019 | 217 | 0.6x0.8 |
| 7 | 50 | 1,66 | 1,34 | 1,37 | 1,11 | 1,14 | 0,93 | 0,96 | 0,78 | 0,62 | 0,50 | 1256 | 242 | 0.6x0.9 |
| 8 | 50 | 1,83 | 1,49 | 1,51 | 1,25 | 1,27 | 1,04 | 1,07 | 0,88 | 0,68 | 0,55 | 1667 | 291 | 0.6x1.1 |
| 9 | 50 | 1,76 | 1,47 | 1,44 | 1,20 | 1,22 | 1,00 | 1,03 | 0,84 | 0,64 | 0,51 | 1945 | 319 | 0.6x1.2 |
| 10 | 50 | 1,83 | 1,54 | 1,51 | 1,25 | 1,27 | 1,04 | 1,06 | 0,87 | 0,65 | 0,51 | 2344 | 362 | 0.6x1.3 |
| 12 | 50 | 1,44 | 1,20 | 1,17 | 0,96 | 0,96 | 0,78 | 0,79 | 0,64 | 0,44 | 0,32 | 2589 | 375 | 0.6x1.4 |

Bon à savoir

Se reporter à la gamme accessoires/embouts démontables pour prévoir la liaison fût/luminaire.

Tip

For connections to lantern see accessories range/removable spigots.

Accessoires et options
PORTE



Accessoires et options
PIED DE MÂT

