


TC 89

Hauteur de 3 à 5 mètres
3 to 5 meters height



Fût cylindrique en acier. Diamètre 89 mm, une lumière pour embouts démontables.

Cylinder-shaped steel pole. 89 mm diameter, one slotted hole for removable spigots.



Dimensions

HS m	Øa mm	Øb mm	Lp mm	Pp mm	Hp mm	Cxd mm	E mm	TS mm
3	89	89	400	55	700	55x60	200	J 16/14x300
3,5	89	89	400	55	700	55x60	200	J 16/14x300
4	89	89	400	55	700	55x60	200	J 16/14x300
4,5	89	89	400	55	700	55x60	200	J 16/14x300
5	89	89	400	55	700	55x60	200	J 16/14x300

Capacités

HS m	Kg	22 m/s		24 m/s		26 m/s		28 m/s		34 m/s		M	T	Lm x Hm m
		Cat II	Cat I	Cat II	Cat I	Cat II	Cat I	Cat II	Cat I	Cat II	Cat I	m.daN	daN	
3	25	1,51	1,29	1,27	1,07	1,06	0,90	0,90	0,77	0,59	0,51	353	139	0.5x0.5
3,5	25	1,17	0,95	0,95	0,78	0,79	0,65	0,67	0,55	0,43	0,35	342	123	0.5x0.5
4	25	0,90	0,70	0,73	0,57	0,60	0,47	0,50	0,39	0,31	0,24	335	114	0.5x0.5
4,5	25	0,68	0,53	0,54	0,42	0,43	0,34	0,36	0,28	0,21	0,16	333	110	0.5x0.5
5	25	0,51	0,38	0,39	0,29	0,31	0,23	0,25	0,18	0,13	0,10	331	107	0.5x0.5

BON À SAVOIR

Se reporter à la gamme accessoires acier/embout démontable, pour prévoir la liaison fût/luminaire.

TIP

To view the pole/light source connection, please refer to the accessories range: steel/removable spigot.

Accessoires et options
PIED DE MÂT

