



Hauteur de 3 à 5 mètres

3 to 5 meters height



Fût cylindrique en acier. Diamètre 89 mm, une lumière pour embouts démontables.

Cylinder-shaped steel pole. 89 mm diameter, one slotted hole for removable spigots.



Dimensions

| HS m | Øa mm | Øb mm | Lp mm | Pp mm | Hp mm | cxd mm | E mm | TS mm |
|---------|----------|----------|----------|----------|----------|-----------|---------|-------------|
| 3 | 89 | 89 | 400 | 55 | 700 | 55x60 | 200 | J 16/14x300 |
| 3,5 | 89 | 89 | 400 | 55 | 700 | 55x60 | 200 | J 16/14x300 |
| 4 | 89 | 89 | 400 | 55 | 700 | 55x60 | 200 | J 16/14x300 |
| 4,5 | 89 | 89 | 400 | 55 | 700 | 55x60 | 200 | J 16/14x300 |
| 5 | 89 | 89 | 400 | 55 | 700 | 55x60 | 200 | J 16/14x300 |

Capacités

| HS m | Kg | 22 m/s | | 24 m/s | | 26 m/s | | 28 m/s | | 34 m/s | | M m.daN | T daN | Lm x Hm m |
|---------|----|--------|-------|--------|-------|--------|-------|--------|-------|--------|-------|------------|----------|--------------|
| | | Cat II | Cat I | Cat II | Cat I | Cat II | Cat I | Cat II | Cat I | Cat II | Cat I | | | |
| 3 | 25 | 1,51 | 1,29 | 1,27 | 1,07 | 1,06 | 0,90 | 0,90 | 0,77 | 0,59 | 0,51 | 353 | 139 | 0.5x0.5 |
| 3,5 | 25 | 1,17 | 0,95 | 0,95 | 0,78 | 0,79 | 0,65 | 0,67 | 0,55 | 0,43 | 0,35 | 342 | 123 | 0.5x0.5 |
| 4 | 25 | 0,90 | 0,70 | 0,73 | 0,57 | 0,60 | 0,47 | 0,50 | 0,39 | 0,31 | 0,24 | 335 | 114 | 0.5x0.5 |
| 4,5 | 25 | 0,68 | 0,53 | 0,54 | 0,42 | 0,43 | 0,34 | 0,36 | 0,28 | 0,21 | 0,16 | 333 | 110 | 0.5x0.5 |
| 5 | 25 | 0,51 | 0,38 | 0,39 | 0,29 | 0,31 | 0,23 | 0,25 | 0,18 | 0,13 | 0,10 | 331 | 107 | 0.5x0.5 |

Bon à savoir

Se reporter à la gamme accessoires acier/ embout démontable, pour prévoir la liaison fût/luminaire.

Tip

To view the pole/light source connection, please refer to the accessories range: steel/removable spigot.

Accessoires et options
PIED DE MÂT

