



Composition Fricokit®

Type	Désignation	Puissance	Surface brut	Composition panneaux				Guirlande connectique			Thermost.	Poids
				Carton	SKP36N neutre 1200x600	SKP3606 44 W 600x600	SKP3612 88 W 1200x600	Type	Nbre pann. maxi	Long. [m]		
		[W]	[m²]									[kg]
Fkit132	Fricokit® 132W	132	1,80	A	1	1	1	GPRP06	6	6	1	6
Fkit264	Fricokit® 264W	264	3,60	2 x A	2	2	2	GPRP06	6	6	1	12
Fkit396	Fricokit® 396W	396	5,40	B	3	3	3	GPRP06	6	6	1	16
Fkit528	Fricokit® 528W	528	7,20	A + B	4	4	4	GPRP10	10	9	1	22
Fkit660	Fricokit® 660W	660	9,00	2 x A + C	5	3	6	GPRP10	10	9	1	28
Fkit792	Fricokit® 792W	792	10,80	B + C	6	4	7	GPRP14	14	12	1	32
Fkit924	Fricokit® 924W	924	12,60	A + 2 x C	7	3	9	GPRP14	14	12	1	38
Fkit1056	Fricokit® 1056W	1056	14,40	2 x A + 2 x C	8	4	10	GPRP14	14	12	1	44
Fkit1188	Fricokit® 1188W	1188	16,20	3 x C	9	3	12	GPRP18	18	15	1	48
Fkit1320	Fricokit® 1320W	1320	18,00	A + 3 x C	10	4	13	GPRP18	18	15	1	54
Fkit1452	Fricokit® 1452W	1452	19,80	2 x A + 3 x C	11	5	14	GPRM20	20	9	1	60
Fkit1584	Fricokit® 1584W	1584	21,60	4 x C	12	4	16	GPRM20	20	9	1	64
Fkit1716	Fricokit® 1716W	1716	23,40	A + 4 x C	13	5	17	GPRP24	24	18	1	70
Fkit1848	Fricokit® 1848W	1848	25,20	2 x A + 4 x C	14	6	18	GPRP24	24	18	1	76
Fkit1980	Fricokit® 1980W	1980	27,00	5 x C	15	5	20	GPRM30	30	12	1	80
Fkit2244	Fricokit® 2244W	2244	30,60	2 x A + 5 x C	17	7	22	GPRM30	30	12	1	92
Fkit n3	Fricokit® neutre	0	2,16	N	3	-	-	-			-	6
FkitCartA	Carton A 132W	132	1,80	A	1	1	1	-			-	5
FkitCartB	Carton B 396W	396	5,40	B	3	3	3	-			-	16
FkitCartC	Carton C 396W	396	5,40	C	3	1	4	-			-	16

A = 1 x SKP36N + 1 x SKP3606 + 1 x SKP3612

B = 3 x SKP36N + 3 x SKP3606 + 3 x SKP3612

C = 3 x SKP36N + 1 x SKP3606 + 4 x SKP3612

N = 3 x SKP36N