



Type of luminaire

Type of luminaire	Post light fixture.
Photometric body	Light with rotationally symmetrical light distribution.
Characteristics of the luminaire	A bollard luminaire with a stable and durable construction For lighting private and public areas Functions: control, color change 2700K...6500K (TW), WiZ, WiZ Pro. - Available after mounting in the luminaire, Signify WiZ Pro A60 E27 TW 8W lamps 230V - Full control of the luminaire after installing the free application https://pro.wizconnected.com/ - Technical support: Information Sales Department of Norlys

General information

Materials	Powder painted aluminum cast. Lens - satin PMMA plastic. Silicone gasket. Nylon6 cable gland.
Mounting method	Mounting of the luminaire: 3 holes Ø9mm on a diameter Ø65mm every 120° According to the attached assembly instructions Other accessories must be purchased separately Full control of the luminaire with the WiZ lamp, using Bluetooth and WiFi signals - Check the range of the WiFi network at the place of installation of the luminaire
Terminal	Connection terminals: max 2x2,5mm ² Possibility to connect in loop max 2x2,5mm ² Round insulated cable with a diameter of Ø7...10,5mm
Type of light source	Lamp E27 Replaceable light source by an end-user.
Luminaire weight net / gross	4,75kg / 5,73kg
Box dimensions [cm]	16cm x 16cm x 93cm
Luminaire dimensions [cm]	12cm x 12cm x 85cm

Technical data

Lamp E27	Yes
Luminaire wattage	LED max 9W
ULOR	41%
Ta Rated temperature	+25°C, up to +50°C on request
Ambient temperature	TA MAX=+65°C
BUG rating	"B0-U3-G1"

Accessories sold separately

206GA0S10	Adapter for concrete foundation
205ZX0010	Concreting anchor
206GA0010	Ground anchor
3080GA0009	Mounting adapter

Recommended light sources

Osram ECO PRO Classic 46 <=> 60W E27	Philips ECO Classic 42 <=> 60W E27
Osram LED Parathom Classic / Retrofit E27	Philips Master LEDbulb / Classic / CorePro E27

Files to download

Photometric LDT files	Photometric IES files
Manual	

Indexes

Index	Color	RAL
1380AL	ALUMINUM	9006
1380GR	GRAPHITE	7016