

Combination (%)	Capacity index (kW)	Outdoor air temp.	Indoor air temperature: °CWB																
			14.0		16.0		18.0		19.0		20.0		22.0		24.0				
			TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI			
90	60.30	°CDB	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW		
		10	40.7	7.40	48.5	8.51	56.4	9.67	60.3	10.3	64.2	10.9	72.1	12.1	79.9	13.4	79.9	13.4	
		12	40.7	7.49	48.5	8.63	56.4	9.81	60.3	10.4	64.2	11.0	72.1	12.3	79.9	13.6	79.9	13.6	
		14	40.7	7.59	48.5	8.74	56.4	9.96	60.3	10.6	64.2	11.2	72.1	12.5	79.9	13.8	79.9	13.8	
		16	40.7	7.69	48.5	8.87	56.4	10.11	60.3	10.7	64.2	11.4	72.1	12.7	79.8	14.0	79.8	14.0	
		18	40.7	7.79	48.5	9.00	56.4	10.3	60.3	10.9	64.2	11.6	72.1	12.9	78.7	14.4	78.7	14.4	
		20	40.7	7.89	48.5	9.13	56.4	10.4	60.3	11.1	64.2	12.0	72.1	13.8	77.6	15.1	77.6	15.1	
		21	40.7	7.95	48.5	9.20	56.4	10.6	60.3	11.5	64.2	12.4	72.1	14.3	77.0	15.5	77.0	15.5	
		23	40.7	8.06	48.5	9.54	56.4	11.3	60.3	12.2	64.2	13.2	72.1	15.3	76.0	16.2	76.0	16.2	
		25	40.7	8.45	48.5	10.14	56.4	12.0	60.3	13.0	64.2	14.1	72.1	16.3	74.9	16.9	74.9	16.9	
		27	40.7	8.95	48.5	10.8	56.4	12.8	60.3	13.8	64.2	15.0	72.1	17.4	73.8	17.6	73.8	17.6	
		29	40.7	9.48	48.5	11.4	56.4	13.6	60.3	14.7	64.2	15.9	71.2	18.2	72.7	18.3	72.7	18.3	
		31	40.7	10.03	48.5	12.1	56.4	14.4	60.3	15.6	64.2	16.9	70.1	18.9	71.6	19.0	71.6	19.0	
		33	40.7	10.60	48.5	12.8	56.4	15.3	60.3	16.6	64.2	18.0	69.0	19.6	70.5	19.7	70.5	19.7	
		35	40.7	11.2	48.5	13.6	56.4	16.2	60.3	17.6	64.2	19.1	67.9	20.3	69.4	20.5	69.4	20.5	
		37	40.7	11.8	48.5	14.4	56.4	17.2	60.3	18.7	64.2	20.3	66.9	21.0	68.3	21.2	68.3	21.2	
		39	40.7	12.5	48.5	15.2	56.4	18.2	60.3	19.8	64.2	21.5	65.8	21.7	67.2	21.9	67.2	21.9	
		80	53.60	°CDB	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW
				10	36.2	6.79	43.1	7.74	50.1	8.74	53.6	9.26	57.1	9.78	64.1	10.9	71.0	12.0	71.0
12	36.2			6.87	43.1	7.84	50.1	8.86	53.6	9.39	57.1	9.92	64.1	11.0	71.0	12.1	71.0	12.1	
14	36.2			6.95	43.1	7.94	50.1	8.98	53.6	9.52	57.1	10.07	64.1	11.2	71.0	12.3	71.0	12.3	
16	36.2			7.03	43.1	8.05	50.1	9.11	53.6	9.66	57.1	10.2	64.1	11.4	71.0	12.5	71.0	12.5	
18	36.2			7.12	43.1	8.16	50.1	9.25	53.6	9.81	57.1	10.4	64.1	11.5	71.0	12.7	71.0	12.7	
20	36.2			7.21	43.1	8.27	50.1	9.39	53.6	9.96	57.1	10.5	64.1	11.9	71.0	13.6	71.0	13.6	
21	36.2			7.26	43.1	8.33	50.1	9.46	53.6	10.04	57.1	10.7	64.1	12.3	71.0	14.0	71.0	14.0	
23	36.2			7.36	43.1	8.45	50.1	9.87	53.6	10.6	57.1	11.4	64.1	13.1	71.0	15.0	71.0	15.0	
25	36.2			7.56	43.1	8.96	50.1	10.5	53.6	11.3	57.1	12.2	64.1	14.0	71.0	16.0	71.0	16.0	
27	36.2			8.00	43.1	9.50	50.1	11.2	53.6	12.0	57.1	13.0	64.1	14.9	71.0	17.0	71.0	17.0	
29	36.2			8.46	43.1	10.06	50.1	11.8	53.6	12.8	57.1	13.8	64.1	15.9	71.0	18.2	71.0	18.2	
31	36.2			8.93	43.1	10.6	50.1	12.5	53.6	13.6	57.1	14.6	64.1	16.9	69.9	18.9	69.9	18.9	
33	36.2			9.43	43.1	11.3	50.1	13.3	53.6	14.4	57.1	15.5	64.1	17.9	68.8	19.6	68.8	19.6	
35	36.2			9.95	43.1	11.9	50.1	14.1	53.6	15.2	57.1	16.5	64.1	19.0	67.8	20.3	67.8	20.3	
37	36.2			10.49	43.1	12.6	50.1	14.9	53.6	16.1	57.1	17.4	64.1	20.2	66.7	21.0	66.7	21.0	
39	36.2			11.1	43.1	13.3	50.1	15.8	53.6	17.1	57.1	18.5	64.1	21.4	65.6	21.7	65.6	21.7	
70	46.90			°CDB	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW
				10	31.7	6.20	37.8	7.00	43.9	7.84	46.9	8.27	49.9	8.72	56.0	9.62	62.1	10.6	62.1
		12	31.7	6.27	37.8	7.08	43.9	7.94	46.9	8.38	49.9	8.84	56.0	9.76	62.1	10.7	62.1	10.7	
		14	31.7	6.34	37.8	7.17	43.9	8.05	46.9	8.50	49.9	8.96	56.0	9.91	62.1	10.9	62.1	10.9	
		16	31.7	6.41	37.8	7.26	43.9	8.15	46.9	8.62	49.9	9.09	56.0	10.05	62.1	11.0	62.1	11.0	
		18	31.7	6.48	37.8	7.35	43.9	8.27	46.9	8.74	49.9	9.22	56.0	10.2	62.1	11.2	62.1	11.2	
		20	31.7	6.56	37.8	7.45	43.9	8.38	46.9	8.87	49.9	9.36	56.0	10.4	62.1	11.5	62.1	11.5	
		21	31.7	6.60	37.8	7.50	43.9	8.44	46.9	8.93	49.9	9.43	56.0	10.5	62.1	11.9	62.1	11.9	
		23	31.7	6.68	37.8	7.60	43.9	8.58	46.9	9.20	49.9	9.84	56.0	11.2	62.1	12.7	62.1	12.7	
		25	31.7	6.76	37.8	7.86	43.9	9.11	46.9	9.77	49.9	10.5	56.0	11.9	62.1	13.5	62.1	13.5	
		27	31.7	7.11	37.8	8.33	43.9	9.66	46.9	10.37	49.9	11.1	56.0	12.7	62.1	14.4	62.1	14.4	
		29	31.7	7.51	37.8	8.81	43.9	10.23	46.9	11.0	49.9	11.8	56.0	13.5	62.1	15.3	62.1	15.3	
		31	31.7	7.92	37.8	9.31	43.9	10.8	46.9	11.6	49.9	12.5	56.0	14.3	62.1	16.2	62.1	16.2	
		33	31.7	8.34	37.8	9.83	43.9	11.5	46.9	12.3	49.9	13.2	56.0	15.2	62.1	17.3	62.1	17.3	
		35	31.7	8.79	37.8	10.37	43.9	12.1	46.9	13.0	49.9	14.0	56.0	16.1	62.1	18.3	62.1	18.3	
		37	31.7	9.25	37.8	10.9	43.9	12.8	46.9	13.8	49.9	14.8	56.0	17.1	62.1	19.4	62.1	19.4	
		39	31.7	9.73	37.8	11.5	43.9	13.5	46.9	14.6	49.9	15.7	56.0	18.1	62.1	20.6	62.1	20.6	
		60	40.20	°CDB	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW
				10	27.1	5.64	32.4	6.29	37.6	6.98	40.2	7.33	42.8	7.69	48.0	8.44	53.3	9.21	53.3
12	27.1			5.70	32.4	6.36	37.6	7.06	40.2	7.42	42.8	7.79	48.0	8.55	53.3	9.34	53.3	9.34	
14	27.1			5.75	32.4	6.43	37.6	7.15	40.2	7.52	42.8	7.89	48.0	8.67	53.3	9.47	53.3	9.47	
16	27.1			5.81	32.4	6.50	37.6	7.23	40.2	7.61	42.8	8.00	48.0	8.79	53.3	9.61	53.3	9.61	
18	27.1			5.87	32.4	6.58	37.6	7.33	40.2	7.71	42.8	8.11	48.0	8.92	53.3	9.76	53.3	9.76	
20	27.1			5.93	32.4	6.66	37.6	7.42	40.2	7.82	42.8	8.22	48.0	9.05	53.3	9.91	53.3	9.91	
21	27.1			5.96	32.4	6.70	37.6	7.47	40.2	7.87	42.8	8.28	48.0	9.12	53.3	9.98	53.3	9.98	
23	27.1			6.03	32.4	6.78	37.6	7.57	40.2	7.98	42.8	8.40	48.0	9.43	53.3	10.6	53.3	10.6	
25	27.1			6.10	32.4	6.87	37.6	7.83	40.2	8.35	42.8	8.89	48.0	10.03	53.3	11.2	53.3	11.2	
27	27.1			6.29	32.4	7.25	37.6	8.29	40.2	8.85	42.8	9.42	48.0	10.6	53.3	12.0	53.3	12.0	
29	27.1			6.63	32.4	7.65	37.6	8.77	40.2	9.36	42.8	9.98	48.0	11.3	53.3	12.7	53.3	12.7	
31	27.1			6.98	32.4	8.07	37.6	9.27	40.2	9.90	42.8	10.6	48.0	12.0	53.3	13.5	53.3	13.5	
33	27.1			7.34	32.4	8.51	37.6	9.79	40.2	10.47	42.8	11.2	48.0	12.7	53.3	14.3	53.3	14.3	
35	27.1			7.72	32.4	8.96	37.6	10.33	40.2	11.1	42.8	11.8	48.0	13.4	53.3	15.1	53.3	15.1	
37	27.1			8.11	32.4	9.44	37.6	10.9	40.2	11.7	42.8	12.5	48.0	14.2	53.3	16.0	53.3	16.0	
39	27.1			8.52	32.4	9.93	37.6	11.5	40.2	12.3	42.8	13.2	48.0	15.0	53.3	17.0	53.3	17.0	
50	33.50			°CDB	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW
				10	22.6	5.11	27.0	5.62	31.3	6.16	33.5	6.44	35.7	6.72	40.0	7.31	44.4	7.92	44.4
		12	22.6	5.16	27.0	5.68	31.3	6.23	33.5	6.51	35.7	6.80	40.0	7.40	44.4	8.02	44.4	8.02	
		14	22.6	5.20	27.0	5.73	31.3	6.29	33.5	6.58	35.7	6.88	40.0	7.49	44.4	8.12	44.4	8.12	
		16	22.6	5.24	27.0	5.79	31.3	6.36	33.5	6.66	35.7	6.96	40.0	7.59	44.4	8.24	44.4	8.24	
		18	22.6	5.29	27.0	5.85	31.3	6.44	33.5	6.74	35.7	7.05	40.0	7.69	44.4	8.35	44.4	8.35	
		20	22.6	5.34	27.0	5.91	31.3	6.51	33.5	6.82	35.7	7.14	40.0	7.79	44.4	8.47	44.4	8.47	
		21	22.6	5.37	27.0	5.94	31.3	6.55	33.5	6.86	35.7	7.19	40.0	7.85	44.4	8.53	44.4	8.53	
		23	22.6	5.42	27.0	6.01	31.3	6.63	33.5	6.95	35.7	7.28	40.0	7.96	44.4	8.69	44.4		