

RQYQ48PY1		TC: Total Capacity: kW ; PI: Power Input: kW (compressor + outdoor fan motor)													
Combination (%)	Capacity index (kW)	Outdoor air temp.		Indoor air temperature: °CDB											
				16.0		18.0		20.0		21.0		22.0		24.0	
				TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI
90%	118,35 kW	°CDB	°CWB	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW
		-19.8	-20.0	65.8	24.8	65.6	26.7	65.3	28.6	65.2	29.6	65.1	30.5	64.9	32.5
		-18.8	-19.0	69.2	26.6	69.0	28.4	68.8	30.2	68.6	31.1	68.5	32.0	68.3	33.8
		-16.7	-17.0	76.2	29.6	75.9	31.3	75.7	32.9	75.6	33.7	75.4	34.6	75.2	36.2
		-13.7	-15.0	83.2	32.2	82.9	33.7	82.7	35.2	82.6	35.9	82.4	36.7	82.2	38.2
		-11.8	-13.0	90.2	34.4	90.0	35.7	89.7	37.1	89.6	37.8	89.5	38.5	89.3	39.8
		-9.8	-11.0	97	36.2	97	37.5	97	38.8	97	39.4	97	40.0	96	41.3
		-9.5	-10.0	101	37.1	101	38.3	100	39.5	100	40.1	100	40.7	100	41.9
		-8.5	-9.1	104	37.8	104	38.9	104	40.1	104	40.7	104	41.3	103	42.5
		-7.0	-7.6	110	38.8	109	40.0	109	41.1	109	41.6	109	42.2	109	43.3
		-5.0	-5.6	117	40.1	117	41.2	117	42.2	116	42.7	116	43.3	116	44.3
		-3.0	-3.7	124	41.2	124	42.2	124	43.2	123	43.7	123	44.2	118	42.1
		0.0	-0.7	135	42.7	135	43.6	135	44.5	131	42.8	126	41.1	118	37.8
		3.0	2.2	146	44.0	144	43.6	135	40.4	131	38.9	126	37.4	118	34.4
		5.0	4.1	152	44.0	144	41.0	135	38.1	131	36.7	126	35.3	118	32.5
		7.0	6.0	152	41.6	144	38.8	135	36.0	131	34.7	126	33.4	118	30.8
		9.0	7.9	152	39.3	144	36.7	135	34.2	131	32.9	126	31.7	118	29.2
		11.0	9.8	152	37.3	144	34.9	135	32.5	131	31.3	126	30.1	118	27.8
		13.0	11.8	152	35.4	144	33.1	135	30.8	131	29.7	126	28.6	118	26.5
		15.0	13.7	152	33.7	144	31.6	135	29.4	131	28.4	126	27.4	118	25.3
80%	105,20 kW	-19.8	-20.0	65.3	28.5	65.1	30.2	64.9	31.9	64.8	32.8	64.7	33.6	64.5	35.3
		-18.8	-19.0	68.8	30.1	68.6	31.7	68.4	33.3	68.2	34.1	68.1	34.9	67.9	36.6
		-16.7	-17.0	75.7	32.8	75.5	34.3	75.3	35.8	75.2	36.5	75.1	37.2	74.8	38.7
		-13.7	-15.0	82.7	35.1	82.5	36.4	82.3	37.8	82.2	38.4	82.1	39.1	81.8	40.4
		-11.8	-13.0	89.8	37.0	89.5	38.3	89.3	39.5	89.2	40.1	89.1	40.7	88.9	41.9
		-9.8	-11.0	97	38.7	97	39.8	96	40.9	96	41.5	96	42.1	96	43.2
		-9.5	-10.0	101	39.4	100	40.5	100	41.6	100	42.1	100	42.7	100	43.8
		-8.5	-9.1	104	40.1	104	41.1	103	42.2	103	42.7	103	43.2	103	44.3
		-7.0	-7.6	109	41.0	109	42.0	109	43.0	109	43.5	109	44.0	105	42.6
		-5.0	-5.6	117	42.2	116	43.1	116	44.0	116	44.5	112	42.8	105	39.3
		-3.0	-3.7	124	43.1	123	44.0	120	43.1	116	41.4	112	39.8	105	36.6
		0.0	-0.7	135	44.5	128	41.7	120	38.7	116	37.2	112	35.8	105	33.0
		3.0	2.2	135	40.6	128	37.9	120	35.2	116	33.9	112	32.6	105	30.1
		5.0	4.1	135	38.3	128	35.7	120	33.2	116	32.0	112	30.8	105	28.5
		7.0	6.0	135	36.2	128	33.8	120	31.5	116	30.3	112	29.2	105	27.0
		9.0	7.9	135	34.3	128	32.1	120	29.9	116	28.8	112	27.8	105	25.7
		11.0	9.8	135	32.6	128	30.5	120	28.4	116	27.4	112	26.5	105	24.5
		13.0	11.8	135	30.9	128	29.0	120	27.1	116	26.1	112	25.2	105	23.4
		15.0	13.7	135	29.5	128	27.7	120	25.9	116	25.0	112	24.1	105	22.4
		70%	92,05 kW	-19.8	-20.0	64.9	32.3	64.7	33.8	64.5	35.2	64.4	36.0	64.3	36.7
-18.8	-19.0			68.3	33.6	68.1	35.1	67.9	36.5	67.8	37.2	67.8	37.9	67.6	39.3
-16.7	-17.0			75.2	36.0	75.0	37.3	74.9	38.6	74.8	39.2	74.7	39.9	74.5	41.1
-13.7	-15.0			82.2	38.0	82.0	39.2	81.9	40.4	81.8	40.9	81.7	41.5	81.5	42.7
-11.8	-13.0			89.3	39.7	89.1	40.8	88.9	41.8	88.8	42.4	88.7	42.9	88.6	44.0
-9.8	-11.0			96	41.2	96	42.1	96	43.1	96	43.6	95.9	44.1	91.5	42.1
-9.5	-10.0			100	41.8	100	42.8	100	43.7	100	44.2	98.3	43.8	91.5	40.2
-8.5	-9.1			103	42.4	103	43.3	103	44.2	102	43.8	98.3	42.1	91.5	38.7
-7.0	-7.6			109	43.2	109	44.1	105	42.8	102	41.1	98.3	39.5	91.5	36.3
-5.0	-5.6			116	44.2	112	42.5	105	39.5	102	38.0	98.3	36.5	91.5	33.6
-3.0	-3.7			118	42.4	112	39.6	105	36.8	102	35.4	98.3	34.0	91.5	31.4
0.0	-0.7			118	38.1	112	35.6	105	33.1	102	31.9	98.3	30.7	91.5	28.4
3.0	2.2			118	34.7	112	32.5	105	30.3	102	29.2	98.3	28.1	91.5	26.0
5.0	4.1			118	32.8	112	30.7	105	28.6	102	27.6	98.3	26.6	91.5	24.6
7.0	6.0			118	31.0	112	29.1	105	27.1	102	26.2	98.3	25.3	91.5	23.4
9.0	7.9			118	29.5	112	27.6	105	25.8	102	24.9	98.3	24.0	91.5	22.3
11.0	9.8			118	28.1	112	26.3	105	24.6	102	23.8	98.3	22.9	91.5	21.3
13.0	11.8			118	26.7	112	25.1	105	23.5	102	22.7	98.3	21.9	91.5	20.4
15.0	13.7			118	25.5	112	24.0	105	22.5	102	21.7	98.3	21.0	91.5	19.5
60%	78,90 kW			-19.8	-20.0	64.4	36.0	64.3	37.3	64.1	38.6	64.0	39.2	63.9	39.8
		-18.8	-19.0	67.8	37.2	67.7	38.4	67.5	39.6	67.4	40.2	67.4	40.8	67.2	42.0
		-16.7	-17.0	74.8	39.2	74.6	40.3	74.4	41.4	74.4	42.0	74.3	42.5	74.1	43.6
		-13.7	-15.0	81.8	40.9	81.6	41.9	81.4	42.9	81.4	43.4	81.3	43.9	78.4	42.6
		-11.8	-13.0	88.8	42.4	88.7	43.3	88.5	44.2	87.1	43.6	84.2	41.9	78.4	38.5
		-9.8	-11.0	96	43.6	95.8	44.5	90.0	41.2	87.1	39.7	84.2	38.1	78.4	35.1
		-9.5	-10.0	100	44.2	95.8	42.5	90.0	39.4	87.1	37.9	84.2	36.5	78.4	33.6
		-8.5	-9.1	102	43.8	95.8	40.8	90.0	37.9	87.1	36.5	84.2	35.1	78.4	32.3
		-7.0	-7.6	102	41.1	95.8	38.3	90.0	35.6	87.1	34.3	84.2	33.0	78.4	30.5
		-5.0	-5.6	102	37.9	95.8	35.4	90.0	33.0	87.1	31.8	84.2	30.6	78.4	28.3
		-3.0	-3.7	102	35.4	95.8	33.0	90.0	30.8	87.1	29.7	84.2	28.6	78.4	26.5
		0.0	-0.7	102	31.9	95.8	29.9	90.0	27.9	87.1	26.9	84.2	25.9	78.4	24.0
		3.0	2.2	102	29.2	95.8	27.3	90.0	25.5	87.1	24.7	84.2	23.8	78.4	22.1
		5.0	4.1	102	27.6	95.8	25.9	90.0	24.2	87.1	23.4	84.2	22.6	78.4	21.0
		7.0	6.0	102	26.2	95.8	24.6	90.0	23.0	87.1	22.3	84.2	21.5	78.4	20.0
		9.0	7.9	102	24.9	95.8	23.4	90.0	21.9	87.1	21.2	84.2	20.5	78.4	19.1
		11.0	9.8	102	23.8	95.8	22.3	90.0	21.0	87.1	20.3	84.2	19.6	78.4	18.3
		13.0	11.8	102	22.7	95.8	21.3	90.0	20.0	87.1	19.4	84.2	18.7	78.4	17.5
		15.0	13.7	102	21.7	95.8	20.4	90.0	19.2	87.1	18.6	84.2	18.0	78.4	16.8
		50%	65,75 kW	-19.8	-20.0	64.0	39.7	63.8	40.8	63.7	41.9	63.6	42.4	63.6	42.9
-18.8	-19.0			67.4	40.7	67.3	41.7	67.1	42.7	67.0	43.2	67.0	43.7	65.4	43.2
-16.7	-17.0			74.3	42.4	74.2	43.3	74.0	44.3	72.6	43.4	70.2	41.7	65.4	38.3
-13.7	-15.0			81.3	43.9	79.8	43.5	75.0	40.4	72.6	38.9	70.2	37.3	65.4	34.4
-11.8	-13.0			84.6	42.1	79.8	39.3	75.0	36.5	72.6	35.2	70.2	33.8	65.4	31.2
-9.8	-11.0			84.6	38.3	79.8	35.8	75.0	33.3	72.6	32.1	70.2	30.9	65.4	28.5
-9.5	-10.0			84.6	36.7	79.8	34.3	75.0	31.9	72.6	30.7	70.2	29.6	65.4	27.4
-8.5	-9.1			84.6	35.3	79.8	33.0	75.0	30.7	72.6	29.6	70.2	28.5	65.4	26.4
-7.0	-7.6			84.6	33.2	79.8	31.1	75.0	29.0	72.6	27.9	70.2	26.9	65.4	24.9
-5.0	-5.6			84.6	30.8	79.8	28.8	75.0	26.9	72.6	26.0	70.2	25.1	65.4	23.2
-3.0	-3.7			84.6	28.8	79.8	27.0	75.0	25.2	72.6	24.3	70.2	23.5	65.4	21.8
0.0	-0.7			84.6	26.1	79.8	24.5	75.0	22.9	72.6	22.2	70.2	21.4	65.4	19.9
3.0	2.2			84.6	23.9	79.8	22.5	75.0	21.1	72.6	20.4	70.2	19.7	65.4	18.4
5.0	4.1			84.6	22.7	79.8	21.4	75.0	20.1	72.6	19.4	70.2	18.8	65.4	17.5
7.0	6.0			84.6	21.6	79.8	20.3	75.0	19.1	72.6	18.5	70.2	17.9		