AGICITY ALTO

AGICITY ALTO 7 KVA

Contact
Sales contact
contact.agicity@nexans.com

Nexans Ref.: 304020E

1 plug socket charging station, 7 kW, wall or pedestal mounted. AGICITY ALTO ev-charger is is ideal for equipping a parking space in collective housing, businesses and establishments open to the public that do not require remote management.

DESCRIPTION

AGICITY ALTO is the most economical solution in the AGICITY range by Nexans.

Its polycarbonate design allows it to combine lightness ans robustness. Its small footprint allows installation with reduced wall or floor space, indoors and outdoors.

Configuration

- Power supply: from 1x 3.7kW to 1x 22kW
- · Electrical protections: not integrated
- Plug socket: Lockable Type 2S
- · Metering: none
- Identification: optional RFID reader (ISO 14443A, ISO 14443B, MiFare)

Charge access

- Plug & charge
- · Local user authentication through RFID
- · Offline authorization by badges



STANDARDS

International IEC 61851; IEC 62196

National NF C15-100

CHARACTERISTICS

Construction characteristics	
Plug socket	Type 2S Lockable
RFID system	None
Charging mode	Mode 3
Colour	Light grey RAL 7035
Material	Polycarbonate
Number of charging points	1
Dimensional characteristics	
Approximate net weight	4.5 kg
Electrical characteristics	
Power	7 kVA
Current type	Single phase
Mechanical characteristics	
IK Rating	10
Usage characteristics	
IP Rating	IP55

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Nexans indicative only and shall not be binding on Nexans or be treated as constituting a representation on the part of Nexans.



Page 1 / 2





AGICITY ALTO 7 KVA

Contact

Sales contact contact.agicity@nexans.com

Usage characteristics

Operating temperature, range

-25 ... 55 °C

ALTO DETAILS









