THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.



*NOTE: PICTURE FOR REFERENCE ONLY.

Punch Drive Adapter for CT-2920/CCP, CT-3001/CCP, CT-920CH/CCP

NOTES, UNLESS OTHERWISE SPECIFIED:

• Punch drive adapters holes to be punched in sheet metal with minimal burrs. Go to www.panduit.com for more information.

Size Chart:

Consult table below to select appropriate punch adapter required for the appropriate hole size, sheet metal thickness and Panduit Tool:

Panduit P/N	Largest Hole Size	Thickest Sheet Metal	Compatible with Panduit Tool(s)	
CD-2001-PDA	2" (50mm)	10 Gauge (3.42 mm)	CT-3001/CCP	
	Conduit Size	mild steel		
CD-920-PDA	5-5/8" (144mm)	10 Gauge (3.42 mm),	CT-2920/CCP, CT-920CH/CCP	
	Dia. Round	mild steel		

Technical Information:

Panduit P/N	Weight	Punch Adapter Dims
CD-2001-PDA	4.6 lbs (2.1 kg)	6.6" L X 3.3" H X 2.1" W
	, , ,	[168 L X 83 H X 54 W] mm
CD-920-PDA	5.1 lbs (2.3 kg)	7.5" L X 3.3" H X 2.1" W
	, , ,	[191 L X 83 H X 54 W] mm

Each box contains one punch adapter, one 3/4" threaded stud, one pilot hole drill and one spacer. Can be used with standard Greenlee Hole Punches.

							CD-2001-PDA and CD-920-PDA Punch Drive Adapters	
							CUSTOMER DRAWING	
							O0084SMU_DC/00	T
							UNLESS OTHERWISE SPECIFIED, MATERIAL: DIMENSIONAL TOLERANCES ARE:	
01	10-14-16	ACC	RAKL	JADE	CORRECTED PART NUMBERS	010819	(.x) ± (.xxx) ± (.xx) ±	
00	9-12-16	ACC	BKA	JADE	DRAWING RELEASED	010062	THIRD ANGLE PROJECTION DRAWING NUMBER: 00084SMU_DC	
REV	DATE	ВҮ	СНК	APR	DESCRIPTION	ECN	DRAWN BY: DATE: CHK SCALE NONE SHT 1 OF 1 B	_