



A. Cable Ties

B. Stainless Steel







F. Part Number Index

Uni-Die ™ Quad-Point, Dieless, Remote Hydraulic, 6.2 Ton, Crimp Head

- Quad-point indent crimping feature with patented centering system, no dies required
- Requires 10,000 psi hydraulic pump system. Panduit CT-902HP pump and accessories available see page E.31
- Incorporates Parker type quick-connect fittings to ease installation and save time
- Light weight due to high quality aluminum crimp head, results in lightweight tool and ease of operation
- Closed head with bolt interlock, flip top style.
- Provides UL Listed and CSA Certified wire range-taking capability on Panduit[®] Pan-Lug[™] Copper Lugs and Splices, minimizes connector inventory and saves cost



CT-980CH



Part Number	Part Description	Std. Pkg. Qty.
CT-980CH	Remote hydraulic Uni-Die [™] dieless crimp head provides UL Listed or Recognized and CSA Certified terminations of Panduit [®] • Pan-Lug [™] Copper Compression Lugs and Splices for #4 AWG – 750 kcmil copper code conductor. • Pan-Lug [™] Aluminum compression lugs and splices for #4 AWG – 500 kcmil code conductor Use with Panduit CT-902HP hydraulic pump and CT-900HPH 10' hydraulic hose see page E.31. Specifications: Output: 6.2 tons Jaw opening: 1.46" Weight: 6.2 lbs. (2.8 kg.) Length: 12.6" (321 mm) Height: 5.2" (132 mm) Width: 2.9" (74 mm) Warranty: 2 years CT-980CH includes: • Heavy duty carrying bag • 10 solder slug gauges and Go/No-Go gauge	1

See tool charts on pages E.47 - E.95 for selection of crimping dies and number of crimps used with specific tool and connector combinations.

Accessories for CT-980 Hydraulic Crimping Tools





CG-980SS

Part Number	Part Description	Std. Pkg. Qty.
CG-980SS	Tool calibration solder slugs (10 pieces) (Normally included with tool)	1