# **Mini-Com® Faceplate Frames and Inserts**



# specifications

Faceplate frames shall be available in single and double gang versions and shall accept a variety of inserts. Executive design faceplate frames shall have a curved appearance and include labels and label covers. Classic design faceplate frames shall have a flush appearance and include color matched mounting screws. Inserts shall be available in sloped, sloped shuttered, and flat versions, and accept all modules for increased design flexibility. Modules shall be accessible from the front for easy moves, adds, and changes.



# technical information

Mounting options:	Faceplate frames are compatible with wall board adapters (MWBA1 and MWBA-2G); single or double junction boxes; raceway mounting brackets
Packaging:	Executive series faceplate frames include two labels, two label covers; all faceplate frames include 1" long #6-32 slotted pan head screws with non-threaded lead point

# key features and benefits

· · · · · · · · · · · · · · · · · · ·		
Modular	Faceplate frames accept all Panduit Inserts; inserts accept all Mini-Com <sup>®</sup> Modules for design flexibility	
Front access	Mini-Com <sup>®</sup> Modules are accessible from the front for easy moves, adds, and changes	
Sloped versions	Provide additional bend radius control to protect cable	
Shuttered versions	Integrated shuttered door keeps dust and debris out of unmated Mini-Com <sup>®</sup> Jack Modules	
Identification	Executive series faceplate frames can be clearly identified with labels; classic series faceplate frames can be clearly identified with optional adhesive labels; sloped shuttered version available with label option; Mini-Com <sup>®</sup> Modules can be clearly identified with optional icons	

#### Mini-Com<sup>®</sup> Faceplate Frames and Inserts

Executive Series Fa	ceplate Frames				
Dauble neme	CBE**Y				
Double gang:	CBE**-2GY				
Classic Series Faceplate Frames					
Single gang:	CB**^				
Double gang:	CB**-2G^				
1/2 Size Inserts					
Sloped:	CHS2**-X				
Sloped, shuttered:	CHS1S**-X				
Sloped, shuttered:	CHS2S**-X				
Sloped, shuttered with labels:	CHLS2S**-X				
Sloped, recessed:	CHSRE2**-X				
Flat:	CHF2**-X				
Flat. Blank:	CHF2 -X CHB2**-X				
1/3 Size Inserts					
Flat, 1 port:	CHF1M**-X				
Flat, 2 ports:	CHF2M**-X				
Blank:	CHB2M**-X				
1/3 Size D-Subminiature Inserts					
9-pin, female to					
female coupler:	CHD9C**Y				
15-pin, female to female coupler:	CHD15HDC**Y				
15-pin, DB connector					
15-pill, DB connect					
mounted to a					
mounted to a circuit board:	CHD15HDSC**Y				
mounted to a circuit board: **To designate color, add	suffix IW (Off				
15-pin, female to female coupler: CHD15HDC**Y 15-pin, DB connector mounted to a					

White), El (Electric Ivory), IG (International Gray), AW (Arctic White), WH (White), or BL (Black). Not all parts are available in all colors;

visit www.panduit.com for a complete listing of available colors.


<sup>^</sup>Frames CB<sup>\*\*</sup> and CB<sup>\*\*</sup>-2G require the following clearance when installing over a mud ring: CB<sup>\*\*</sup>=2.80"x1.74" CB<sup>\*\*</sup>-2G=2.83"x3.63"


Visit www.panduit.com for complete offering of copper, fiber, and audio/video modules.


## applications


The combination of faceplate frames and inserts provide the design flexibility when installing connectivity in single or double gang junction boxes, wallboard adapters, and raceway mounting brackets. A variety of inserts enable front access to connectivity for easy moves, adds, and changes. Sloped inserts are ideal for installations which require additional bend radius control and blank inserts allow for future growth. All inserts accept Mini-Com<sup>®</sup> Modules for copper, fiber, and audio/video applications.

## executive series faceplate frames













## classic series faceplate frames










### inserts




1/2 Sloped Insert




1/2 Blank Insert




1/2 Sloped, Shuttered with or without Labels



1/3 Flat Insert




1/2 Flat Insert



1/3 Blank Insert



1/2 Sloped Recessed



1/3 One Position Insert

Dimensions are in inches [Dimensions in brackets are metric].

#### WORLDWIDE SUBSIDIARIES AND SALES OFFICES

PANDUIT CANADA Markham, Ontario cs-cdn@panduit.com Phone: 800.777.3300

PANDUIT EUROPE LTD. London, UK cs-emea@panduit.com Phone: 44.20.8601.7200

PANDUIT SINGAPORE PTE. LTD. Republic of Singapore cs-ap@panduit.com Phone: 65.6305.7575 PANDUIT JAPAN P Tokyo, Japan G cs-japan@panduit.com c Phone: 81.3.6863.6000 P

PANDUIT LATIN AMERICA Guadalajara, Mexico cs-la@panduit.com Phone: 52.33.3777.6000 PANDUIT AUSTRALIA PTY. LTD. Victoria, Australia cs-aus@panduit.com Phone: 61.3.9794.9020

For a copy of Panduit product warranties, log on to www.panduit.com/warranty

For more information

#### Visit us at www.panduit.com

Contact Customer Service by email: cs@panduit.com or by phone: 800.777.3300 © 2018 Panduit Corp. ALL RIGHTS RESERVED. **0TSP38--WW-ENG** Replaces WW-0TSP15 12/2018