



THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.



PANDUIT PART NUMBER	WEIGHT
NKA6XPPG24Y	1.26 lb (572.73 g)

- NOTES:
- SEE CURRENT CATALOG FOR VARIOUS APPLICATIONS AS WELL AS OPTIONAL ICONS.
  - MATERIAL:  
 PANEL HOUSING: STEEL  
 RJ45 MODULES: THERMOPLASTIC RESIN UL94V-0  
 PUNCHDOWN BLOCKS: THERMOPLASTIC RESIN UL94V-0  
 BEZEL ASSEMBLY: THERMOPLASTIC RESIN UL94H-B  
 RETENTION CAP: THERMOPLASTIC RESIN UL94V-0
  - 24 PORT ANGLED PATCH PANEL 8 POSITION 8 WIRE.
  - THE PATCH PANEL IS DESIGNED FOR MOUNTING TO 19" UNIVERSAL RACKS.
  - FOUR (4) 12-24 X 1/2" ROUND HEAD SCREWS ARE PROVIDED FOR FASTENING TO RACKS.
  - DIMENSIONS IN BRACKETS ARE IN METRIC.
  - USE 110 STYLE TERMINATION TOOL FOR PUNCHDOWN.
  - RETENTION CAPS (ONE PER CONNECTOR) PROVIDED FOR SNAP-IN ON TERMINATED CONNECTORS.



PART NUMBER	SEE CHART	PRODUCT SPEC/PKG SPEC	N/A			
I.I. NUMBER	N/A	WORK INSTRUCTION	N/A			
TITLE						
<b>NETKEY CAT6A 24 PORT ANGLED PATCH PANEL</b>						
CUSTOMER DRAWING						
ITEM REVISION NAME		<b>PANDUIT</b>				
M02088AQ/01						
DATASET FILE NAME						
M02088AQ_DC46/01A		MATERIAL:				
UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE: IN (mm)		SEE NOTE 2				
.x ± .1 [ 2.54 ]      .xxx ± .005 [ .127 ] .xx ± .01 [ .25 ]      ANGLES ± 5 °						
DRAWN BY		DRAWING NUMBER:				
BJN		02088-46				
DATE		THIRD ANGLE PROJECTION				
2-4-15						
REV	DATE	BY	CHK	SCALE	SHT 1 OF 1	SIZE
				.25:1		A

REV	DATE	BY	CHK	APR	DESCRIPTION	ECN
1	10-1-18	BAME	KRKE	MMR	A. REMOVED M6 SCREWS	M09000HW
R	2-4-15	BJN	MDJR	LPH	RELEASED TO PRODUCTION	02088-46

D10100DA/14

2

1

2

1