THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP. NOTES, UNLESS OTHERWISE SPECIFIED: 4.05 (103) = Panduit Tool Number BT2HT is used to install - 7.64 (194) coated and uncoated Pan-Steel MS Series strap 3.09 (78) and buckles in widths of 3/8" (9.5mm), 1/2" (12.7mm); and 5/8" (15.9mm). (25)(1.6)THIS TOOLS' FEATURES INCLUDE: • Single handle trigger for fast installation • Cable strap side entry for immediate positioning of strap and tool • Adjustable controlled or Installer controlled (176)tension • Cut-off capability with the cutter and cutter handle - 1.33 (34) • Easy removal of excess strap. • Multi-position rear handle allows access to tight -.74 (19) • Features to release & remove strap from tool before cutting. CABLE TIE CROSS-SECTION CODE: MS Series straps and buckles. TOOL WEIGHT: 2.6 lbs. (41.6 oz.) Dimensions shown in parenthesis are metric. 3.46 (88) F:\wrkgrp\rvusers\ENGR DOCS\ CUSTDWG/TB25755A01_01 BT2HT.doc

¥							BT2HT CUSTOMER DRAWING CUSTOMER DRAWING					
							TB25755A01_01 UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE: (.x) ± (.xxx) ± (.xx) ± ANGLES ±				PAND	UIT
			2/							RE:	MATERIAL:	
01	7-28-14	BLR	pozli		REDRAWN; NEW TEMPLATE, UPD BRANDING	4765	THIRD ANGLE PROJECTION				DRAWING NUMBER: TB25755A01	
REV	DATE	вү	снк	APR	DESCRIPTION	ECN	DRAWN BY: BLR	DATE: 7-28-14	CHK BJPU	SCALE	- 1	SIZE