| | N A RESTRICTED BASIS AND IS NOT TO BE L | ISED IN ANY WAY DETRIMENTA | L ТО ТІ | HE INTI | ERESTS OF PANDUIT CORP. |
|--|--|----------------------------|-------------------|----------------------|---|
| Material | High Conductivity Seamless Copper Tube | | | | |
| Plating | Electro-Tin | | | | |
| Wire Size | 8 AWG | | | | .37 R Ref |
| Wire Type | Stranded Copper; Class B: Compact, Compressed or Concentric, Class C: Concentric | | \uparrow | 8 STR CU LCC8-14A | Color coded barrel markings |
| Wire Strip Length | 3/4 in. | | \mathcal{V} | 8 STF LCC8 | |
| Stud Size | 1/4 in. |] <u>*</u> | | | |
| UL Listed Wire Connector | Yes, for applications up to 35kv. Consult cable manufacturer for voltage stress relief instructions with applications greater than 2000 volts. | .25±.04 — | • | .63±.0 | 02 → .27±.02 DIA (2) PLS 2.16±.06 → |
| UL Temperature Rating | 90°C | | | | |
| C.S.A Certified Wire Connector | Yes | | | | |
| Panduit Color Code on Barrel | RED | | | | |
| Panduit Die Index No on Barrel | p. P21 | | | | 70±.04 - Beveled wire entry |
| Alternate Industry Die Index No. () on Barrel | N/A | | | | .18±.01 .27±.01 |
| CERTIF | ED LISTED Wire Connector | .07±.01 | | | |
| | | | | | CORP. TINLEY PARK, ILLINOIS |
| 7/10 | | | DOF | DOC | LCC8-14A-L |
|)1 7/12 JHNU JHN EV DATE BY CHI | | N10883BC-LCC8-14A-CUST | RGB - R | RGB SUP | SCALE DRAWING NO / CAD FILE |
| | | | | | N/A LCC8-14A-CUST |