



2



1

THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.

FINISHED GOOD PART NUMBER	FINISHED GOOD DESCRIPTION	COLOR	INPUT CORD LENGTH	WEIGHT
P24E01G	G6 MS PDU,32AMP,(20) C13,(4) C19,IEC 60309 2P 3W 6H IP44-3M,TOP FED,BLACK	BLACK (RAL 9005)	3M(+254MM-127MM) 10'[+10"-5"]	6.5kg

B

B

A

A

WE ASK THAT YOU CHECK FULLY THE DIMENSIONS, NOTES, AND SIGN THE CLIENT SIGNATURE BOX. THE JOB WILL NOT PROGRESS WITHOUT SIGNED APPROVAL. PLEASE DO NOT DELAY IN RETURNING PROOF AS IT WILL AFFECT DELIVERY		SIGN																		
		DATE																		
		PRINT																		
TITLE INTELLIGENT SERIES PDU P24E01G-XXYZ CUSTOMER DRAWING																				
ITEM REVISION NAME:		<b>PANDUIT</b>																		
DATASHEET FILE NAME:																				
UNLESS OTHERWISE SPECIFIED DIMENSIONAL TOLERANCE ARE: mm [IN]		MATERIAL/COLOR: N/A																		
<table border="0"> <tr> <td></td> <td>Tolerance(mm)</td> <td></td> </tr> <tr> <td>0&lt;l&lt;50</td> <td>±0.5</td> <td></td> </tr> <tr> <td>50&lt;l&lt;250</td> <td>±1.0</td> <td></td> </tr> <tr> <td>250&lt;l&lt;500</td> <td>±1.5</td> <td></td> </tr> <tr> <td>500&lt;l&lt;1000</td> <td>±2.5</td> <td></td> </tr> <tr> <td>1000&lt;l&lt;2000</td> <td>±4.0</td> <td></td> </tr> </table>			Tolerance(mm)		0<l<50	±0.5		50<l<250	±1.0		250<l<500	±1.5		500<l<1000	±2.5		1000<l<2000	±4.0		DRAWING NUMBER: P24E01G-XXYZ_DC
	Tolerance(mm)																			
0<l<50	±0.5																			
50<l<250	±1.0																			
250<l<500	±1.5																			
500<l<1000	±2.5																			
1000<l<2000	±4.0																			
DRAWN BY	DATE	SCALE																		
LWB	08/30/2023	NONE																		
CHK	SCALE																			
SEAN	NONE																			
SHT 2 OF 2		SCALE B																		

REV	DATE	BY	CHK	APR	DESCRIPTION	ECN
00A	08/30/2023	LWB	CSH	MJD	INITIAL RELEASE	P24E01G-XXYZ

2



1