

DP4300H and DP4600H Thermal Transfer Desktop Printers

The DP4300H and DP4600H Thermal Transfer Desktop Printers produce high-quality print-on-demand labels for a wide range of applications for electrical and network infrastructure. These high-volume printers are ideal for OEM, MRO, Construction, Data Center, and Enterprise labeling.

Quickly create self-laminating labels, heat shrink labels, and marker plates for wire and cable marking. Easily print raised panel labels, electrical component labels, network component labels, arc flash labels, and safety signs for equipment and facility identification.

With very fast printing speed, rugged design, color touchscreen display, wide variety of label and ribbon options, and Easy-Mark Plus™ Labeling Software included, the DP4300H and DP4600H are ideal for any high-volume label printing needs.



KEY FEATURES AND BENEFITS

High volume printing:	Rugged, durable design for printing in all environments
Fast label production:	Up to 11.8 inches per second print speed
Up to 600 dots per inch (dpi) print resolution:	Superior print quality for all type of labels
Large color touchscreen display:	Easy to use screen with intuitive interface
Quick and easy loading of label and ribbon media:	Minimize setup time to switch label and ribbon rolls, maximize uptime
Easy-Mark Plus™ Labeling Software included with printer:	No additional investment for labeling software, print right out of the box
USB, ethernet, and serial connectivity:	Increased flexibility to quickly connect to any computer

TECHNICAL PERFORMANCE INFORMATION

	DP4300H	DP4600H
Print method :	300 dpi thermal transfer	600 dpi thermal transfer
Print speed (maximum) :	11.8" (300mm) per second	5.9" (150mm) per second
Maximum print width:	4.16" (105.7mm)	
Maximum print length:	78.74" (2.0m)	39.37" (1.0m)
Weight:	22 lbs. (10 kg)	
Size (width x height x depth):	9.9" x 11.3" x 18.1" (252mm x 288mm x 460mm)	
Connectivity:	USB, Ethernet, Serial	
Regulatory Compliance:	FCC, cUL, ICES3, CE, UKCA, CB, CCC, KC, BSMI, RCM, ECAS, CoC	
Compatibility:	Windows 10, 11^	

^Windows is a registered trademark of Microsoft Corp. in the United States and/or other countries.

ORDERING INFORMATION

Part Number	Part Description	Std. Pkg. Qty.
DP4300H	300 dpi printer; includes printer, Panduit Easy-Mark Plus™ Labeling Software, RHEH4BL black hybrid ribbon, USB cable, quick start guide, and U.S. power cord; for use in North America.	1
DP4600H	600 dpi printer; includes printer, Panduit Easy-Mark Plus™ Labeling Software, RHEH4BL black hybrid ribbon, USB cable, quick start guide, and U.S. power cord; for use in North America.	

Thermal Transfer Desktop Printers

DP4300HD Two-Sided Thermal Transfer Desktop Printer

The DP4300HD Two-Sided Thermal Transfer Desktop Printer enables printing on both sides of two-side printable labels at the same time. This functionality saves 50% of the time required to print on both sides compared to using a single-sided printer.

The DP4300HD printer produces high-quality print-on-demand labels for wire and cable marking applications using Panduit Two-Sided Heat Shrink Labels. This solution is ideal for labeling in OEM, MRO, and Construction. With the included Panduit Easy-Mark Plus™ Labeling Software, designing and printing labels is quick and easy.

Panduit offers a wide range of compatible labeling options, including Military Grade Two-Sided Heat Shrink Labels, Halogen-Free Two-Sided Heat Shrink Labels, and continuous heat shrink label material.



KEY FEATURES AND BENEFITS

Rugged, durable design:	Ideal printer for high volume labeling applications, industrial production, and harsh environments
Print two-sided heat shrink labels in one pass:	Maximize printing efficiency, cut printing time for two-sided labels by 50%
300 dots per inch (dpi) print resolution:	Provides crisp, clear, legible print for best label appearance
Large color touchscreen display:	Easy to use screen with intuitive interface
Quick and easy loading of label and ribbon media:	Minimize setup time to switch label and ribbon rolls, maximize uptime
Easy-Mark Plus™ labeling software included with printer:	No additional investment for labeling software, print right out of the box
USB, ethernet, and serial connectivity:	Increased flexibility to quickly connect to any computer

TECHNICAL PERFORMANCE INFORMATION

Print method:	300 dpi thermal transfer
Print speed (maximum) :	5.9" (150mm) per second
Maximum print width:	4.16" (105.7mm)
Label types:	Military Grade Two-Sided Heat Shrink, Halogen Free Two-Sided Heat Shrink, Continuous Heat Shrink
Weight:	46 lbs. (21 kg)
Size (width x height x depth):	9.8" x 15.6" x 23.4" (248mm x 395mm x 594mm)
Connectivity:	USB, Ethernet, Serial
Regulatory compliance:	FCC, cUL, ICES3, CE, UKCA, CB
Compatibility:	Windows 10, 11 [^]

[^]Windows is a registered trademark of Microsoft Corporation in the United States and/or other countries

ORDERING INFORMATION

Part Number	Part Description	Std. Pkg. Qty.
DP4300HD	300 dpi printer; includes printer, Panduit Easy-Mark Plus Labeling Software, 2 rolls of RHEH4BL black hybrid ribbon, USB cable, quick start guide, and U.S. power cord; for use in North America.	1

For more information visit:
www.panduit.com

Thermal Transfer Desktop Printers

THERMAL TRANSFER RIBBONS

Part Number	Part Description	Width In. (mm)	Length ft (m)	Std. Pkg Qty.	
RHEH4BL	Black hybrid thermal transfer ribbon. Use with heat shrink, self-laminating, Turn-Tell®, and vinyl cloth.	4.33 (110.0)	1181.0 (363.0)	1	
RHER4BL	Black resin thermal transfer ribbon. Use with polyester labels, continuous vinyl tape, marker plates, and raised panel labels.				
RHER4WH	White resin thermal transfer ribbon. Use with polyester labels, continuous vinyl tape, marker plates, and raised panel labels.	4.50 (114.3)			
RHER4BL-A	Black resin thermal transfer ribbon. Use with high-temperature marker plates.	4.33 (110.0)	1345.0 (410.0)		
RHER4BL-C	Black resin thermal transfer ribbon. Use with fluid resistant heat shrink markers and white polyimide labels.				
RHER4BL-E	Black resin thermal transfer ribbon. Use with standard marker plates and component labels for extra durability for harsh environments.				

DESKTOP PRINTER ACCESSORIES

Part Number	Part Description
DP4X00H-CUT	Optional power/automatic cutter for DP4300H, DP4600H, and DP4300HD thermal transfer desktop printers.
DP4X00H-PCUT	Optional power/automatic perforation cutter for DP4300H, DP4600H, and DP4300HD thermal transfer desktop printers.
TDP43ME-RS	External label roll stand for use with continuous tapes
PTR-CLN	Printer cleaning kit—contains (1) cleaning pen, (8) cleaning solution soaked wipes, (8) foam swabs pre-saturated with cleaning solution.

DESKTOP LABELING APPLICATIONS




Wire and Cable
Marking



Terminal Block
Labeling



Electrical Infrastructure
Labeling



Marker Plates



Raised Panel Labels




Network Infrastructure
Labeling



2-Sided Heat
Shrink Labels



Pipe Marking




Turn-Tell® Labels



Safety Signs



Electrical Hazard
Labels



Flag Labels

RELATED PRODUCTS




TDP43ME



PXE™ Mobile Printers



Abrasion Protection



Wiring Duct

WORLDWIDE SUBSIDIARIES AND SALES OFFICES

PANDUIT US/CANADA
Phone: 800.777.3300

PANDUIT EUROPE LTD.
London, UK
Phone: 44.20.8601.7200

PANDUIT SINGAPORE PTE. LTD.
Republic of Singapore
Phone: 65.6305.7575

PANDUIT JAPAN
Tokyo, Japan
Phone: 81.3.6863.6000

PANDUIT LATIN AMERICA
Guadalajara, Mexico
Phone: 52.33.3777.6000

PANDUIT AUSTRALIA PTY. LTD.
Victoria, Australia
Phone: 61.3.9794.9020

For a copy of Panduit product warranties, log on to www.panduit.com/warranty

PANDUIT®

For more information
Visit us at www.panduit.com
Contact Customer Service by email: cs@panduit.com
or by phone: 800.777.3300

© 2024 Panduit Corp.
ALL RIGHTS RESERVED.
IDCB99-SA-ENG
10/2024