ELECTRICAL SOLUTIONS





${\mathfrak c}_{{{\text{LISTED}}}}^{{{\text{US}}}}{{\text{US}}}{{\text{US}}}{{\text{CERTIFIED}}}^{\circ}\text{ Code/Flex Conductor HTAP Kit}$

Type HTWC


- Include all components to make a complete HTAP and cover installation: HTCT HTAP, matching CLRCVR clear cover, and cable ties
- Each HTCT HTAP designed to terminate a wide range of copper code and flex conductor combinations to accommodate a variety of applications
- HTAPs incorporate a unique slotted design that allows for quick and easy installation using supplied Panduit cable ties; saves time
- Matching clear covers are made from high impact plastic and provide high impact strength and 360° viewing of installed HTAP
- Clear covers have a UL 94 V-0 flame rating and an oxygen index of 28 providing self-extinguishing, flame retardant properties
- UL Listed and CSA Certified for applications up to 600 V when crimped with Panduit and specified competitor crimping tools and Panduit crimping dies^
- See page D3.33 for detailed installation instructions




















Part Number	Components		Copper Conductor Size Range AWG (mm²)					Std.
	HTAP Part No.	Clear Cover Part No.	Wire Strand Type	Run	Tap 1	Tap 2	Tap 3	Pkg. Qty.
HTWC6X-6X-1	HTCT6X-6X-1	CLRCVR1-1	Code	#6 – #14 AWG (10 – 2.5)	#6 – #14 AWG (10 – 2.5)	_	_	1
			Flex	#6 – #10 AWG (10 – 2.5)	#6 – #14 AWG (10 – 2.5)		_	
HTWC2-2-1	HTCT2-2-1	CLRCVR2-1	Code	#2 – #6 AWG STR/SOL (25 – 16)	#2 – #6 AWG STR/SOL (25 – 16)	#8 – #14 AWG (6 – 2.5)	#8 – #14 AWG (6 – 2.5)	1
			Flex	#2 – #8 AWG (25 – 10)	#2 – #8 AWG (25 – 10)	#8 – #14 AWG (6 – 2.5)	#8 – #14 AWG (6 – 2.5)	
HTWC250-2-1	HTCT250-2-1	CLRCVR3-1	Code	250 kcmil – #2 AWG (120 – 35)	#2 – #6 AWG STR/SOL (25 – 16)	#8 – #14 AWG (6 – 2.5)		1
			Flex	4/0 – #2 AWG (95 – 35)	#2 – #8 AWG (25 – 10)	#8 – #14 AWG (6 – 2.5)		
HTWC250-250-1	HTCT250-250-1	CLRCVR3-1	Code	250 kcmil – #2 AWG (120 – 35)	250 kcmil – #2 AWG (120 – 35)	_		1
			Flex	4/0 - #2 AWG (95 - 35)	4/0 – #2 AWG (95 – 35)	_	_	

See pages D3.13 - D3.14 for more information on HTAPs and clear covers, including tap sizes and locations. ^Note: HTCT parts are UL Listed and CSA Certified with AWG wire only.

System Overview

B1. **Cable Ties**

B2. Cable Accessories

B3. Stainless Steel Ties

> **C1**. Wiring Duct

C2. Surface Raceway

СЗ. Abrasion Protection

C4. Cable Management

> D1. Terminals

D2. Power Connectors

D3. Grounding Connectors

E1. Labeling Systems

> E2. Labels

E3. Pre-Printed & Write-On Markers

E4. Permanent Identification

E5. Lockout/ Tagout & Safety Solutions

> F. Index