



Product Environmental Profile

**SpaceLogic, Thermostat, FCU, LCD, Modbus, 4P, 240V, XS,
White**




General information

| | |
|-----------------------------------|--|
| Representative product | SpaceLogic, Thermostat, FCU, LCD, Modbus, 4P, 240V, XS, White - TC903-3A4DLMSA |
| Description of the product | To control FAN coil units to match with the setpoint |
| Functional unit | Control during 10 years the ambient temperature in a zone according to a temperature set by the user a range of ambient temperature between 0° and 35°C, with a temperature step of 0.5 °C and characterized by a rated current of up to 30 mA and a current of up to 45 mA when the contact is closed (heating/air conditioning is on) and backlit is ON. |

Constituent materials

Reference product mass 220.6 g including the product, its packaging and additional elements and accessories



| | |
|----------|-------|
| Plastics | 32,0% |
| Metals | 10,6% |
| Others | 57,4% |

Substance assessment

Products of this range are designed in conformity with the requirements of the RoHS directive (European Directive 2011/65/EU of 8 June 2011 and EU 2015/863) and do not contain, or only contain in the authorised proportions, lead, mercury, cadmium, hexavalent chromium flame retardants (polybrominated biphenyls - PBB, polybrominated diphenyl ethers – PBDE, Bis(2-ethylhexyl) phthalate -DEHP, Butyl benzyl phthalate -BBP, Dibutyl phthalate – DBP, Diisobutyl phthalate - DIBP) as mentioned in the Directive

Details of ROHS and REACH substances information are available on the Schneider-Electric Green Premium website

<http://www2.schneider-electric.com/sites/corporate/en/products-services/green-premium/green-premium.page>

Additional environmental information

The SpaceLogic, Thermostat, FCU, LCD, Modbus, 4P, 240V, XS, White presents the following relevant environmental aspects

| | |
|----------------------|--|
| Manufacturing | Manufactured at a Schneider Electric production site ISO14001 certified |
| Distribution | Weight and volume of the packaging optimized, based on the European Union's packaging directive Packaging weight is 54.1 g, consisting of Cardboard (95.84%), Plastic (4.08%), Paper (0.08%) Product distribution optimised by setting up local distribution centres |
| Installation | Ref TC903-3A4DLMSA does not require any installation operations. |
| Use | The product does not require special maintenance operations. |
| End of life | End of life optimized to decrease the amount of waste and allow recovery of the product components and materials This product contains Main PCBA (14.7g), Power PCBA (55.6g), Li Button battery (0.8g), LCD (18.7g) that should be separated from the stream of waste so as to optimize end-of-life treatment. The location of these components and other recommendations are given in the End of Life Instruction document which is available on the Schneider-Electric Green Premium website http://www2.schneider-electric.com/sites/corporate/en/products-services/green-premium/green-premium.page Recyclability potential: 42% Based on "ECO'DEEE recyclability and recoverability calculation method" (version V1, 20 Sep. 2008 presented to the French Agency for Environment and Energy Management: ADEME). |


Environmental impacts

| Reference life time | 10 years | | | | | | | | |
|---|---|--|--|-----|-------------|--------------------------|--|--|--|
| Product category | Thermostats | | | | | | | | |
| Installation elements | No special components needed | | | | | | | | |
| Use scenario | Refer to PSR0005, Load rate of the product:100% of In during 100% of the RLT, Load rate of the closed contact: 30% of IL during 14% of the RLT. But confirm with designer, The product is in active mode 5% of the time with a power use of 2.0W, in stand-by mode 50% of the time with a power use of 1.2W, in sleep mode 40% of the time with a power use of 0.6W, and in off mode 5% of the time with a power use of 0W, for 10 years. | | | | | | | | |
| Geographical representativeness | Europe | | | | | | | | |
| Technological representativeness | To control FAN coil units to match with the setpoint | | | | | | | | |
| Energy model used | <table border="1"> <thead> <tr> <th>Manufacturing</th> <th>Installation</th> <th>Use</th> <th>End of life</th> </tr> </thead> <tbody> <tr> <td>Energy model used: China</td> <td>Electricity grid mix; AC; consumption mix, at consumer; < 1kV; EU-27</td> <td>Electricity grid mix; AC; consumption mix, at consumer; < 1kV; EU-27</td> <td>Electricity grid mix; AC; consumption mix, at consumer; < 1kV; EU-27</td> </tr> </tbody> </table> | Manufacturing | Installation | Use | End of life | Energy model used: China | Electricity grid mix; AC; consumption mix, at consumer; < 1kV; EU-27 | Electricity grid mix; AC; consumption mix, at consumer; < 1kV; EU-27 | Electricity grid mix; AC; consumption mix, at consumer; < 1kV; EU-27 |
| Manufacturing | Installation | Use | End of life | | | | | | |
| Energy model used: China | Electricity grid mix; AC; consumption mix, at consumer; < 1kV; EU-27 | Electricity grid mix; AC; consumption mix, at consumer; < 1kV; EU-27 | Electricity grid mix; AC; consumption mix, at consumer; < 1kV; EU-27 | | | | | | |

Compulsory indicators

SpaceLogic, Thermostat, FCU, LCD, Modbus, 4P, 240V, XS, White - TC903-3A4DLMSA

| Impact indicators | Unit | Total | Manufacturing | Distribution | Installation | Use | End of Life |
|--|-------------------------------------|----------|---------------|--------------|--------------|----------|-------------|
| Contribution to mineral resources depletion | kg Sb eq | 9,88E-04 | 9,85E-04 | 0* | 0* | 3,51E-06 | 0* |
| Contribution to the soil and water acidification | kg SO ₂ eq | 1,77E-01 | 8,78E-03 | 1,30E-04 | 0* | 1,68E-01 | 8,43E-05 |
| Contribution to water eutrophication | kg PO ₄ ³⁻ eq | 1,18E-02 | 1,56E-03 | 2,99E-05 | 3,69E-06 | 1,02E-02 | 4,74E-05 |
| Contribution to global warming | kg CO ₂ eq | 4,39E+01 | 3,40E+00 | 2,85E-02 | 0* | 4,03E+01 | 1,36E-01 |
| Contribution to ozone layer depletion | kg CFC11 eq | 3,00E-06 | 3,64E-07 | 0* | 0* | 2,63E-06 | 4,23E-09 |
| Contribution to photochemical oxidation | kg C ₂ H ₄ eq | 1,01E-02 | 7,93E-04 | 9,27E-06 | 0* | 9,25E-03 | 7,11E-06 |
| Resources use | Unit | Total | Manufacturing | Distribution | Installation | Use | End of Life |
| Net use of freshwater | m3 | 1,46E+02 | 2,30E-02 | 0* | 0* | 1,46E+02 | 0* |
| Total Primary Energy | MJ | 8,54E+02 | 4,75E+01 | 4,02E-01 | 0* | 8,06E+02 | 3,59E-01 |



| Optional indicators | | SpaceLogic, Thermostat, FCU, LCD, Modbus, 4P, 240V, XS, White - TC903-3A4DLMSA | | | | | | |
|---|------|--|---------------|--------------|--------------|----------|-------------|--|
| Impact indicators | Unit | Total | Manufacturing | Distribution | Installation | Use | End of Life | |
| Contribution to fossil resources depletion | MJ | 4,89E+02 | 3,06E+01 | 4,00E-01 | 0* | 4,58E+02 | 2,92E-01 | |
| Contribution to air pollution | m³ | 2,15E+03 | 4,10E+02 | 1,21E+00 | 0* | 1,74E+03 | 2,67E+00 | |
| Contribution to water pollution | m³ | 2,24E+03 | 5,63E+02 | 4,68E+00 | 4,52E-01 | 1,66E+03 | 6,49E+00 | |
| Resources use | Unit | Total | Manufacturing | Distribution | Installation | Use | End of Life | |
| Use of secondary material | kg | 2,73E-04 | 2,73E-04 | 0* | 0* | 0* | 0* | |
| Total use of renewable primary energy resources | MJ | 1,04E+02 | 1,21E+00 | 0* | 0* | 1,02E+02 | 0* | |
| Total use of non-renewable primary energy resources | MJ | 7,50E+02 | 4,63E+01 | 4,02E-01 | 0* | 7,03E+02 | 3,59E-01 | |
| Use of renewable primary energy excluding renewable primary energy used as raw material | MJ | 1,03E+02 | 1,81E-01 | 0* | 0* | 1,02E+02 | 0* | |
| Use of renewable primary energy resources used as raw material | MJ | 1,03E+00 | 1,03E+00 | 0* | 0* | 0* | 0* | |
| Use of non renewable primary energy excluding non renewable primary energy used as raw material | MJ | 7,48E+02 | 4,34E+01 | 4,02E-01 | 0* | 7,03E+02 | 3,59E-01 | |
| Use of non renewable primary energy resources used as raw material | MJ | 2,86E+00 | 2,86E+00 | 0* | 0* | 0* | 0* | |
| Use of non renewable secondary fuels | MJ | 0,00E+00 | 0* | 0* | 0* | 0* | 0* | |
| Use of renewable secondary fuels | MJ | 0,00E+00 | 0* | 0* | 0* | 0* | 0* | |
| Waste categories | Unit | Total | Manufacturing | Distribution | Installation | Use | End of Life | |
| Hazardous waste disposed | kg | 3,06E+00 | 2,69E+00 | 0* | 0* | 2,10E-02 | 3,50E-01 | |
| Non hazardous waste disposed | kg | 1,53E+02 | 2,28E+00 | 0* | 0* | 1,50E+02 | 0* | |
| Radioactive waste disposed | kg | 1,01E-01 | 6,65E-04 | 0* | 0* | 1,00E-01 | 0* | |
| Other environmental information | Unit | Total | Manufacturing | Distribution | Installation | Use | End of Life | |
| Materials for recycling | kg | 1,36E-01 | 1,37E-02 | 0* | 5,22E-02 | 0* | 7,01E-02 | |
| Components for reuse | kg | 0,00E+00 | 0* | 0* | 0* | 0* | 0* | |
| Materials for energy recovery | kg | 2,96E-02 | 0* | 0* | 0* | 0* | 2,96E-02 | |
| Exported Energy | MJ | 1,64E-04 | 1,54E-05 | 0* | 1,49E-04 | 0* | 0* | |

* represents less than 0.01% of the total life cycle of the reference flow

Life cycle assessment performed with EIME version EIME v5.8.1, database version 2016-11 in compliance with ISO14044.

The use phase is the life cycle phase which has the greatest impact on the majority of environmental indicators (based on compulsory indicators).

Please note that the values given above are only valid within the context specified and cannot be used directly to draw up the environmental assessment of an installation.

| | | | |
|--|---------------------|--|--|
| <i>Registration number</i> | ENVPEP2001001_V1-EN | <i>Drafting rules</i> | PCR-ed3-EN-2015 04 02 |
| <i>Date of issue</i> | 3/2020 | <i>Supplemented by</i> | PSR-0005-ed2-EN-2016 03 29 |
| <i>Validity period</i> | 5 years | <i>Information and reference documents</i> | www.pep-ecopassport.org |
| <i>Independent verification of the declaration and data</i> | | | |
| Internal | X | External | |
| <i>The elements of the present PEP cannot be compared with elements from another program.</i> | | | |
| <i>Document in compliance with ISO 14021:2016 « Environmental labels and declarations - Self-declared environmental claims (Type II environmental labelling) »</i> | | | |

Schneider Electric Industries SAS

Country Customer Care Center
<http://www.schneider-electric.com/contact>

35, rue Joseph Monier

CS 30323

F- 92506 Rueil Malmaison Cedex

RCS Nanterre 954 503 439

Capital social 896 313 776 €

www.schneider-electric.com

Published by Schneider Electric

ENVPEP2001001_V1-EN

© 2019 - Schneider Electric – All rights reserved

3/2020

