


Product Environmental Profile

Sensor, Solid State, Push-Button, LCD, Wt






General information

Representative product	Sensor, Solid State, Push-Button, LCD, Wt - SLEASLXXB
Description of the product	The Temperature Sensor is to measure the temperature of air in a living space.
Functional unit	Control during 10 years the ambient temperature in a zone according to a temperature set by the user in a range of 0~50°C, with a temperature step of 0.5°C and characterized by a rated current of 50mA.



Constituent materials

Reference product mass	198.97 g including the product, its packaging and additional elements and accessories
-------------------------------	---



Plastics	26.5%
Metals	4.5%
Others	69.0%



Substance assessment

Products of this range are designed in conformity with the requirements of the RoHS directive (European Directive 2011/65/EU of 2 January 2013, amended in March 2015, 2015/863/EU and in November 2017, 2017/2102/EU) and do not contain, or only contain in the authorised proportions, lead, mercury, cadmium, hexavalent chromium or flame retardants (polybrominated biphenyls - PBB, polybrominated diphenyl ethers – PBDE), Bis (2-ethylhexyl)phthalate - DEHP, Benzyl butyl phthalate– BBP, Dibutyl phthalate - DBP, Diisobutyl phthalate - DIBP) as mentioned in the Directive.

Details of ROHS and REACH substances information are available on the Schneider-Electric Green Premium website

http://www2.schneider-electric.com/sites/corporate/en/products-services/green-premium/green-premium_page



Additional environmental information

The Sensor, Solid State, Push-Button, LCD, Wt presents the following relevant environmental aspects


Manufacturing	Manufactured at a Schneider Electric production site ISO14001 certified
Distribution	Weight and volume of the packaging optimized, based on the European Union's packaging directive Packaging weight is 89.8 g, consisting of Plastic film (1.7%), Cardboard (86.6%), Paper (11.7%) Product distribution optimised by setting up local distribution centres
Installation	Ref SLEASLXXB does not require any special installation.
Use	The product does not require special maintenance operations.
End of life	End of life optimized to decrease the amount of waste and allow recovery of the product components and materials This product contains Electronic card (20.5g) that should be separated from the stream of waste so as to optimize end-of-life treatment. The location of these components and other recommendations are given in the End of Life Instruction document which is available on the Schneider-Electric Green Premium website http://www2.schneider-electric.com/sites/corporate/en/products-services/green-premium/green-premium.page Recyclability potential: 10% Based on "ECO'DEEE recyclability and recoverability calculation method" (version V1, 20 Sep. 2008 presented to the French Agency for Environment and Energy Management: ADEME).



Environmental impacts

Reference life time	10 years			
Product category	Thermostats			
Installation elements	No special components needed			
Use scenario	Load rate of the product: 100% of In during 100% of the RLT Load rate of the closed contact : 30% of IL during 14% of the RLT			
Geographical representativeness	China			
Technological representativeness	The means of material production, processing and transport modeled are representative of the technologies used in production.			
Energy model used	Manufacturing	Installation	Use	End of life
	Energy model used: China	Electricity mix; AC; consumption mix, at consumer; 220V; CN	Electricity mix; AC; consumption mix, at consumer; 220V; CN	Electricity mix; AC; consumption mix, at consumer; 220V; CN

Compulsory indicators		Sensor, Solid State, Push-Button, LCD, Wt - SLEASLXXB					
Impact indicators	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Contribution to mineral resources depletion	kg Sb eq	2.09E-03	2.09E-03	0*	0*	4.69E-07	0*
Contribution to the soil and water acidification	kg SO ₂ eq	1.28E-01	1.17E-02	1.17E-04	2.05E-05	1.16E-01	4.12E-05
Contribution to water eutrophication	kg PO ₄ ³⁻ eq	3.36E-02	2.91E-03	2.70E-05	5.44E-06	3.06E-02	1.66E-05
Contribution to global warming	kg CO ₂ eq	1.15E+02	7.79E+00	2.57E-02	0*	1.07E+02	4.59E-02
Contribution to ozone layer depletion	kg CFC11 eq	1.77E-06	9.21E-07	0*	0*	8.51E-07	1.68E-09
Contribution to photochemical oxidation	kg C ₂ H ₄ eq	1.49E-02	1.15E-03	8.36E-06	1.53E-06	1.37E-02	3.77E-06
Resources use	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Net use of freshwater	m ³	3.64E-01	2.45E-01	0*	0*	1.19E-01	0*
Total Primary Energy	MJ	1.84E+03	9.37E+01	3.63E-01	0*	1.75E+03	1.85E-01



Optional indicators		Sensor, Solid State, Push-Button, LCD, Wt - SLEASLXXB					
Impact indicators	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Contribution to fossil resources depletion	MJ	1.69E+03	7.81E+01	3.61E-01	0*	1.62E+03	0*
Contribution to air pollution	m³	1.17E+04	6.31E+02	0*	0*	1.11E+04	1.35E+00
Contribution to water pollution	m³	6.20E+03	8.76E+02	4.22E+00	7.43E-01	5.32E+03	2.32E+00
Resources use	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Use of secondary material	kg	2.12E-03	2.12E-03	0*	0*	0*	0*
Total use of renewable primary energy resources	MJ	9.40E+01	4.28E+00	0*	0*	8.97E+01	0*
Total use of non-renewable primary energy resources	MJ	1.75E+03	8.94E+01	3.62E-01	0*	1.66E+03	1.85E-01
Use of renewable primary energy excluding renewable primary energy used as raw material	MJ	9.23E+01	2.56E+00	0*	0*	8.97E+01	0*
Use of renewable primary energy resources used as raw material	MJ	1.72E+00	1.72E+00	0*	0*	0*	0*
Use of non renewable primary energy excluding non renewable primary energy used as raw material	MJ	1.75E+03	8.74E+01	3.62E-01	0*	1.66E+03	1.85E-01
Use of non renewable primary energy resources used as raw material	MJ	2.08E+00	2.08E+00	0*	0*	0*	0*
Use of non renewable secondary fuels	MJ	0.00E+00	0*	0*	0*	0*	0*
Use of renewable secondary fuels	MJ	0.00E+00	0*	0*	0*	0*	0*
Waste categories	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Hazardous waste disposed	kg	4.30E+01	3.94E+01	0*	0*	3.45E+00	2.20E-01
Non hazardous waste disposed	kg	2.33E+01	3.89E+00	0*	0*	1.94E+01	0*
Radioactive waste disposed	kg	1.57E-03	9.27E-04	6.50E-07	1.71E-07	6.39E-04	1.08E-06
Other environmental information	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Materials for recycling	kg	1.14E-01	1.51E-02	0*	8.83E-02	0*	1.10E-02
Components for reuse	kg	0.00E+00	0*	0*	0*	0*	0*
Materials for energy recovery	kg	1.12E-02	0*	0*	0*	0*	1.12E-02
Exported Energy	MJ	2.79E-04	2.62E-05	0*	2.53E-04	0*	0*

* represents less than 0.01% of the total life cycle of the reference flow

Life cycle assessment performed with EIME version EIME v5.9.4, database version 2022-01 in compliance with ISO14044.

The use phase is the life cycle phase which has the greatest impact on the majority of environmental indicators (based on compulsory indicators). The Manufacturing phase has the greatest impact on Abiotic depletion, Ozone layer depletion ODP steady state and Net use of freshwater.

Please note that the values given above are only valid within the context specified and cannot be used directly to draw up the environmental assessment of an installation.

<i>Registration number :</i>	SCHN-00854-V01.01-EN	<i>Drafting rules</i>	PCR-ed3-EN-2015 04 02
<i>Verifier accreditation N°</i>	VH18	<i>Supplemented by</i>	PSR-0005-ed2-EN-2016 03 29
<i>Date of issue</i>	09/2022	<i>Information and reference documents</i>	www.pep-ecopassport.org
		<i>Validity period</i>	5 years
<i>Independent verification of the declaration and data, in compliance with ISO 14025 : 2006</i>			
Internal	External X		
<i>The PCR review was conducted by a panel of experts chaired by Philippe Osset (SOLINNEN)</i>			
<i>PEP are compliant with XP C08-100-1 :2016</i>			
<i>The elements of the present PEP cannot be compared with elements from another program.</i>			
<i>Document in compliance with ISO 14025 : 2006 « Environmental labels and declarations. Type III environmental declarations »</i>			



Schneider Electric Industries SAS
Country Customer Care Center
<http://www.schneider-electric.com/contact>
35, rue Joseph Monier
CS 30323
F- 92506 Rueil Malmaison Cedex
RCS Nanterre 954 503 439
Capital social 896 313 776 €

www.schneider-electric.com

Published by Schneider Electric

SCHN-00854-V01.01-EN

© 2019 - Schneider Electric – All rights reserved

09/2022