

Product Environmental Profile

Harmony Pro XVTS Ø70mm Smart Monolithic Tower Light



Schneider
Electric




General information

Reference product	Harmony Pro XVTs Ø70mm Smart Monolithic Tower Light - XVTs2BSW
Description of the product	This product is an advanced signaling device designed for industrial environments. It provides highly flexible visual and audible status indication using multi-color LED segments that can display steady, blinking, flashing or rotating light effects
Description of the range	Single product
Functional unit	These tower lights are fully programmable and support smart connectivity through IO-Link for integration into Industry 4.0 systems with configuration possible via USB and software. Optional audible alerts with multiple tones and up to 105 dB sound level enhance safety and communication. Built for durability and they feature IP66/IP69K protection and UV resistance which making them suitable for harsh environments, clean rooms and industrial applications.
Specifications are:	<p>Beacon or indicator bank unit type : 15 segments LED</p> <p>IP degree of protection : IP66, IP69K</p> <p>[Uimp] rated impulse withstand voltage : 0.33 kV</p> <p>Service life in hours : 50000 h</p> <p>Product certifications : cULus, UKCA, CE</p>



Constituent materials



Substance assessment

Details of ROHS and REACH substances information are available on the Schneider-Electric website
<https://www.se.com>



Additional environmental information

End Of Life	Recyclability potential:	92%	The recyclability rate was calculated from the recycling rates of each material making up the product based on REEECY'LAB tool developed by Ecosystem, for components/materials not covered by the tool, data from the EIME database and the related PSR was taken. If no data was found a conservative assumption was used (0% recyclability).
-------------	--------------------------	-----	---



Environmental impacts

Reference service life time	10 years			
Product category	Other equipments - Active product			
Life cycle of the product	The manufacturing, the distribution, the installation, the use and the end of life were taken into consideration in this study			
Electricity consumption	The electricity consumed during manufacturing processes is considered for each part of the product individually, the final assembly generates a negligible consumption			
Installation elements	The product does not require any installation operations			
Use scenario	The product is in active mode 73% of the time with a power use of 14.88 W and 27% of the time with off mode with power use of 0W for 10 years			
Time representativeness	The collected data are representative of the year 2025			
Technological representativeness	The Modules of Technologies such as material production, manufacturing processes and transport technology used in the PEP analysis (LCA EIME in the case) are similar and representative of the actual type of technologies used to make the product.			
Geographical representativeness	Final assembly site	Use phase	End-of-life	
	Germany, Europe	Global	Global	
Energy model used	[A1 - A3] Electricity Mix; High voltage; 2020; Germany, DE	[A5] No energy used	[B6] Electricity Mix; Low voltage; 2020; Global, GLO	[C1 - C4] Global, European and French datasets are used.

Detailed results of the optional indicators mentioned in PCRed4 are available in the LCA report and on demand in a digital format - Country Customer Care Center - <http://www.se.com/contact>

Mandatory Indicators		Harmony Pro XVTS Ø70mm Smart Monolithic Tower Light - XVTS2BSW						
Impact Indicators	Unit	Total (without Module D)	[A1 - A3] - Manufacturing	[A4] - Distribution	[A5] - Installation	[B1 - B7] - Use	[C1 - C4] - End of life	[D] - Benefits and loads
Contribution to climate change	kg CO2 eq	4.75E+02	1.25E+01	7.33E-01	0*	4.61E+02	6.70E-01	-2.64E+00
Contribution to climate change-fossil	kg CO2 eq	4.70E+02	1.25E+01	7.33E-01	0*	4.56E+02	6.64E-01	-2.53E+00
Contribution to climate change-biogenic	kg CO2 eq	4.97E+00	8.72E-02	0*	0*	4.87E+00	6.30E-03	-1.15E-01
Contribution to climate change-land use and land use change	kg CO2 eq	1.11E-03	1.11E-03	0*	0*	0*	0*	-9.78E-04
Contribution to ozone depletion	kg CFC-11 eq	7.35E-06	4.76E-06	6.48E-07	0*	1.94E-06	1.86E-09	-5.23E-08
Contribution to acidification	mol H+ eq	2.42E+00	4.72E-02	3.23E-03	0*	2.37E+00	2.74E-03	-4.63E-03
Contribution to eutrophication, freshwater	kg P eq	7.59E-04	4.29E-05	8.60E-08	0*	7.12E-04	4.67E-06	-1.55E-05
Contribution to eutrophication, marine	kg N eq	2.97E-01	1.15E-02	1.48E-03	0*	2.83E-01	7.80E-04	-1.22E-03
Contribution to eutrophication, terrestrial	mol N eq	3.81E+00	1.26E-01	1.61E-02	0*	3.66E+00	8.99E-03	-1.31E-02
Contribution to photochemical ozone formation - human health	kg COVNM eq	9.77E-01	4.21E-02	5.26E-03	0*	9.27E-01	2.11E-03	-4.34E-03
Contribution to resource use, minerals and metals	kg Sb eq	2.09E-03	1.99E-03	0*	0*	9.76E-05	0*	-2.70E-06
Contribution to resource use, fossils	MJ	9.95E+03	2.10E+02	9.14E+00	0*	9.73E+03	9.65E+00	-6.58E+01
Contribution to water use	m3 eq	3.14E+01	3.19E+00	3.73E-02	5.96E-03	2.81E+01	6.65E-02	-5.11E-01

Inventory flows Indicators		Harmony Pro XVTs Ø70mm Smart Monolithic Tower Light - XVTs2BSW						
Inventory flows	Unit	Total (without Module D)	[A1 - A3] - Manufacturing	[A4] - Distribution	[A5] - Installation	[B1 - B7] - Use	[C1 - C4] - End of life	[D] - Benefits and loads
Contribution to renewable primary energy used as energy	MJ	1.60E+03	1.31E+01	0*	0*	1.58E+03	1.65E+00	-3.81E+00
Contribution to renewable primary energy used as raw material	MJ	3.98E-01	3.98E-01	0*	0*	0*	0*	0.00E+00
Contribution to total renewable primary energy	MJ	1.60E+03	1.35E+01	0*	0*	1.58E+03	1.65E+00	-3.81E+00
Contribution to non renewable primary energy used as energy	MJ	9.93E+03	1.84E+02	9.14E+00	0*	9.73E+03	9.65E+00	-4.34E+01
Contribution to non renewable primary energy used as raw material	MJ	2.61E+01	2.61E+01	0*	0*	0*	0*	-2.24E+01
Contribution to total non renewable primary energy	MJ	9.95E+03	2.10E+02	9.14E+00	0*	9.73E+03	9.65E+00	-6.58E+01
Contribution to use of secondary material	kg	5.26E-02	5.26E-02	0*	0*	0*	0*	0.00E+00
Contribution to use of renewable secondary fuels	MJ	0.00E+00	0*	0*	0*	0*	0*	0.00E+00
Contribution to use of non renewable secondary fuels	MJ	0.00E+00	0*	0*	0*	0*	0*	0.00E+00
Contribution to net use of fresh water	m³	7.33E-01	7.37E-02	8.68E-04	1.39E-04	6.56E-01	1.42E-03	-1.19E-02
Contribution to hazardous waste disposed	kg	2.49E+01	1.41E+01	0*	0*	1.07E+01	7.36E-02	-1.91E-01
Contribution to non hazardous waste disposed	kg	8.11E+01	8.09E+00	0*	6.52E-02	7.29E+01	5.47E-02	-1.97E+00
Contribution to radioactive waste disposed	kg	2.02E-02	5.52E-03	1.46E-04	0*	1.45E-02	1.56E-05	-1.06E-03
Contribution to components for reuse	kg	0.00E+00	0*	0*	0*	0*	0*	0.00E+00
Contribution to materials for recycling	kg	7.32E-01	5.95E-03	0*	0*	0*	7.26E-01	0.00E+00
Contribution to materials for energy recovery	kg	0.00E+00	0*	0*	0*	0*	0*	0.00E+00
Contribution to exported energy	MJ	1.74E-05	1.74E-05	0*	0*	0*	0*	0.00E+00

* represents less than 0.01% of the total life cycle of the reference flow

Contribution to biogenic carbon content of the product kg of C 0.00E+00

Contribution to biogenic carbon content of the associated packaging kg of C 1.82E-02

* The calculation of the biogenic carbon is based on the Ademe for the Cardboard (28%), EN16485 for Wood (39,52%), and APESA/RECORD for Paper (37,8%)

Mandatory Indicators		Harmony Pro XVTs Ø70mm Smart Monolithic Tower Light - XVTs2BSW							
Impact Indicators	Unit	[B1 - B7] - Use	[B1]	[B2]	[B3]	[B4]	[B5]	[B6]	[B7]
Contribution to climate change	kg CO2 eq	4.61E+02	0*	0*	0*	0*	0*	4.61E+02	0*
Contribution to climate change-fossil	kg CO2 eq	4.56E+02	0*	0*	0*	0*	0*	4.56E+02	0*
Contribution to climate change-biogenic	kg CO2 eq	4.87E+00	0*	0*	0*	0*	0*	4.87E+00	0*
Contribution to climate change-land use and land use change	kg CO2 eq	0*	0*	0*	0*	0*	0*	0*	0*
Contribution to ozone depletion	kg CFC-11 eq	1.94E-06	0*	0*	0*	0*	0*	1.94E-06	0*
Contribution to acidification	mol H+ eq	2.37E+00	0*	0*	0*	0*	0*	2.37E+00	0*
Contribution to eutrophication, freshwater	kg P eq	7.12E-04	0*	0*	0*	0*	0*	7.12E-04	0*
Contribution to eutrophication marine	kg N eq	2.83E-01	0*	0*	0*	0*	0*	2.83E-01	0*
Contribution to eutrophication, terrestrial	mol N eq	3.66E+00	0*	0*	0*	0*	0*	3.66E+00	0*
Contribution to photochemical ozone formation - human health	kg COVNM eq	9.27E-01	0*	0*	0*	0*	0*	9.27E-01	0*
Contribution to resource use, minerals and metals	kg Sb eq	9.76E-05	0*	0*	0*	0*	0*	9.76E-05	0*
Contribution to resource use, fossils	MJ	9.73E+03	0*	0*	0*	0*	0*	9.73E+03	0*
Contribution to water use	m3 eq	2.81E+01	0*	0*	0*	0*	0*	2.81E+01	0*

Inventory flows Indicators		Harmony Pro XVTS Ø70mm Smart Monolithic Tower Light - XVTS2BSW							
Inventory flows	Unit	[B1 - B7] - Use	[B1]	[B2]	[B3]	[B4]	[B5]	[B6]	[B7]
Contribution to use of renewable primary energy excluding renewable primary energy used as raw material	MJ	1.58E+03	0*	0*	0*	0*	0*	1.58E+03	0*
Contribution to use of renewable primary energy resources used as raw material	MJ	0*	0*	0*	0*	0*	0*	0*	0*
Contribution to total use of renewable primary energy resources	MJ	1.58E+03	0*	0*	0*	0*	0*	1.58E+03	0*
Contribution to use of non renewable primary energy excluding non renewable primary energy used as raw material	MJ	9.73E+03	0*	0*	0*	0*	0*	9.73E+03	0*
Contribution to use of non renewable primary energy resources used as raw material	MJ	0*	0*	0*	0*	0*	0*	0*	0*
Contribution to total use of non-renewable primary energy resources	MJ	9.73E+03	0*	0*	0*	0*	0*	9.73E+03	0*
Contribution to use of secondary material	kg	0*	0*	0*	0*	0*	0*	0*	0*
Contribution to use of renewable secondary fuels	MJ	0*	0*	0*	0*	0*	0*	0*	0*
Contribution to use of non renewable secondary fuels	MJ	0*	0*	0*	0*	0*	0*	0*	0*
Contribution to net use of freshwater	m³	6.56E-01	0*	0*	0*	0*	0*	6.56E-01	0*
Contribution to hazardous waste disposed	kg	1.07E+01	0*	0*	0*	0*	0*	1.07E+01	0*
Contribution to non hazardous waste disposed	kg	7.29E+01	0*	0*	0*	0*	0*	7.29E+01	0*
Contribution to radioactive waste disposed	kg	1.45E-02	0*	0*	0*	0*	0*	1.45E-02	0*
Contribution to components for reuse	kg	0*	0*	0*	0*	0*	0*	0*	0*
Contribution to materials for recycling	kg	0*	0*	0*	0*	0*	0*	0*	0*
Contribution to materials for energy recovery	kg	0*	0*	0*	0*	0*	0*	0*	0*
Contribution to exported energy	MJ	0*	0*	0*	0*	0*	0*	0*	0*

* represents less than 0.01% of the total life cycle of the reference flow

Life cycle assessment performed with EIME version v6.2.5-6, database version 2024-01 in compliance with ISO14044, EF3.1 method is applied, for biogenic carbon storage, assessment methodology -1/1 is used

Please note that the values given above are only valid within the context specified and cannot be used directly to draw up the environmental assessment of an installation.

Registration number :	ENVPEP2510037_V1	Drafting rules Supplemented by www.pep-ecopassport.org	PEP-PCR-ed4-2021 09 06 PSR-0005-ed3.1-EN-2023 12 08
Date of issue	10-2025	Information and reference documents	www.pep-ecopassport.org
Independent verification of the declaration and data, in compliance with ISO 14021 : 2016			
Internal	X	External	Validity period 5 years
<p>The PCR review was conducted by a panel of experts chaired by Julie Orgelet (DDemain)</p> <p>PEPs are compliant with XP C08-100-1:2016 and EN 50693:2019 or NF E38-500 :2022</p> <p>The components of the present PEP may not be compared with components from any other program.</p> <p>Document complies with ISO 14021:2016 "Environmental labels and declarations. Type II environmental declarations"</p>			

Schneider Electric Industries SAS
Country Customer Care Center
<http://www.se.com/contact>
Head Office
35, rue Joseph Monier
CS 30323
F- 92500 Rueil Malmaison Cedex
RCS Nanterre 954 503 439
Capital social 928 298 512 €

www.se.com

ENVPEP2510037_V1

Published by Schneider Electric
©2024 - Schneider Electric – All rights reserved

10-2025