


Product Environmental Profile

RESI9 PLASTIC CABLE TRUNKING






General information

| | |
|----------------------------|--|
| Representative product | RESI9 PLASTIC CABLE TRUNKING -R9HKT13 |
| Description of the product | The main function of the Resi9 cable trunking (GTL - gaine technique lodgement) product range is to allow the installation of Resi9 enclosure for distribution or Resi9 Control Panel for metering on it. |
| Functional unit | Accommodate and protect the wiring and wiring accessories along 1 meter for a reference service life of 20 years. The installation trunking system with cross-section 13300 mm ² includes the profile and accessories that are representative of standard use. |



Constituent materials

Reference product mass 4113.25 g including the product, its packaging and additional elements and accessories



Substance assessment

Products of this range are designed in conformity with the requirements of the RoHS directive (European Directive 2011/65/EU of 8 June 2011) and do not contain, or only contain in the authorised proportions, lead, mercury, cadmium, hexavalent chromium or flame retardants (polybrominated biphenyls - PBB, polybrominated diphenyl ethers - PBDE) as mentioned in the Directive

As the products of the range are designed in accordance with the RoHS Directive (European Directive 2002/95/EC of 27 January 2003), they can be incorporated without any restriction in an assembly or an installation subject to this Directive.

Details of ROHS and REACH substances information are available on the Schneider-Electric Green Premium website

http://www2.schneider-electric.com/sites/corporate/en/products-services/green-premium/green-premium_page



Additional environmental information

The RESI9 PLASTIC CABLE TRUNKING presents the following relevant environmental aspects


| | |
|----------------------|--|
| Manufacturing | Manufactured at a Schneider Electric production site ISO14001 certified |
| Distribution | Weight and volume of the packaging optimized, based on the European Union's packaging directive Packaging weight is 416.7 g, consisting of cardboard (100%) Product distribution optimised by setting up local distribution centres |
| Installation | Ref R9HKT13 does not require any installation operations |
| Use | The product does not require special maintenance operations. |
| End of life | End of life optimized to decrease the amount of waste and allow recovery of the product components and materials No special end-of-life treatment required. According to countries' practices this product can enter the usual end-of-life treatment process. Recyclability potential: 9% Based on "ECO'DEEE recyclability and recoverability calculation method" (version V1, 20 Sep. 2008 presented to the French Agency for Environment and Energy Management: ADEME). |



Environmental impacts

| | | | | |
|---|---|---------------------|------------|--------------------|
| Reference life time | 20 years | | | |
| Product category | Enclosures | | | |
| Installation elements | No special components needed | | | |
| Use scenario | This product does not have any energy consumption | | | |
| Geographical representativeness | Europe | | | |
| Technological representativeness | The main function of the Resi9 cable trunking (GTL - gaine technique lodgement) product range is to allow the installation of Resi9 enclosure for distribution or Resi9 Control Panel for metering on it. | | | |
| Energy model used | Manufacturing | Installation | Use | End of life |
| | Energy model used: United Kingdom (UK) | 0 | 0 | 0 |

| Compulsory indicators | | RESI9 PLASTIC CABLE TRUNKING - R9HKT13 | | | | | |
|--|-------------------------------------|--|---------------|--------------|--------------|-----|-------------|
| Impact indicators | Unit | Total | Manufacturing | Distribution | Installation | Use | End of Life |
| Contribution to mineral resources depletion | kg Sb eq | 7.30E-06 | 7.26E-06 | 2.12E-08 | 1.29E-09 | 0* | 1.12E-08 |
| Contribution to the soil and water acidification | kg SO ₂ eq | 3.60E-02 | 3.23E-02 | 2.42E-03 | 1.24E-04 | 0* | 1.18E-03 |
| Contribution to water eutrophication | kg PO ₄ ³⁻ eq | 1.14E-02 | 1.04E-02 | 5.58E-04 | 2.92E-05 | 0* | 3.91E-04 |
| Contribution to global warming | kg CO ₂ eq | 2.16E+01 | 2.02E+01 | 5.31E-01 | 4.03E-02 | 0* | 9.10E-01 |
| Contribution to ozone layer depletion | kg CFC11 eq | 1.59E-06 | 1.56E-06 | 1.08E-09 | 2.53E-09 | 0* | 2.83E-08 |
| Contribution to photochemical oxidation | kg C ₂ H ₄ eq | 5.10E-03 | 4.80E-03 | 1.73E-04 | 1.35E-05 | 0* | 1.18E-04 |
| Resources use | Unit | Total | Manufacturing | Distribution | Installation | Use | End of Life |
| Net use of freshwater | m3 | 8.14E-02 | 8.06E-02 | 4.75E-05 | 4.93E-05 | 0* | 6.21E-04 |
| Total Primary Energy | MJ | 6.61E+02 | 6.47E+02 | 7.50E+00 | 6.95E-01 | 0* | 6.11E+00 |




| Optional indicators | | RESI9 PLASTIC CABLE TRUNKING - R9HKT13 | | | | | |
|---|----------------|--|---------------|--------------|--------------|-----|-------------|
| Impact indicators | Unit | Total | Manufacturing | Distribution | Installation | Use | End of Life |
| Contribution to fossil resources depletion | MJ | 3.48E+02 | 3.35E+02 | 7.46E+00 | 5.71E-01 | 0* | 5.04E+00 |
| Contribution to air pollution | m ³ | 1.84E+03 | 1.77E+03 | 2.26E+01 | 4.43E+00 | 0* | 4.10E+01 |
| Contribution to water pollution | m ³ | 3.86E+03 | 3.71E+03 | 8.73E+01 | 4.73E+00 | 0* | 5.61E+01 |
| Resources use | Unit | Total | Manufacturing | Distribution | Installation | Use | End of Life |
| Use of secondary material | kg | 8.22E-04 | 8.22E-04 | 0* | 0* | 0* | 0* |
| Total use of renewable primary energy resources | MJ | 9.40E+00 | 9.38E+00 | 1.00E-02 | 0* | 0* | 6.03E-03 |
| Total use of non-renewable primary energy resources | MJ | 6.52E+02 | 6.37E+02 | 7.49E+00 | 6.95E-01 | 0* | 6.11E+00 |
| Use of renewable primary energy excluding renewable primary energy used as raw material | MJ | 4.92E-01 | 4.75E-01 | 1.00E-02 | 7.05E-04 | 0* | 6.03E-03 |
| Use of renewable primary energy resources used as raw material | MJ | 8.91E+00 | 8.91E+00 | 0* | 0* | 0* | 0* |
| Use of non renewable primary energy excluding non renewable primary energy used as raw material | MJ | 5.64E+02 | 5.50E+02 | 7.49E+00 | 6.95E-01 | 0* | 6.11E+00 |
| Use of non renewable primary energy resources used as raw material | MJ | 8.76E+01 | 8.76E+01 | 0* | 0* | 0* | 0* |
| Use of non renewable secondary fuels | MJ | 0.00E+00 | 0* | 0* | 0* | 0* | 0* |
| Use of renewable secondary fuels | MJ | 0.00E+00 | 0* | 0* | 0* | 0* | 0* |
| Waste categories | Unit | Total | Manufacturing | Distribution | Installation | Use | End of Life |
| Hazardous waste disposed | kg | 1.03E+01 | 2.82E+00 | 0* | 4.38E-01 | 0* | 7.06E+00 |
| Non hazardous waste disposed | kg | 9.85E-01 | 9.48E-01 | 1.89E-02 | 1.94E-03 | 0* | 1.68E-02 |
| Radioactive waste disposed | kg | 1.29E-03 | 1.25E-03 | 1.34E-05 | 2.96E-06 | 0* | 2.71E-05 |
| Other environmental information | Unit | Total | Manufacturing | Distribution | Installation | Use | End of Life |
| Materials for recycling | kg | 8.88E-01 | 1.13E-01 | 0* | 4.32E-01 | 0* | 3.44E-01 |
| Components for reuse | kg | 0.00E+00 | 0* | 0* | 0* | 0* | 0* |
| Materials for energy recovery | kg | 2.11E-01 | 2.68E-02 | 0* | 0* | 0* | 1.84E-01 |
| Exported Energy | MJ | 0.00E+00 | 0* | 0* | 0* | 0* | 0* |

* represents less than 0.01% of the total life cycle of the reference flow

Life cycle assessment performed with EIME version EIME v5.5, database version 2015-04.

The manufacturing phase is the life cycle phase which has the greatest impact on the majority of environmental indicators (based on compulsory indicators).

Please note that the values given above are only valid within the context specified and cannot be used directly to draw up the environmental assessment of an installation.

| | | | |
|--|----------------------|--|---|
| <i>Registration N°</i> | SCHN-00071-V01.01-EN | <i>Drafting rules</i> | PCR-ed3-EN-2015 04 02 |
| <i>Verifier accreditation N°</i> | VH08 | <i>Supplemented by</i> | PSR-0003-ed1-2012 02 02 |
| <i>Date of issue</i> | 05/2016 | <i>Information and reference documents</i> | www.pep-ecopassport.org |
| | | <i>Validity period</i> | 5 years |
| <i>Independent verification of the declaration and data, in compliance with ISO 14025 : 2010</i> | | | |
| Internal | External | X | |
| <i>The PCR review was conducted by a panel of experts chaired by Philippe Osset (SOLINNEN)</i> | | |  |
| <i>The elements of the present PEP cannot be compared with elements from another program.</i> | | | |
| <i>Document in compliance with ISO 14025 : 2010 « Environmental labels and declarations. Type III environmental declarations »</i> | | | |

Schneider Electric Industries SAS

Country Customer Care Center: www.schneider-electric.com/contact

35, rue Joseph Monier

CS 30323

F- 92506 Rueil Malmaison Cedex

RCS Nanterre 954 503 439

Capital social 896 313 776 €

www.schneider-electric.com

SCHN-00071-V01.01-EN

Published by Schneider Electric

© 2016 - Schneider Electric – All rights reserved

05/2016