

Product Environmental Profile

ILM62 Hybrid Cable






General information

Representative product	ILM62 Hybrid Cable - VW3E1142R010 – Hybrid Cable DB 4 D1 to DB 4 D1 ILM D1, 1 meter
Description of the product	The wiring of the Connection Module ILM62CM, the Distribution Box ILM62DB and the ILM62 Servo Module in line structure or tree structure occurs with the ILM62 Hybrid Cable range. This range consists of hybrid cables of different length (from 1 meter to 20 meters) and plug connector variants (straight connection; connection at the bottom and connection on the top).
	The environmental impacts of this referenced product are representative of the impacts of the other products of the range which are developed with a similar technology.
Functional unit	To transmit energy over a distance of 1 meter during 10 years at a 100% use rate



Constituent materials

Reference product mass 595 g including the product, its packaging and additional elements and accessories



Plastics	27.3%
Metals	5.7%
Others	67.1%

Substance assessment

Products of this range are designed in conformity with the requirements of the RoHS directive (European Directive 2011/65/EU of 2 January 2013, amended in March 2015, 2015/863/EU and in November 2017, 2017/2102/EU) and do not contain, or only contain in the authorised proportions, lead, mercury, cadmium, hexavalent chromium or flame retardants (polybrominated biphenyls - PBB, polybrominated diphenyl ethers – PBDE), Bis (2-ethylhexyl)phthalate - DEHP, Benzyl butyl phthalate– BBP, Dibutyl phthalate - DBP, Diisobutyl phthalate - DIBP) as mentioned in the Directive.

Details of ROHS and REACH substances information are available on the Schneider-Electric Green Premium website

<http://www2.schneider-electric.com/sites/corporate/en/products-services/green-premium/green-premium.page>

Additional environmental information


The ILM62 Hybrid Cable presents the following relevant environmental aspects

Manufacturing	Manufactured at a Schneider Electric production site ISO14001 certified
Distribution	Weight and volume of the packaging optimized, based on the European Union's packaging directive Packaging weight is 19.2 g, consisting of plastic (100%) Product distribution optimised by setting up local distribution centres
Installation	The product does not require any specific installation operation
Use	The product does not require special maintenance operations.
End of life	End of life optimized to decrease the amount of waste and allow recovery of the product components and materials This product contains one cable (386g) that should be separated from the stream of waste so as to optimize end-of-life treatment. The location of these components and other recommendations are given in the End of Life Instruction document which is available on the Schneider-Electric Green Premium website http://www2.schneider-electric.com/sites/corporate/en/products-services/green-premium/green-premium.page Recyclability potential: 29% Based on "ECO'DEEE recyclability and recoverability calculation method" (version V1, 20 Sep. 2008 presented to the French Agency for Environment and Energy Management: ADEME).

Environmental impacts

Reference life time	10 years			
Installation elements	No special components needed			
Use scenario	The product is in active mode 100% of the time with a power dissipation of 13,2W, for 10 years			
Geographical representativeness	Europe			
Technological representativeness	The wiring of the Connection Module ILM62CM, the Distribution Box ILM62DB and the ILM62 Servo Module in line structure or tree structure occurs with the ILM62 Hybrid Cable range. This range consists of hybrid cables of different length (from 1 meter to 20 meters) and plug connector variants (straight connection; connection at the bottom and connection on the top).			
Energy model used	Manufacturing	Installation	Use	End of life
	Energy model used: Germany	Electricity grid mix; AC; consumption mix, at consumer; < 1kV; EU-27	Electricity grid mix; AC; consumption mix, at consumer; < 1kV; EU-27	Electricity grid mix; AC; consumption mix, at consumer; < 1kV; EU-27

Compulsory indicators		ILM62 Hybrid Cable - VW3E1142R010 – Hybrid Cable DB 4 D1 to DB 4 D1 ILM D1, 1 meter					
Impact indicators	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Contribution to mineral resources depletion	kg Sb eq	2.65E-04	2.16E-04	0*	0*	4.92E-05	0*
Contribution to the soil and water acidification	kg SO ₂ eq	2.37E+00	6.29E-03	3.51E-04	0*	2.36E+00	3.52E-04
Contribution to water eutrophication	kg PO ₄ ³⁻ eq	1.45E-01	1.75E-03	8.07E-05	0*	1.43E-01	1.29E-04
Contribution to global warming	kg CO ₂ eq	5.70E+02	3.44E+00	7.68E-02	0*	5.67E+02	4.21E-01
Contribution to ozone layer depletion	kg CFC11 eq	3.75E-05	5.64E-07	0*	0*	3.69E-05	1.84E-08
Contribution to photochemical oxidation	kg C ₂ H ₄ eq	1.31E-01	6.67E-04	2.50E-05	0*	1.30E-01	3.95E-05
Resources use	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Net use of freshwater	m3	2.05E+03	0*	0*	0*	2.05E+03	0*
Total Primary Energy	MJ	1.14E+04	5.10E+01	0*	0*	1.13E+04	2.39E+00



Optional indicators		ILM62 Hybrid Cable - VW3E1142R010 – Hybrid Cable DB 4 D1 to DB 4 D1 ILM D1, 1 meter					
Impact indicators	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Contribution to fossil resources depletion	MJ	6.46E+03	2.96E+01	1.08E+00	0*	6.43E+03	1.47E+00
Contribution to air pollution	m ³	2.49E+04	4.88E+02	3.27E+00	0*	2.44E+04	1.44E+01
Contribution to water pollution	m ³	2.45E+04	6.84E+02	1.26E+01	0*	2.34E+04	4.25E+02
Resources use	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Use of secondary material	kg	3.47E-03	3.47E-03	0*	0*	0*	0*
Total use of renewable primary energy resources	MJ	1.44E+03	3.56E-01	0*	0*	1.44E+03	0*
Total use of non-renewable primary energy resources	MJ	9.93E+03	5.06E+01	1.08E+00	0*	9.88E+03	2.39E+00
Use of renewable primary energy excluding renewable primary energy used as raw material	MJ	1.44E+03	3.56E-01	0*	0*	1.44E+03	0*
Use of renewable primary energy resources used as raw material	MJ	0.00E+00	0*	0*	0*	0*	0*
Use of non renewable primary energy excluding non renewable primary energy used as raw material	MJ	9.92E+03	3.66E+01	1.08E+00	0*	9.88E+03	2.39E+00
Use of non renewable primary energy resources used as raw material	MJ	1.40E+01	1.40E+01	0*	0*	0*	0*
Use of non renewable secondary fuels	MJ	0.00E+00	0*	0*	0*	0*	0*
Use of renewable secondary fuels	MJ	0.00E+00	0*	0*	0*	0*	0*

Waste categories	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Hazardous waste disposed	kg	4.59E+00	2.91E+00	0*	0*	2.95E-01	1.39E+00
Non hazardous waste disposed	kg	2.11E+03	6.40E-01	0*	0*	2.11E+03	0*
Radioactive waste disposed	kg	1.41E+00	5.42E-04	0*	0*	1.41E+00	0*
Other environmental information	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Materials for recycling	kg	2.01E-01	1.74E-02	0*	1.69E-02	0*	1.67E-01
Components for reuse	kg	0.00E+00	0*	0*	0*	0*	0*
Materials for energy recovery	kg	5.67E-03	0*	0*	0*	0*	5.67E-03
Exported Energy	MJ	0.00E+00	0*	0*	0*	0*	0*

* represents less than 0.01% of the total life cycle of the reference flow

Life cycle assessment performed with EIME version EIME v5.8.1, database version 2016-11 in compliance with ISO14044.

The use phase is the life cycle phase which has the greatest impact on the majority of environmental indicators (based on compulsory indicators).

According to this environmental analysis, proportionality rules may be used to evaluate the impacts of other products of this range.

The environmental impacts of other products in this family may be estimated as follow: The impact categories in the use phase are proportional to the power losses of the product. The impact categories in the manufacturing and distribution phase are proportional to the mass of the product.

Please note that the values given above are only valid within the context specified and cannot be used directly to draw up the environmental assessment of an installation.

Registration number	ENVPEP1409022_V2	Drafting rules	PCR-ed3-EN-2015 04 02
Date of issue	11/2020	Supplemented by	PSR-0001-ed3-EN-2015 10 16
Validity period	5 years	Information and reference documents	www.pep-ecopassport.org
<i>Independent verification of the declaration and data</i>			
Internal	X	External	
<i>The elements of the present PEP cannot be compared with elements from another program.</i>			
<i>Document in compliance with ISO 14021:2016 « Environmental labels and declarations - Self-declared environmental claims (Type II environmental labelling) »</i>			

Schneider Electric Industries SAS

Country Customer Care Center
<http://www.schneider-electric.com/contact>

35, rue Joseph Monier
 CS 30323
 F- 92506 Rueil Malmaison Cedex
 RCS Nanterre 954 503 439
 Capital social 896 313 776 €

www.schneider-electric.com

ENVPEP1409022_V2

Published by Schneider Electric

© 2020 - Schneider Electric – All rights reserved

11/2020