

USB 3.1 Type-C to DisplayPort Adapter (DP Altmode)

User Manual



Contents

1.0 INTRODUCTION 1

2.0 FEATURES 1

3.0 SPECIFICATIONS 1

4.0 PACKAGE CONTENTS 2

5.0 OPERATION 2

6.0 CONNECTION DIAGRAM 2

USB 3.1 Type-C to DisplayPort Adapter (DP Altmode)

DEAR CUSTOMER

Thank you for purchasing this product. For optimum performance and safety, please read these instructions carefully before connecting, operating or using this product. Please keep this manual for future reference.

1.0 INTRODUCTION

The USB-C to DisplayPort Adapter (DP Altmode) allows you to connect an extra monitor with DP port to your new Macbook or Chromebook. You can watch videos or slideshows together on the big screen.

2.0 FEATURES

- Supports USB-C input and DisplayPort output
- Supports DisplayPort 1.2 Altmode
- Supports per lane data rates of 5.4Gbps (HBR2), 2.7Gbps (HBR) and 1.62Gbps (RBR)
- Supports content protection of HDCP
- Supports DisplayPort resolution up to 3840x2160@60Hz
- USB bus power (no external power supply)

3.0 SPECIFICATIONS

Inputs/Output Connector	
Input	USB-C Malex1
Output	DisplayPort Femalex1
Resolutions	
Resolutions	Max up to 3840X2160
Warranty	
Limited Warranty	1 Year
Physical	
Weight	21.5g

Size(L-W-H)	42x35x16 (mm) Cable:150mm
Environmental	
Operating Temperature	0 °C to +45°C
Operating Humidity	10% to 85 % RH (no condensation)
Storage Temperature	-10°C to +70°C
Storage Humidity	5% to 90 % RH (no condensation)
Regulatory Approvals	
Certifications	FCC,CE
Power Requirement	
Power Source	USB bus power
Accessories Adapter	
User Manual	English Version

4.0 PACKAGE CONTENTS

Before attempting to use this unit, please check the packaging and make sure the following items are contained in the shipping carton:

- Main unit x1
- User Manual x1

5.0 OPERATION

- ① Connect USB-C port of this product to the Macbook
- ② Connect DisplayPort output of this product to HDTV with one DisplayPort cable

6.0 CONNECTION DIAGRAM

