

USB 3.1 Type-C to HDMI Adapter (DP Altmode)

User Manual



Contents

1.0 INTRODUCTION	1
2.0 FEATURES	1
3.0 SPECIFICATIONS	1
4.0 PACKAGE CONTENTS	2
5.0 OPERATION	2
6.0 CONNECTION DIAGRAM	2

USB 3.1 Type-C to HDMI Adapter (DP Altmode)

DEAR CUSTOMER

Thank you for purchasing this product. For optimum performance and safety, please read these instructions carefully before connecting, operating or using this product. Please keep this manual for future reference.

1.0 INTRODUCTION

This USB-C to HDMI Adapter (DP Altmode) allows you to connect an extra monitor with HDMI port to your new Macbook or Chromebook. You can watch videos or slideshows together on the big screen.

2.0 FEATURES

- Supports USB-C input and HDMI output
- Supports DisplayPort 1.2 Altmode
- Supports per lane data rates of 2.7Gbps (HBR) and 1.62Gbps (RBR)
- Supports content protection of HDCP
- Supports HDMI resolution max up to 4kx2k@30Hz
- USB bus power (no external power supply)

3.0 SPECIFICATIONS

Input/Output Connector	
Input	USB-C Male x1
Output	HDMI Female x1 (HDMI 1.4)
Resolutions(HDTV)	
Resolutions	480i/480P/720P/1920X1080/1920 X1200/3840X2160
Mechanical	
Size(W-L)	Main Unit:37*42mm Cable: 150mm

Warranty	
Limited Warranty	1 Year
Environmental	
Operating Temperature	0 °C to +45°C
Operating Humidity	10% to 85 % RH (no condensation)
Storage Temperature	-10°C to +70°C
Storage Humidity	5% to 90 % RH (no condensation)
Regulatory Approvals	
Certifications	FCC,CE
Power Requirement	
Power Source	USB Bus Power
Accessories Adapter	
User Manual	English Version

4.0 PACKAGE CONTENTS

Before attempting to use this unit, please check the packaging and make sure the following items are contained in the shipping carton:

- Main unit x1
- User Manual x1

5.0 OPERATION

- ① Connect USB-C port of this product to the Macbook
- ② Connect HDMI output of this product to HDTV with one HDMI cable

6.0 CONNECTION DIAGRAM

