

Goulottes de protection pvc / alu

Norme(s) :

(M = Marron, I = Ivoire, A = Gris)

Code SM-CI	Référence	Codet Enedis	L (mm)	Capacité maxi (mm ²)
P977033004	GPC 35 35	68 80 540	2,75	3 x 50 + 50 (ø 35)
P977033005	GPC 35 35 M	68 80 562	2,75	3 x 50 + 50 (ø 35)
P977033006	GPC 35 35 I	68 80 572	2,75	3 x 50 + 50 (ø 35)
P977033007	GPC 60 60	68 80 542	2,75	3 x 150 + 70 (ø 60)
P977033008	GPC 60 60 M	68 80 563	2,75	3 x 150 + 70 (ø 60)
P977033009	GPC 60 60 I	68 80 573	2,75	3 x 150 + 70 (ø 60)
P977033010	GPC 90 90	68 80 544	2,75	3 x 240 + 95 (ø 90)
P977033011	GPC 90 90 M	68 80 564	2,75	3 x 240 + 95 (ø 90)
P977033012	GPC 90 90 I	68 80 574	2,75	3 x 240 + 95 (ø 90)
P977033001	GPT 30 30	68 80 535	2,60	1 x 29 Cu (ø 16)
P977033002	GPT 30 30 M	68 80 560	2,60	1 x 29 Cu (ø 16)
P977033003	GPT 30 30 I	68 80 570	2,60	1 x 29 Cu (ø 16)
Code SM-CI	Référence	Codet Enedis	L (mm)	Capacité maxi (mm ²)
S2565012	GPT 30 30 ALU	68 80 536	2,60	2,60
S2565014	GPC 35 35 ALU	68 80 541	2,75	2,75
S2565016	GPC 60 60 ALU	68 80 543	2,75	2,75
S2565018	GPC 90 90 ALU	68 80 545	2,75	2,75
S2565020	GPC 140-50 ALU	68 80 547	2,75	2,75

