

0010400	DATA SHEET	
valid from: 01.01.2019	ÖLFLEX® CLASSIC 100 YELLOW	

Application

ÖLFLEX® CLASSIC 100 yellow cables are PVC connecting cables for flexible use and fixed installation for medium mechanical use for special warning feature in accordance to VDE 0113 part 1 that is EN 60204 part 1. They are suitable for use in dry, damp and wet areas. If using outdoors, observe the indicated temperature range and use with UV protection. They are largely resistant to acids, alkalis and certain oils at room temperature.

ÖLFLEX® CLASSIC 100 yellow cables are suitable for occasional, non-automated movements. They meet the requirements for slow rotational movements, such as in the loop of a wind turbine. The maximum tensile load is 15 N/mm² of conductor cross-section during installation and operation. Compulsory guidance is not permitted.

This cable is suitable for torsion application in wind turbines (WTG). The torsional load is limited to applications, as they typically occur in the loop of a wind turbine.

Design

Design	based on EN 50525-2-11 resp. VDE 0285-525-2-11 EN 50525-2-51 resp. VDE 0285-525-2-51
Conductor	bare copper, fine wire strand in acc. with IEC 60228 resp. VDE 0295, Class 5
Insulation	PVC compound T12 acc. to EN 50363-3 resp. VDE 0207-363-3 with increased requirements acc. to Lapp specification
Core identification code	acc. to VDE 0293-1, with GN/YE protective conductor coloured acc. to VDE 0293-308 / HD 308 S2
Stranding	cores are stranded in layers
Outer sheath	PVC compound TM2 acc. to EN 50363-4-1 resp. VDE 0207-363-4-1 with increased requirements acc. to LAPP specification colour: yellow, similar RAL 1016

Electrical properties at 20°C

Rated voltage	U ₀ / U: 450 / 750 V
Test voltage	core / core: 4000 V AC

Mechanical and thermal properties

Minimum bending radius	occasional flexing: 15 x cable diameter fixed installation: 4 x cable diameter
Temperature range	occasional flexing: - 5 °C up to +70 °C max. conductor temp. fixed installation: - 40 °C up to +80 °C max. conductor temp.
Torsional stress	in WTG: TW-0 (5000 cycles at ≥ +5 °C) TW-1 (2000 cycles at ≥ -20 °C) ± 150° /m at 1 revolution per minute
Flammability	flame retardant acc. to IEC 60332-1-2 resp. VDE 0482-332-1-2
Tests	acc. to IEC 60811, EN 50395, EN 50396
General requirements	These cables are conform to the EU-Directive 2014/35/EU (Low Voltage Directive)

Creator: HESC / PDC	Document: DB0010400EN	Page 1 of 1
Released: ALTE / PDC	Version: 06	