

15382000	DATA SHEET	
Valid from: 10.12.2018	ÖLFLEX® TRAIN HT 150 F 1,8kV	

Application

ÖLFLEX® TRAIN HT 150 F 1,8kV are single core silicone rubber insulated high temperature cables for railway rolling stock, having special fire performance.
They are designed for fixed installation and for applications, where limited movement may occur. They are particularly used in areas, where human and animal life as well as valuable property are exposed to high risk of fire hazards.
ÖLFLEX® TRAIN HT 150 F 1,8kV are ozone-, oil-, acid and alkali-resistant according to EN 50382-2.

Application range:

Railway vehicles: Wiring of control cabinets, distributors, converters, motors and batteries

Design

Design/type-standard	according to EN 50382-2, 1800V, code designation F F = low temperature resistant, oil-resistant
Classification	EN 45545-2: Hazard Level HL1, HL2, HL3
Conductor	fine wire strands of tinned copper acc. to IEC/EN 60228 resp. VDE 0295, Class 5
Separator	semi-conductive tape, black
Core insulation	silicone compound type EI 111 according to EN 50382-2
Core identification	black

Electrical properties

Nominal voltage	U_0/U : 1,8/3 kV AC
Max. permissible operating voltage	U_m : 3,6 kV AC V_0 : 2,7 kV DC
Test voltage	core / core: 6,5 kV AC; 15 kV DC

Mechanical and thermal properties

Min. bending radius	fixed installation: 3 x cable diameter occasional flexing: 5 x cable diameter
Temperature range	-40 °C to +150 °C max. conductor temperature
Short circuit temperature	max. +250 °C (5s)

Fire protection according to EN 50382-2 / EN 45545:

Classification	EN 45545-2: Hazard Level HL1, HL2, HL3
Flammability	acc. to EN 60332-1-2 resp. VDE 0482-332-1-2
No flame propagation acc. to	≥ 12 mm: EN 60332-3-24 / VDE 0482-332-3-24 > 6 mm and < 12mm: EN 60332-3-25 / VDE 0482-332-3-25
Smoke density	acc. to EN 50382-1, light transmission: min. 70% acc. to IEC/EN 61034-2

Creator: JUBE/PCM	Document: DB15382000EN	Page 1 of 2
Released: ALTE/PDC	Version: 01	

We reserve all rights according to DIN ISO 16016.

PD 0019/05_04.18EN

15382000	DATA SHEET	
Valid from: 10.12.2018	ÖLFLEX® TRAIN HT 150 F 1,8kV	

Halogen-free	acc. to IEC/EN 60754-1 (chlorine and bromine) acc. to EN 60684-2 (fluorine)
Corrosivity	acc. to EN 50382-1: pH ≥ 4.3 and conductivity ≤ 10µS/mm acc. to IEC/EN 60754-2
Toxicity	acc. to EN 50382-1 (≤ 3) acc. to EN 50305

Material properties

Ozone resistance	acc. to EN 50382-2 / EN 50305
Mineral oil resistance	acc. to EN 50382-2 / EN 60811-2-1
Acid and alkali resistance	acc. to EN 50382-2 / EN 60811-2-1
Tests	acc. to EN 50382-2

Article number	Conductor cross section [mm ²]	Max. wire ø [mm]	Max. DC conductor resistance (20°C) [Ohm/km]	Conductor ø reference value [mm]	Core ø min. – max. [mm]	Weight [kg/km]
15382000	1,5	0,26	13,7	1,5	6,3 - 7,3	57
15382001	2,5	0,26	8,21	2,0	6,7 - 7,8	69
15382002	4	0,31	5,09	2,5	7,2 - 8,4	86
15382003	6	0,31	3,39	3,0	7,7 - 9,0	107
15382004	10	0,41	1,95	3,9	8,5 - 10,0	151
15382005	16	0,41	1,24	5,0	9,6 - 11,2	219
15382006	25	0,41	0,795	6,4	10,9 - 12,7	305
15382007	35	0,41	0,565	7,7	12,1 - 14,1	394
15382008	50	0,41	0,393	9,2	13,5 - 15,8	540
15382009	70	0,51	0,277	11,0	15,2 - 17,8	725
15382010	95	0,51	0,210	12,5	17,0 - 19,9	961
15382011	120	0,51	0,164	14,2	18,6 - 21,7	1182
15382012	150	0,51	0,132	15,8	20,1 - 23,5	1438
15382013	185	0,51	0,108	17,5	21,7 - 25,4	1760
15382014	240	0,51	0,0817	20,1	24,1 - 28,2	2249
15382015	300	0,51	0,0654	22,5	26,4 - 30,9	2680
15382016	400	0,51	0,0486	25,8	29,9 - 34,9	3450

Creator: JUBE/PCM Released: ALTE/PDC	Document: DB15382000EN Version: 01	Page 2 of 2
---	---------------------------------------	-------------