DATA SHEET

valid from: 28.09.2021 H07ZZ-F (X07ZZ-F)



Application

1600804

H07ZZ-F (X07ZZ-F) are halogen-free, heat-resistant hose cables for heavy stress and especially for applications where low smoke density and low emission of corrosive gases are required at in case of fire. Suitable for connection with equipment and machine tools, where cables for heavy mechanical stress are required. In dry, damp or wet rooms. Also for installation e.g. on plaster in temporary buildings and residential barracks.

Design

Design acc. to EN 50525-3-21

Certification The cable is characterized with the ⊲HAR⊳ HAR-sign or HAR-identification thread.

Conductor fine-wire copper conductor acc. to IEC 60228 resp. EN 60228, class 5

Insulation halogen-free rubber compound EI8 acc. to EN 50363-5

Core identification code up to 5 cores:

colour-coded acc. to VDE 0293-308 with or without GN-YE ground conductor

starting at 6 cores:

black cores with white numbers with GN-YE ground conductor

acc. to EN 50334

Outer sheath for cable up to 50 mm²:

single-layered: EM 8 acc. to EN 50363-6

for cable starting at 70 mm²:

double-layered:

inner layer EM 8 or EM 10 acc. to EN 50363-6 outer sheath: EM 8 acc. to EN 50363-6

Electrical properties at 20 °C

Nominal voltage U_0/U : 450/750 V Test voltage A / A: 2500 V AC

Mechanical and thermal properties

Minimum bending radius 4 to 8 x outer diameter acc. to DIN EN 50565-1

Temperature range occasional flexing: - 5 °C to +90 °C max. conductor temperature

fixed installation: -40 °C to +90 °C max. conductor temperature

Flammability flame retardent acc. to IEC 60332-1-2 resp. EN 60332-1-2 no

flame propagation acc. to IEC 60332-3-24 resp. EN 60332-3-24

Halogen freeacc. to EN 50525-1 Appendix B and CCorrosivity of gasesacc. to IEC 60754-2 resp. EN 60754-2Smoke densityacc. to IEC 61034-2 resp. EN 61034-2

Ozone resistance acc. to EN 50363-3, EN 60811-403 method A, EN 50396 8.1.3 method B

Tests acc. to IEC 60811 resp. EN 60811, EN 50395, EN 50396 and EN 50363-3.

General requirements These cables are conform to the EU-Directive 2014/35/EU (Low Voltage Directive)

Environmental information These cables meet the substance-specific requirements of the EU Directive 2011/65/EU (RoHS).

Note Trade product, no Lapp product

Creator: LABU / PDC Document: DB1600804EN

Released: ALTE / PDC Version: 07

Page 1 of 1