


2170300	DATA SHEET	
valid from: 2023-06-26	ETHERLINE® P FLEX Cat. 5e 4x2x26/7 AWG	

Application

Field of use:	Flexible Industrial Ethernet cable for generic cable system acc. to ISO/IEC 11801 and EN 50173. Suitable for occasional flexing. Meeting the transmission requirements of IEC 61156-6, Category 5e and EN 50288-2-2.
Performance:	4-pair, overall braid and foil screened symmetrical cable (SF/UTP), having a nominal impedance of 100 Ω, supporting a bandwidth of 100 Mbit/s (e.g. 10BASE-T, 100BASE-T) over up to 60 m.
Characteristics:	flame retardant, halogen free, oil-resistant, UV-resistant, abrasion resistant, largely resistant to acids, alkalis and certain oil
Applications:	CC-Link IE, EtherCAT, EtherNet/IP and other




Design

Certification	E63634 cRUus AWM Style 21576 AWM I/II A/B 1000 V 80 °C FT2 acc. to UL 758 and CSA C22.2 No.210 KBA type approval ECE-R 118: E1*118R03/01*0228*00 certified for CC-Link IE Field Network
Conductor	stranded bare copper 26/7 AWG
Insulation	PO (Polyolefine) core diameter: max. 1.04 mm
Core identification code	pair 1: white-blue/blue; pair 2: white-orange/orange; pair 3: white-green/green; pair 4: white-brown/brown
Stranding	cores twisted to pairs four pairs stranded to bundle
Taping	plastic tape
Screen	plastic laminated aluminum foil on top: braid of tinned copper wires (coverage nom. 85 %)
Outer sheath	TPU (Thermoplastic polyurethane) blue, similar RAL 5021 outer diameter: 6.2 mm ± 0.3 mm

Electrical properties at 20 °C

Loop resistance	≤ 28 Ω/100 m	
Test voltage	core/core:	3000 V
	core/screen:	3000 V
Maximum operating voltage	125 V (not for power applications)	
Insulation resistance	≥ 5 GΩxkm	
Mutual capacitance	1 kHz:	nom. 50 nF/km
Capacitance unbalance	1 kHz:	≤ 1600 pF/km
Transfer impedance	Grade 1 acc. to IEC 61156-6	
	1 MHz:	≤ 15 mΩ/m
	10 MHz:	≤ 10 mΩ/m
	30 MHz:	≤ 30 mΩ/m
	100 MHz:	≤ 100 mΩ/m
Coupling attenuation	Type I acc. to IEC 61156-6	
	30 MHz:	≥ 85

Creator: KIOS / PDC	Document: DB2170300EN	Page 1 of 2
Released: ALTE / PDC	Version: 10	

2170300	DATA SHEET	
valid from: 2023-06-26	ETHERLINE® P FLEX Cat. 5e 4x2x26/7 AWG	

	100 MHz:	≥ 85
	1000 MHz:	≥ 65
Velocity of propagation	100 MHz:	nom. 67 c
Characteristic impedance	nom. 100 Ω acc. to IEC 61156-6	

Transmission properties at 20°C

The transmission characteristics meet the requirements of IEC 61156-6 for category 5e.

Frequency	(max.) Phase delay	(max.) Differential delay	(max.) Attenuation	(min.) TCL Level 1	(min.) EL TCTL Level 1	(min.) NEXT	(min.) PS NEXT	(min.) ACR-F	(min.) PS ACR-F	Char. Impedance	(min.) RL
f [MHz]	[ns/ 100 m]	[ns/ 100 m]	[dB/ 100 m]	[dB]	[dB]	[dB]	[dB]	[dB/ 100 m]	[dB/ 100 m]	[Ohm]	[dB]
4	552.0	45.0	6.0	34.0	23.0	56.3	53.3	55.0	52.0	—	23.0
10	545.4	45.0	9.5	30.0	15.0	50.3	47.3	49.0	46.0	—	25.0
16	543.0	45.0	12.1	28.0	10.9	47.2	44.2	45.9	42.9	—	25.0
20	542.0	45.0	13.5	27.0	9.0	45.8	42.8	44.5	41.5	—	25.0
30	540.6	45.0	16.7	25.2	5.5	43.1	40.1	41.8	38.8	—	23.5
62.5	538.6	45.0	24.8	22.0	—	38.4	35.4	37.1	34.1	—	20.7
100	537.6	45.0	32.0	20.0	—	35.3	32.3	34.0	31.0	100 ± 5	19.0

Mechanical and thermal properties

Minimum bending radius	fixed installation:	8× outer diameter
	occasional flexing:	15× outer diameter
Temperature range	fixed installation:	-20°C up to +80°C
	occasional flexing:	-5°C up to +50°C
	UL:	80 °C
Flammability	flame retardant acc. to ISO 6722-1 and IEC 60332-1-2 resp. EN 60332-1-2 FT2 acc. to UL 1581 §1100	
Halogen free	acc. to IEC 60754-1 resp. EN 60754-1	
UV resistance	acc. to ISO 4892-2, method A	
Oil resistance	acc. to EN 50363-10-2	

General requirements

These cables are conform to the EU-Directive 2011/65/EU (RoHS, Restriction of the use of certain hazardous substances) and the LV-Directive 2014/35/EU (Low voltage Directive).

Environmental information

These cables meet the substance-specific requirements of the EU Directive 2011/65/EU (RoHS).

Creator: KIOS / PDC	Document: DB2170300EN	Page 2 of 2
Released: ALTE / PDC	Version: 10	