22260766 **DATA SHEET**Valid from: 17.09.2018 **AB-C5-M12MS-DN-TR**



Description

Terminating resistor CANopen®/DeviceNet™ M12

General characteristics

Type of connection M12

Protection class IP 65 / IP 67

Number of pins 5

Coding A-standard

Ambient Temperature (operation) -25 to +90 °C (-13 to 194 °F)

Mechanical characteristics

Contact, material CuSn
Contact surface, material Ni/Au
Contact carrier, material TPU GF

Grip body, material TPU, hardly inflammable, self-extinguishing


Knurl, material Zinc die-cast, nickel-plated


Inflammability class acc. to UL 94 HB

Electrical characteristics

 $\begin{array}{lll} \text{Rated voltage} & 60 \text{ V} \\ \text{Rated current} & 4 \text{ A} \\ \text{Overvoltage category} & \text{II} \\ \text{Pollution degree} & 3 \\ \text{Terminating resistor} & 120 \text{ }\Omega \\ \end{array}$

Technical Drawing






Terminating resistor M12





Pin assignment M12 plug, A-coded, 5-pos.

Circuit diagram



Internal wiring of connections

Application range

Machine and equipment manufacturing

Note

Photographs are not to scale and do not represent detailed images of the respective products.

Creator: MOKO2/PDP	Document: DB22260766EN	Page 1 of 1
Released: IVSE1/PDP	Version: 03	