

55507360	DATA SHEET	
Valid from: 03.07.2018	SILVYN® FPAX R	

SILVYN® FPAX R is a reducer conduit gland with fast fit and an inner seal for a safety assembling. For the demounting we are recommending to use a screwdriver. The gland is suitable for SILVYN® FPAS and can be used in the machine- and plant constructions.



Material: Body – PA66
Seal – Polyester

Features: Fast assembling
Anti-vibration
Suitable for fine and coarse conduits
High mechanical strength

Temperature range: -50°C up to +135°C

Colour: Black (UV-Resistant)

Norm Reference:



Note: Free of halogen, Sulphur and phosphorus

Protection class: IP66, IP67 and IP68 (2bar)

Dimension table:

Part no.	Part name	Conduit Ø		Length mm	Largest Ø mm	Clearance hole mm
		Input value mm	Output value mm			
5550 7360	SILVYN® FPAX R	13	16	43,2	22,5	11,7
5550 7361	SILVYN® FPAX R	16	21	51	29,5	14,5
5550 7363	SILVYN® FPAX R	16	28	57	33,8	14,5
5550 7362	SILVYN® FPAX R	21	28	58,5	33,8	17,5
5550 7366	SILVYN® FPAX R	16	34	58,3	44,1	14,5
5550 7365	SILVYN® FPAX R	21	34	59,8	44,1	17,5
5550 7364	SILVYN® FPAX R	28	34	64,8	44,1	25,7
5550 7369	SILVYN® FPAX R	21	42	59,8	50	17,5
5550 7368	SILVYN® FPAX R	28	42	64,8	50	25,7
5550 7367	SILVYN® FPAX R	34	42	66,8	50	31,5

For more information please see our current catalogue. Please do not hesitate to contact our laboratory if there are any questions regarding resistance against aggressive agents and special oil.

Creator: M. Wegerer /PDP Released: DAMU1/PDP	Document: DB55507360EN Version: 01	Page 1 of 1
---	---------------------------------------	-------------