

## OBICO 5,4W 550lm 827/830/840 IP65 DIM Blanc 0005363



### Caractéristiques de la gamme

• OBICO 5,4W 550lm 927/930/940 IP65 DIM Blanc - Spot d'accentuation LED étanche à l'air répondant aux exigences des réglementations RE2020 (label BBC). Recouvrable d'isolant déroulé ou projeté. Diamètre d'encastrement 68mm. Connecteur rapide repiquable (LiLo). Dimmable. Orientable à 360°. 3 températures de couleur 2700K, 3000K et 4000K. IRC90. Flux lumineux 550lm. Puissance consommée 5,4W. Efficacité lumineuse 102lm/W. IP65/20 - IK03. Groupe de risque photobiologique RG1. Classe II. Durée de vie : 100 000h (L80B10). Garantie 5 ans. Sylv...

### CIBSE TM66

Result				How to analyse the score	
Category	Points Scored	Maximum possible points	Assessment	Score Range	Performance Level
Product design	34	134.0	1	0.0 to 0.5	Very poor circular economy performance
Manufacturing	17.1	46.5	1.5	0.5 to 1.5	Some circular economy functionality
Materials	2	24.0	0.3	1.5 to 2.5	Definite/substantial progress to circularity
Ecosystem	17	43.0	1.6	2.5 to 4.0	Excellent circularity
Overall performance	70.1	247.5	1.10		

Technical Memorandum (TM) 66 describes a Circular Economy's main aims, how it can be achieved and what its practice will mean to the different branches of our industry like specifiers, manufacturers, contractors, and Facilities Managers.

The Circular Economy Assessment Method for Manufacturing (CEAM-Make)'s list of 66 searching questions, the majority of which ask for back-up evidence, is split into four sections :

- Product Design : Covering topics such as design for long life and repair
- Manufacturing : Additive and subtractive techniques and localisation
- Materials : Usage of recyclable materials rather than virgin
- Ecosystem : Repair or upgrade services to complement circular economy design

The outcome of the assessment is a single figure rating by which product comparisons can be made. A TM66 score demonstrates a product's performance in the context of a Circular Economy