

Insaver Slim G2 UGR19 150 9,5W 1200lm 840 DALI
0030535



Caractéristiques de la gamme

• Insaver Slim G2 UGR19 150 9,5W 1200lm 840 DALI - Downlight LED rond avec dissipateur aluminium alliant confort visuel et performances élevées. Lentilles en polycarbonate spécialement conçues avec réflecteur en aluminium permettant un éblouissement de niveau UGR<19. Température de couleur (CCT) 4000K, IRC80. Flux lumineux sortant 1200lm. Driver Dali fourni compatible avec bouton poussoir. Puissance consommée 9,5W. Efficacité lumineuse 126lm/W. SDCM:3. Durée de vie (L80) : 90.000h. IP44, IK07. Classe II. 850°C. Diamètre 164mm. Hauteur 5...

CIBSE TM66

Result					
Category	Points Scored	Maximum possible points	Assessment	How to analyse the score	
Product design	60	134.0	1.8	0.0 to 0.5	Very poor circular economy performance
Manufacturing	17.1	46.5	1.5	0.5 to 1.5	Some circular economy functionality
Materials	0	24.0	0	1.5 to 2.5	Definite/substantial progress to circularity
Ecosystem	18	43.0	1.7	2.5 to 4.0	Excellent circularity
Overall performance	95.1	247.5	1.25		

Technical Memorandum (TM) 66 describes a Circular Economy’s main aims, how it can be achieved and what it’s practice will mean to the different branches of our industry like specifiers, manufacturers, contractors, and Facilities Managers.

The Circular Economy Assement Method for Manufacturing (CEAM-Make)’s list of 66 searching questions, the majority of which askfor back-up evidence, is split into four sections :

- Product Design :
Manufacturing :
Materials :
Ecosystem :
- Covering topics such as design for long life and repair
Additive and subtractive techniques and localisation
Usage of recyclable materials rather than virgin
Repair or upgrade services to complement circular economy design

The outcome of the assement is a single figure rating by which product comparisons can be made. A TM66 score demonstrates a product’s performance in the context of a Circular Economy