



Caractéristiques de la gamme

- Colossal 900mm 59,4W 6955lm PRISM Blanc 940 SSA - Luminaire architectural de grand diamètre (900mm). Installation saillie ou suspendue. Cerclage aluminium sans soudure. coloris blanc (RAL9016). Flux lumineux : 6955lm, puissance consommée : 59,4W. Efficacité lumineuse : 117lm/W. Optique prismatique, UGR<19. SDCM≤3, IRC>90. 650°C, classe 1. Groupe de risque photobiologique : 0. Système de gestion SylSmart Connected avec capteur intégré, hauteur de détection max 5m. IP40, IK07. Dimensions : 888x93mm. Durée de vie : 66.000h (L90). Garant...

CIBSE TM66

Result				How to analyse the score	
Category	Points Scored	Maximum possible points	Assessment	Score Range	Description
Product design	65	134.0	2.3	0.0 to 0.5	Very poor circular economy performance
Manufacturing	21.5	46.5	1.9	0.5 to 1.5	Some circular economy functionality
Materials	5	24.0	0.8	1.5 to 2.5	Definite/substantial progress to circularity
Ecosystem	18	43.0	1.7	2.5 to 4.0	Excellent circularity
Overall performance	109.5	247.5	1.68		

Technical Memorandum (TM) 66 describes a Circular Economy's main aims, how it can be achieved and what its practice will mean to the different branches of our industry like specifiers, manufacturers, contractors, and Facilities Managers.

The Circular Economy Assessment Method for Manufacturing (CEAM-Make)'s list of 66 searching questions, the majority of which ask for back-up evidence, is split into four sections :

- Product Design : Covering topics such as design for long life and repair
- Manufacturing : Additive and subtractive techniques and localisation
- Materials : Usage of recyclable materials rather than virgin
- Ecosystem : Repair or upgrade services to complement circular economy design

The outcome of the assessment is a single figure rating by which product comparisons can be made. A TM66 score demonstrates a product's performance in the context of a Circular Economy