

DIGITUS® Aluminum Outlet Strip, 10 outlets IEC C13, with overload protection



✓ 19" rack mount
✓ 10x outlet IEC C13
✓ Overload protection
✓ Aluminum profile

Abstract

DIGITUS® Aluminum Outlet Strip, 10 outlets IEC C13, with overload protection

Features

- Safe and professional power in the 19" range
- 10 IEC C13 socket outlets 250 VAC 50/60 Hz / 10 A / 2500 W
- Aluminum profile
- Overload protection
- 2 mounting brackets included, variable to change from left to right
- Cable: 2 m H05VV-F 3G1,5 mm²
- IEC C14 plug

Product Overview

The DIGITUS® power distribution units are the perfect solution for you 19" network- or server cabinet. Optimized for rack installation with 220-240 V 50-60 Hz the DIGITUS® PDU offer you the best performance with qualified efficiency. The 19" fixing material provides an optimized enclosing on the profile rails of your cabinets. Every PDU can be mounted horizontally as well as vertically and has the possibility, according to the cabinet, to be mounted faced up or down.

Product Images





Assmann Electronic GmbH, Auf dem Schüffel 3, 58513 Lüdenscheid, Germany, info@assmann.com, printing errors, falsities and technical changes remain reserve



Product Number Information

DN-95404 DIGITUS® 1U Aluminum PDU, rack mount, 10 A, 2500 W, 250VAC 50/60 Hz,

10x IEC C13, overload protection

More Power Distribution Units (PDU) from DIGITUS®

	· ·
DN-95401	DIGITUS® 1U Aluminum PDU, rack mount, 16 A, 4000 W, 250 VAC 50/60 Hz,
	8x safety outlets
DN-95402	DIGITUS® 1U Aluminum PDU, rack mount, 16 A, 4000 W, 250V AC 50/60 Hz,
	7x safety outlets, switch
DN-95403	DIGITUS® 1U Aluminum PDU, rack mount, 16 A, 4000 W, 250 VAC 50/60 Hz,
	7x safety outlets, overload protection
DN-95405	DIGITUS® 1U Aluminum PDU, rack mount, 2x 16 A, 250 VAC 50/60 Hz, 12x safety outlets,
	overload protection
DN-95407	DIGITUS® 1U Aluminum PDU, rack mount, 16 A Plug, 250 VAC 50/60 Hz, 7 way safety outlet,
	with switch, surge protection
DN-95408	DIGITUS® 1U Aluminum PDU, 6 way IEC C19, power cable IEC C20
DN-95411	DIGITUS® 1U Aluminum PDU, rack mount, for 254 mm (10") cabinet, 16 A, 4000 W,
	250 VAC 50/60 Hz, 3x safety outlets
DN-95601	DIGITUS® Metering PDU, 1U, rackmountable, max. 16 A, 7x safety outlets, 1xRJ45, LCD panel,
	measuring power, electricity, tension
DN-95602	DIGITUS® Metering PDU, 1U, rackmountable, max. 10 A, 8x IEC C13, 1x RJ45, LCD Panel,
	measuring power, electricity, tension
Δ-19-STRIP42-1	18 way outlet strip - 4211 in length vertical, dual circuit, aluminum, 2x 16 A

A-19-STRIP42-1 18 way outlet strip - 42U in length vertical, dual circuit, aluminum, 2x 16 A, circuit breaker, vertical mount