

PRODUCT-DETAILS

# E217-16-10G

E217-16-10GLuminous Pushbutton, 16 A, acc. to EN 250 V AC, 1NO, 0NC, 0CO, EI.  
Color: Grey, 1LED, Blue, MW: 0.5



## Informations générales

|                              |   |
|------------------------------|---|
| Extension du type de produit | E217-16-10G   |
| Code de produit              | 2CCA703164R0001   |
| EAN                          | 7612270939022   |
| Description courte           | E217-16-10GLuminous Pushbutton, 16 A, acc. to EN 250 V AC, 1NO, 0NC, 0CO, EI.<br>Color: Grey, 1LED, Blue, MW: 0.5   |
| Description longue           | Pushbutton 1 NO / 1 NC with maintenance-free LED, Rated current: 16A/250 VACPDC, LED colour: blue, 115-250 VACPDC, 12-48 VACDCPDC, 110-220 VDCPDC, Module width 0,5 |

## Technique

|                                    |   |
|------------------------------------|---|
| Normes et standards                | EN60068-2-1<br>EN60068-2-2<br>EN60068-2-30<br>DIN EN 60669-1<br>VDE 0632-1<br>UL508 |
| Tension nominale (U <sub>r</sub> ) | Lamp 230 ... 250 V  |
| Tension                            | acc. to EN 250 V AC<br>acc. to UL 508 240 V AC                                      |
| Voltage Range                      | 115 ... 250 V AC  |
| Auxiliary Voltage AC/DC            | LED Indicator 115...250 V AC  |
| Maximum Switching Voltage          | 250 V   |
| Courant nominal (I <sub>n</sub> )  | 16 A  |

|  |   |
|--|---|
| Fréquence assignée (f)                 | 50/60 Hz  |
| Power Loss                             | 1.1 W   |
| Puissance Watt                         | 1.5 W   |
| Number of Contacts CO                  | 0   |
| Number of Contacts NC                  | 0   |
| Number of Contacts NO                  | 1   |
| Number of Main Contacts NC             | 0   |
| Number of Main Contacts NO             | 1   |
| Number of Auxiliary Contacts CO (SPDT) | 0   |
| Nombre de pôles                        | 1   |
| Nombre de LED                          | 1   |
| Couple de serrage                      | 1.2-1.5 N·m   |
| Switch Type                            | Double Interrupting Contacts  |
| Material of Conductor                  | Copper  |
| Options Provided                       | 1 NO  |
| Remarques                              | Sealable in the On and Off positions  |
| Couleur                                | Blue  |
| Control Element Color                  | Grey  |
| Lamp Color                             | Blue  |
| Connecting Capacity                    | Solid 1x1...6 mm <sup>2</sup><br>Solid 2x2.5 mm <sup>2</sup><br>Flexible 1x0.75...2x2.5 mm <sup>2</sup> |

## Environnement

|   |  |
|---|--|
| Température de l'air ambiant                | Operation -25...+55 °C<br>Storage -40...+70 °C                         |
| Indice de protection                        | IP20   |
| Statut RoHS                                 | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |
| Informations RoHS                           | 2CCC441014D0201  |
| REACH Declaration                           | 2CCC005047D0201  |
| Informations environnementales              | 2CCC441003C0201  |
| Conflict Minerals Reporting Template (CMRT) | 9AKK108468A3363  |

## Dimensions

|   |       |
|---|-------|
| Width in Number of Modular Spacings         | 0.5   |
| Produit Largeur Net                         | 9 mm  |
| Produit Hauteur Net                         | 85 mm |
| Produit Longueur Net                        | 68 mm |
| Poids net                                   | 53 g  |
| Profondeur d'encastrement (t <sub>2</sub> ) | 68 mm |

## Commande

|                           |              |
|---------------------------|--------------|
| Emballage Niveau 1 Unités | box 10 pièce |
|---------------------------|--------------|

|                          |           |
|--------------------------|-----------|
| Emballage Niveau 1 Poids | 594 g     |
| E-Number (Finland)       | 2312342   |
| E-Number (Switzerland)   | 467552188 |

## Certificats et Déclarations (Numéro de document)

|                                     |                 |
|-------------------------------------|-----------------|
| CB Certificate                      | 9AKK108466A3845 |
| CCC Certificate                     | 9AKK108466A3829 |
| Déclaration de Conformité<br>- CE   | 2CCC441014D0201 |
| Declaration of Conformity<br>- UKCA | 9AKK108467A6137 |
| EAC Certificate                     | 9AKK107991A4779 |
| VDE Certificate                     | 9AKK107991A9822 |

## Installation

|                         |                    |
|-------------------------|--------------------|
| Instructions et manuels | No document needed |
|-------------------------|--------------------|

## Downloads Préférés

|   |                 |
|---|-----------------|
| Fiche produit, informations<br>techniques | 2CCC441003C0101 |
|---|-----------------|

## Classifications

|                                   |  |
|-----------------------------------|--|
| ETIM 8                            | EC001546 - Push button for distribution board              |
| ETIM 9                            | EC001546 - Push button for distribution board              |
| Catégorie DEEE                    | 5. Small Equipment (No External Dimension More Than 50 cm) |
| WEEE B2C / B2B                    | Business To Consumer                                       |
| CN8                               | 85365053   |
| eClass                            | V11.0 : 27142302   |
| Code de classification<br>d'objet | S  |

## Catégories

Produits basse tension → Appareillage modulaire et parafoudres → Command and Signalling Devices → Control Switches, Pushbuttons and Indicator Lights

