

PRODUCT-DETAILS

TS 25/12-24 C

TS 25/12-24 C Safety isolating transformer



Informations générales

Extension du type de produit	TS 25/12-24 C
Code de produit	2CSM251043R0811
EAN	8012542928508
Description courte	TS 25/12-24 C Safety isolating transformer
Description longue	TS-C are ideal for supplying permanent power to meters, auxiliary electronic devices and circuits with very low safety voltage (SELV) for bathrooms and showers, lighting, fountains, electro-medical devices and suchlike.

Technique

Normes et standards	IEC/EN 61558-2-6
Application	Building and Industrial
Tension	230 V AC
Tension principale	230 V
Secondary Voltage	(10-12) 12 V AC (10-14) 24 V AC (12-14) 0 V AC
Courant secondaire	(10-12) 2.08 A (10-14) 1.04 A (12-11) 0 A
Output Current Maximum (I_{out})	1.04 A
Fréquence assignée (f)	50/60 Hz

Power Loss	< 5 (full load) W
Alimentation	25 V·A
Rated Output Power	25 W
Classe d'isolation	B
Couple de serrage	0.5 N·m
Transformer Type	Non - Inherently Short Circuit Proof
Options Provided	None
Remarques	Suitable for loads that require a continuous supply. Double insulation between primary and secondary windings
Connecting Capacity	2.5 mm ²
Wire Stripping Length	9 mm

Environnement

Température de l'air ambiant	Operation +10 ... +40 °C
Indice de protection	IP20
Statut RoHS	Following EU Directive 2002/95/EC August 18, 2005 and amendment
Informations RoHS	9AKK106713A5646
REACH Declaration	9AKK108467A9482
Informations environnementales	See RoHS Information
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

Technique UL/CSA

Connecting Capacity UL/CSA	14 AWG
----------------------------	--------

Dimensions

Width in Number of Modular Spacings	4
Produit Largeur Net	70 mm
Produit Hauteur Net	0.085 m
Produit Longueur Net	0.120 m
Poids net	0.945 kg

Commande

Emballage Niveau 1 Unités	box 1 pièce
Emballage Niveau 1 Poids	0.945 kg
E-Number (Finland)	8409006
E-Number (Sweden)	5208116

Certificats et Déclarations (Numéro de document)

Agence de certification	IMQ
Déclaration de Conformité - CE	9AKK106713A5646

EAC Certificate	9AKK107992A6755
IMQ Certificate	9AKK107992A6749

Installation

Instructions et manuels	No document needed
Wiring Diagram	9AKK108467A7317

Downloads Préférés

Fiche produit, informations techniques	9AKK107991A8329
--	-----------------

Classifications

ETIM 8	EC001547 - Bell transformer
ETIM 9	EC001547 - Bell transformer
Catégorie DEEE	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer
CN8	85043121
eClass	V11.0 : 27031190
Code de classification d'objet	T

Catégories

Produits basse tension → Appareillage modulaire et parafoudres → Command and Signalling Devices → Bells and safety transformers

