


PRODUCT-DETAILS

DDA204 B-40/0.03 AP-R

DDA204 B-40/0.03 AP-R Residual Current Device Block



Informations générales

Extension du type de produit	DDA204 B-40/0.03 AP-R
Code de produit	2CSB204592R1400
EAN	8012542020325
Description courte	DDA204 B-40/0.03 AP-R Residual Current Device Block
Description longue	The RCD block DDA200 series is suitable for assembly with MCBs S200 series and S300P. Type B is also sensitive to continuous current pulsating earth fault currents. They are used for protection in installations with electronic equipment according to EN 50178. Applications: tertiary and industrial.

Technique

Normes et standards	IEC/EN 61009 Ann. G IEC/EN 62423
Type of Residual Current	B type
Tension nominale (U_r)	230...400 V
Tension	230/400 V
Tension assignée d'isolement (U_i)	500 V
Tension assignée de tenue aux chocs (U_{imp})	4 kV

Courant nominal (I_n)	40 A
Rated Residual Current	30 mA
Maximum Surge Current	3 kA
Leakage Current Type	B
Fréquence assignée (f)	50 ... 60 Hz
Power Loss	4.8 W
Power Supply Connection	Arbitrary
Electrical Endurance	10000 cycle
Nombre de pôles	4
Operating Characteristic	Instantaneous (APR High Immunity)
Options Provided	-
Connecting Capacity	Rigid 16 ... 16 mm ² Flexible 16 ... 16 mm ²

Environnement

Température extérieure	-25...55 °C
Température de l'air ambiant	Operation -25...55 °C
Indice de protection	IP2X
Resistance to Vibrations acc. to IEC 60068-2-6	0.1 mm or 1 g - 20 cycles at 5...150...5 Hz
Résistance aux chocs selon CEI 60068-2-27	25g 2 shocks 13 ms
Statut RoHS	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Informations RoHS	9AKK106713A5615
REACH Declaration	9AKK108467A9482
Informations environnementales	Refer to RoHS
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

Technique UL/CSA

Short-Circuit Current Rating (SCCR)	0.03 ... 0.03 A
-------------------------------------	-----------------

Dimensions

Produit Largeur Net	140 mm
Produit Hauteur Net	93 mm
Produit Longueur Net	76 mm
Poids net	0.337 kg

Commande

Emballage Niveau 1	box 1 pièce
--------------------	-------------

Unités

Emballage Niveau 1 Poids	0.394 kg
--------------------------	----------

Certificats et Déclarations (Numéro de document)

Déclaration de Conformité - CE	9AKK106713A5615
-----------------------------------	-----------------

Installation

Instructions et manuels	9AKK108467A7092
-------------------------	-----------------

Downloads Préférés

Fiche produit, informations techniques	9AKK107991A8329
---	-----------------

Classifications

ETIM 8	EC002297 - Residual current circuit breaker (RCCB) module
ETIM 9	EC002297 - Residual current circuit breaker (RCCB) module
Catégorie DEEE	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer
CN8	85363030
eClass	V11.0 : 27142210
Code de classification d'objet	F

Catégories

Produits basse tension → Appareillage modulaire et parafoudres → Protection différentielle → Blocs différentiels

