

PRODUCT-DETAILS

TM15/12

TM15/12 Fail safe bell transformer



Informations générales

Extension du type de produit	TM15/12
Code de produit	2CSM228735R0802
EAN	8012542287353
Description courte	TM15/12 Fail safe bell transformer
Description longue	These transformers, with safety extremely-low voltage secondary (SELV), are suitable for driving loads that call for a discontinuous supply.

Technique

Normes et standards	IEC/EN 61558-2-8
Application	Residential
Tension principale	230 V
Secondary Voltage	(6-7) 4 V AC (5-6) 8 V AC (5-7) 12 V AC
Courant secondaire	1.25 A
Output Current Maximum (I_{out})	3.75 A
Fréquence assignée (f)	50/60 Hz
Power Loss	2.5 W

Alimentation	15 V·A
Rated Output Power	15 W
Classe d'isolation	B
Couple de serrage	0.5 N·m
Transformer Type	Fail - Safe Bell Transformers
Options Provided	None
Remarques	Suitable for loads that require a discontinuous supply. Double insulation between primary and secondary windings
Connecting Capacity	2.5 mm ²
Wire Stripping Length	9 mm

Environnement

Température de l'air ambiant	Operation +10 ... +40 °C
Indice de protection	IP20
Statut RoHS	Following EU Directive 2002/95/EC August 18, 2005 and amendment
Informations RoHS	2CSC446004K0201
REACH Declaration	9AKK108467A9482
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

Technique UL/CSA

Connecting Capacity UL/CSA	14 AWG
----------------------------	--------

Dimensions

Width in Number of Modular Spacings	2
Produit Largeur Net	35 mm
Produit Hauteur Net	0.085 m
Produit Longueur Net	0.065 m
Poids net	0.300 kg

Commande

Emballage Niveau 1 Unités	box 6 pièce
Emballage Niveau 1 Poids	2.1 kg
E-Number (Sweden)	5270507

Certificats et Déclarations (Numéro de document)

Agence de certification	IMQ
Déclaration de Conformité	2CSC446004K0201

- CE

EAC Certificate 9AKK107992A6660

IMQ Certificate 9AKK107992A6764

Installation

Instructions et manuels No document needed

Wiring Diagram 9AKK108467A7353

Downloads Préférés

Fiche produit, informations techniques 9AKK107991A8329

Classifications

ETIM 8 EC001547 - Bell transformer

ETIM 9 EC001547 - Bell transformer

Catégorie DEEE 5. Small Equipment (No External Dimension More Than 50 cm)

WEEE B2C / B2B Business To Consumer

CN8 85043121

eClass V11.0 : 27031190

Code de classification d'objet T

Catégories

Produits basse tension → Appareillage modulaire et parafoudres → Command and Signalling Devices → Bells and safety transformers

