

PRODUCT-DETAILS

TM30/24

TM30/24 Fail safe bell transformer



Informations générales

Extension du type de produit	TM30/24
Code de produit	2CSM228765R0802
EAN	8012542287650
Description courte	TM30/24 Fail safe bell transformer
Description longue	These transformers, with safety extremely-low voltage secondary (SELV), are suitable for driving loads that call for a discontinuous supply.

Technique

Normes et standards	IEC/EN 61558-2-8
Application	Residential
Tension principale	230 V
Secondary Voltage	(5-6) & (6-7) 12 V AC (5-7) 24 V AC
Courant secondaire	1.25 A
Output Current Maximum (I_{out})	2.5 A
Fréquence assignée (f)	50/60 Hz
Power Loss	3 W
Alimentation	30 V·A
Rated Output Power	30 W
Classe d'isolation	B

Couple de serrage	0.5 N·m
Transformer Type	Fail - Safe Bell Transformers
Options Provided	None
Remarques	Suitable for loads that require a discontinuous supply. Double insulation between primary and secondary windings
Connecting Capacity	2.5 mm²
Wire Stripping Length	9 mm

Environnement

Température de l'air ambiant	Operation +10 ... +40 °C
Indice de protection	IP20
Statut RoHS	Following EU Directive 2002/95/EC August 18, 2005 and amendment
Informations RoHS	2CSC446004K0201
REACH Declaration	9AKK108467A9482
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

Technique UL/CSA

Connecting Capacity UL/CSA	14 AWG
----------------------------	--------

Dimensions

Width in Number of Modular Spacings	3
Produit Largeur Net	52.5 mm
Produit Hauteur Net	0.085 m
Produit Longueur Net	0.065 m
Poids net	0.450 kg

Commande

Emballage Niveau 1 Unités	box 4 pièce
Emballage Niveau 1 Poids	1.8 kg

Certificats et Déclarations (Numéro de document)

Agence de certification	IMQ
Déclaration de Conformité - CE	2CSC446004K0201
EAC Certificate	9AKK107992A6660
IMQ Certificate	9AKK107992A6760

Installation

Instructions et manuels	No document needed
Wiring Diagram	9AKK108467A7356

Downloads Préférés

Fiche produit, informations techniques	9AKK107991A8329
--	-----------------

Classifications

ETIM 8	EC001547 - Bell transformer
ETIM 9	EC001547 - Bell transformer
Catégorie DEEE	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer
CN8	85043121
eClass	V11.0 : 27031190
Code de classification d'objet	T

Catégories

Produits basse tension → Appareillage modulaire et parafoudres → Command and Signalling Devices → Bells and safety transformers

