


PRODUCT-DETAILS

JA/S4.SMI.1M

JA/S4.SMI.1M SMI Shutter Actuator, 4-fold, Manual Operation, MDRC



Informations générales

| | |
|------------------------------|--|
| Extension du type de produit | JA/S4.SMI.1M |
| Code de produit | 2CDG110028R0011 |
| EAN | 4016779654234 |
| Description courte | JA/S4.SMI.1M SMI Shutter Actuator, 4-fold, Manual Operation, MDRC |
| Description longue | It controls four independent groups (broadcast) with up to four SMI (Standard Motor Interface) drives (230 V) for positioning blinds, roller shutters, awnings and other shading products. Status signals (motor fault, direction of movement) can also be sent from the SMI drive on the bus. Push buttons are located at the front of the device to control the outputs e.g. during commissioning. The current status of the output is displayed via LEDs. |

Installation

| | |
|-------------------------|-----------------|
| Instructions et manuels | 2CDG941032P0003 |
|-------------------------|-----------------|

Technique

| | |
|--|------------------------------------|
| Fiche produit, informations techniques | 2CDC506035D0201 2CDC506037D0201 |
| Type de courant | AC |
| Auxiliary Voltage AC/DC | 230 V AC |

| | |
|------------------------|-----------------------------------|
| Power Loss | 2 W |
| Nombre de sorties | 4 |
| Nombre de LED | 1 |
| Compatible Bus Systems | KNX (TP) SMI |
| Product Range | KNX |
| Type de montage | DIN-Rail |
| Manual Operation | Oui |
| Couleur | light grey |
| Nombre de batteries | 0 |
| Application Function | Blind / Shutter / Shading Control |

Environnement

| | |
|---|-----------------------------------|
| Indice de protection | IP20 |
| Statut RoHS | Following EU Directive 2011/65/EU |
| Informations RoHS | 2CDK506080D2701 |
| REACH Declaration | 9AKK107492A1906 |
| Conflict Minerals Reporting Template (CMRT) | 9AKK108468A3363 |

Dimensions

| | |
|---|-----------------|
| Width in Number of Modular Spacings | 4 |
| Produit Largeur Net | 72 mm |
| Produit Hauteur Net | 90 mm |
| Produit Longueur Net | 64.5 mm |
| Poids net | 0.218 kg |
| Profondeur d'encastrement (t ₂) | 64.5 mm |
| Schéma dimensionnel | 2CDC072033F0015 |

Certificats et Déclarations (Numéro de document)

| | |
|--------------------------------|-----------------|
| Déclaration de Conformité - CE | 2CDK506080D2701 |
| KNX Certificate | 9AKK105710A0050 |

Classifications

| | |
|----------------|--|
| ETIM 8 | EC001330 - Shutting actuator for bus system |
| ETIM 9 | EC001330 - Shutting actuator for bus system |
| Catégorie DEEE | 5. Small Equipment (No External Dimension More Than 50 cm) |
| WEEE B2C / B2B | Business To Consumer |
| CN8 | 8537 10 91 |

eClass

V11.0 : 27143128

Code de classification
d'objet

A

Accessories

| Identifier | Description | Type | Quantity | Unit Of Measure |
|-----------------|-------------------------------------|-----------|----------|-----------------|
| GHQ6310084R0111 | JSB/S1.1 Shutter Control Unit, MDRC | JSB/S 1.1 | 1 | piece |

Catégories

Produits basse tension → Home and Building Automation → KNX → Shading Control → Blind Actuators SMI

