


PRODUCT-DETAILS

# JRA/S4.230.2.1

## JRA/S4.230.2.1 Blind/Roller Shutter Act 4-f, 230 V AC, Manual Operation, MDRC



### Informations générales

|                              |  |
|------------------------------|--|
| Extension du type de produit | JRA/S4.230.2.1   |
| Code de produit              | 2CDG110121R0011  |
| EAN                          | 4016779698405  |
| Description courte           | JRA/S4.230.2.1 Blind/Roller Shutter Act 4-f, 230 V AC, Manual Operation, MDRC  |
| Description longue           | For the control of independent 230 V AC drives via ABB i-bus® KNX. The devices are designed for positioning blinds, roller shutters, awnings and other shading products as well as for controlling doors, windows and ventilation flaps. Additional auxiliary voltage is not needed. To protect the drives, the output contacts are electromechanically locked against each other. Push buttons are located at the front of the device to control the outputs e.g. during commissioning. The current status of the output is displayed via LEDs. |

### Installation

|                         |                 |
|-------------------------|-----------------|
| Instructions et manuels | 2CDG941080P0004 |
|-------------------------|-----------------|

### Technique

|  |                                    |
|--|------------------------------------|
| Fiche produit, informations techniques | 2CDC506040D0201<br>2CDC506063D0202 |
| Type de courant                        | AC                                 |

|                                       |                                   |
|---------------------------------------|-----------------------------------|
| Fonctions spéciales                   | Switching                         |
| Voltage Range                         | 230 V AC                          |
| Tension de sortie (U <sub>out</sub> ) | 230 V AC                          |
| Maximum Switching Current             | 6 A                               |
| Maximum Switching Power               | 2400 W                            |
| Power Loss                            | 0.25 W                            |
| Nombre de sorties                     | 4                                 |
| Nombre de LED                         | 1                                 |
| Compatible Bus Systems                | KNX (TP)                          |
| Product Range                         | KNX                               |
| Type de montage                       | DIN-Rail                          |
| Manual Operation                      | Oui                               |
| Couleur                               | light grey                        |
| Nombre de batteries                   | 0                                 |
| Application Function                  | Blind / Shutter / Shading Control |

## Environnement

|   |   |
|---|---|
| Indice de protection                        | IP20  |
| Statut RoHS                                 | Following EU Directive 2002/95/EC August 18, 2005 and amendment |
| Informations RoHS                           | 2CDG510127-0100   |
| REACH Declaration                           | 9AKK107492A1906   |
| SCIP  | f01e1dea-cf98-4f39-99fb-26bd1168f764 Germany (DE)               |
| Conflict Minerals Reporting Template (CMRT) | 9AKK108468A3363   |

## Dimensions

|   |                 |
|---|-----------------|
| Width in Number of Modular Spacings         | 4               |
| Produit Largeur Net                         | 72 mm           |
| Produit Hauteur Net                         | 90 mm           |
| Produit Longueur Net                        | 64.5 mm         |
| Poids net                                   | 0.22 kg         |
| Profondeur d'encastrement (t <sub>2</sub> ) | 64.5 mm         |
| Schéma dimensionnel                         | 2CDC072033F0015 |

## Certificats et Déclarations (Numéro de document)

|                                |                 |
|--------------------------------|-----------------|
| CB Certificate                 | 9AKK107991A3191 |
| Déclaration de Conformité - CE | 2CDK506045D2701 |
| KNX Certificate                | 9AKK105710A0056 |

## Classifications

|                                |  |
|--------------------------------|--|
| ETIM 8                         | EC001330 - Shutting actuator for bus system                |
| ETIM 9                         | EC001330 - Shutting actuator for bus system                |
| Catégorie DEEE                 | 5. Small Equipment (No External Dimension More Than 50 cm) |
| WEEE B2C / B2B                 | Business To Consumer                                       |
| CN8                            | 8537 10 91   |
| eClass                         | V11.0 : 27143128   |
| Code de classification d'objet | A  |

## Accessories

| Identifiant     | Description                         | Type      | Quantity | Unit Of Measure |
|-----------------|-------------------------------------|-----------|----------|-----------------|
| GHQ6310084R0111 | JSB/S1.1 Shutter Control Unit, MDRC | JSB/S 1.1 | 1        | piece           |

## Catégories

Produits basse tension → Home and Building Automation → KNX → Shading Control → Blind Actuators 230 V AC

