

PRODUCT-DETAILS

6131/40-24-500

6131/40-24-500 KNX Motion Detector Sky W



Informations générales

Extension du type de produit	6131/40-24-500
Code de produit	2CKA006132A0350
EAN	4011395185971
Description courte	6131/40-24-500 KNX Motion Detector Sky W

Description longue	<p>Detection range (for mounting height 6 m and 12 m): circular. Walking persons Ø: max. 18 m and 24 m. Visible height 23 mm. With 2 channels. Targeted for connection and disconnection of lights bands depending on the room brightness. Use of the device as a movement detector. Detectors application with 2 power off stages. Detectors application with integrated monitoring function. Constant light switch with up to two independent channels. Constant light switch with max. 2 outputs for brightness-dependent switching of two light bands in the area. With integrated KNX bus coupler. The programming button can be activated with the IR transmitter 6010-25 (-500). Suitable for false ceilings with a board thickness from 9 to 25 mm. Hole size: Ø 68 mm. Suitable for surface mounting installation. Cannot be installed in British Standard or VDE flushmounted box. Recommendation: Installation housing from Kaiser HaloX-O (Art.no. 1290-40) with corresponding cover plates (1290-47 or 1290-85 for fair faced concrete) or IBTronic H120-68 from Spelsberg.</p>
--------------------	--

Installation

Instructions et manuels	No document needed
-------------------------	--------------------

Valeur Circulaire

Principes du Design Circulaire - Durée de vie	2CKA000073B5454
--	-----------------

Déchets destinés à l'enfouissement en décharge - Destination	Aucun déchet non-dangereux mis en décharge -
Matériau Durable constitutif des Emballages	Carton recyclé FSC - 90 %
Amélioration de l'efficacité des ressources pour les clients	Efficacité numérique - Le produit bénéficie d'un support numérique afin d'optimiser son utilisation et, à terme, optimiser les biens et services du client -
Proposé avec une durée de vie prolongée	Mise à niveau du produit -
Proposition de reprise	Reprendre pour recycler -

Eco Transparence

Environmental Product Declaration - EPD	9AKK108468A1033
---	-----------------

Technique

Fiche produit, informations techniques	2CKA006132D0202
Plage de mesure	24 m
Number of Channels	2
Compatible Bus Systems	KNX (TP)
Product Range	KNX
Minimum Switching Time	Switch-On 10 second [unit of time]
Type de montage	Surface Mounted Flush Mounted
Finition de surface	Surface protection: Untreated Surface finishing: Matt
Matériau	Thermoplastic
Type d'encastrement	Ceiling
Model Number	Movement sensor
RAL Number	RAL 9016 - Blanc signalisation
Couleur	studio white matt
Nombre de batteries	0
Application Function	Electrical Load and Light Control

Environnement

Température de l'air ambiant	Operation -5 ... +45 °C
Indice de protection	IP20
Statut RoHS	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Informations RoHS	2CKA200000E4528
REACH Declaration	2CKA309999E9999
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

Dimensions

Produit Largeur Net	91 mm
Produit Hauteur Net	91 mm
Produit Longueur Net	45 mm

Poids net	81 g
Profondeur d'encastrement (t ₂)	22 mm

Commande

ID du produit remplacé	6132-0-0350
------------------------	-------------

Certificats et Déclarations (Numéro de document)

Déclaration de Conformité - CE	2CKA100000E1061
--------------------------------	-----------------

Classifications

ETIM 8	EC001582 - Movement sensor for bus system
ETIM 9	EC001582 - Movement sensor for bus system
Catégorie DEEE	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer
CN8	8536 50 80
eClass	V11.0 : 27143144

Accessories

Identifiant	Description	Type	Quantity	Unit Of Measure
2CKA006132A0403	6131/38-24-500 Intermediate ring fm box W	6131/38-24-500	1	piece
2CKA006899A2304	Protection Cover	6898	1	piece

Catégories

Produits basse tension → Home and Building Automation → KNX → Presence Detection → Presence Detectors

