

PRODUCT-DETAILS

CE4T-10R-01

CE4T-10R-01 Emergency stop



Informations générales

Extension du type de produit	CE4T-10R-01
Code de produit	1SFA619550R1041
EAN	7320500260715
Description courte	CE4T-10R-01 Emergency stop
Description longue	<p>The CE4T-10R-01 Emergency stop is: Compact - Emergency stop - Twist release - Maintained - Mushroom 40 mm - Red - Non-illuminated - 1NC - 0 NO - 1 NC - 24 ... 300 V</p> <p>This Emergency stop is part of ABB's compact range, the most efficient all-in-one solution available, reducing installation time and cost.</p> <p>The compact range has a high level of dust and water resistance.</p>

Commande

Quantité minimum	10 pièce
Code douanier	8536500000

Downloads Préférés

Fiche produit, informations techniques	1SFC151007C02_
Instructions et manuels	1SFC151011M0201

Dimensions

Produit Largeur Net	0.04 m
Produit Hauteur Net	0.04 m
Produit Longueur Net	0.073 m
Poids net	0.034 kg

Technique

Température de l'air ambiant	Operation -25 ... +70 °C Storage -40 ... +85 °C
Couleur	Red
Actuator Type	Mushroom 40 mm
Bezel Material	n/a
Voyant	Non-illuminated
Fonction	Maintained
Sub-Function	Twist release
Number of Auxiliary Contacts NC	1
Number of Auxiliary Contacts NO	0
Indice de protection	Front IP66 Front IP67 Front IP69K Terminals IP20
Classe de protection (NEMA)	Type1 Type12 Type13 Type3R Type4 Type4X
Degré de pollution	3
Tension assignée d'isolement (U _i)	300 V
Tension assignée de tenue aux chocs (U _{imp})	6 kV
Fréquence assignée (f)	50 / 60 Hz
Tension	24 ... 300 V
Courant assignée d'emploi DC-13 (I _e)	(24 V) 0.3 A (125 V) 0.2 A
Courant assignée d'emploi AC-15 (I _e)	(240 V) 1 A
Power Loss	Maximum 2.5 W
Durabilite mecanique	0.5 million
Connecting Capacity	Flexible with Ferrule 1 x 0.5...1.5 mm ² Flexible with Ferrule 2 x 0.5...1.5 mm ² Flexible with Insulated Ferrule 1 x 0.5...1.5 mm ² Flexible with Insulated Ferrule 2 x 0.5...1.5 mm ² Flexible 1 x 0.5 ...1.5 mm ² Flexible 2 x 0.5 ...1.5 mm ² Solid 1 x 0.5...1.5 mm ² Solid 2 x 0.5...1.5 mm ²
Type de raccordement	Screw Clamp
Type de borne	Screw Terminals
Couple de serrage	0.8 N·m
Wire Stripping Length	6 mm

Technique UL/CSA

Connecting Capacity
UL/CSA1x 22...14 AWG
2x 22...14 AWG**Environnement**

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
Informations RoHS	2CMT2019-005802
Statut RoHS	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
SCIP	c582101b-4939-4d5f-b12d-b32f01ac5d63 Sweden (SE)
SCIP simplifié	5a2122cb-2c0a-4322-898e-904e23243664 Greece (GR) 26db0866-6d9a-475f-9eaa-4722d26d78c5 Czech Republic (CZ) 97c1c5d4-ed74-4eb5-a66a-609ee32af11c Netherlands (NL) b6818551-9f39-4a24-8c7c-29b37d141159 Sweden (SE) a2872bc7-a388-4c47-ba22-e827be568ef4 Poland (PL) eccab23d-e401-4277-95a2-dd6f8d376726 Germany (DE) 28ccc227-3603-460a-a999-435aab89af9c France (FR) 90140c16-e3db-4cd7-b460-38ebdf66fb8f Hungary (HU) 03ab40c0-7d79-4be6-9cb6-08240c1bb990 Belgium (BE) e01cbdef-5887-47c3-a143-19d902e72e2f Spain (ES) 3c26a25e-b21e-47d1-888f-23a27db39a23 France (FR) 717ce62e-6161-4c5c-86da-d3ca4f4d2e83 Germany (DE) 4203ffba-b8eb-4a4e-bea7-6c98d3915711 Finland (FI) c599f7ec-9f48-40bd-8a10-bfe6623e8799 Denmark (DK) 82f1d6ad-9215-4ad9-9028-1f667d1cb6f7 Germany (DE) fe671a11-5008-4a30-8283-9f2d31c23ef8 Hungary (HU) 993700bf-e4b0-42eb-8ae7-9a42efa10ef2 Estonia (EE) cc08b0c8-4050-46f2-9362-f35060ccb92a Portugal (PT) 0a6d189e-ec1c-4753-9cbb-04ab87fb3159 Bulgaria (BG) 57db3164-45d1-47d4-be46-6aaba061e8c5 Poland (PL) 7b843ca6-067a-4c9b-84e8-f91f0254db56 Croatia (HR) 80254368-b583-4bb9-8b94-a0cc4a67fa82 Poland (PL) 901c168f-fe56-4e1a-95d3-77dc0233755b Norway (NO) 753b989e-86e0-49e7-be48-ddbb27ec8da7 Italy (IT) 008604fa-56c6-470e-b8b9-4ddf7c6b70fb Belgium (BE) 610f2db9-1a2b-4996-8c14-59d41077a39b Germany (DE)
WEEE B2C / B2B	Business To Business
Catégorie DEEE	5. Small Equipment (No External Dimension More Than 50 cm)

Certificats et Déclarations (Numéro de document)

CB Certificate	CN54150 CQC_CN_CN50749
CQC Certificate	CQC2003010305054693
Certificat ecULus	UL_E496500-20171020
Declaration of Conformity - CCC	2020980305001187
Déclaration de Conformité - CE	2CMT2019-005802
Declaration of Conformity - UKCA	2CMT2020-006122
DNV GL Certificate	9AKK107046A3749
EAC Certificate	EAC RU C-CN.ME77.B.00537/19

Emballage

Emballage Niveau 1 Unités	bag 1 pièce
Emballage Niveau 1 Largeur	0.165 m
Emballage Niveau 1 Longueur	0.09 m
Emballage Niveau 1	0.045 m

Hauteur

Emballage Niveau 1 Poids	0.036 kg
Emballage Niveau 1 EAN	7320500260715

Classifications

Code de classification d'objet	S
ETIM 6	EC002034 - bouton-poussoir ARRET D'URGENCE, appareil complet
ETIM 7	EC002034 - Emergency stop complete
ETIM 8	EC002034 - Emergency stop complete
eClass	V11.0 : 27371244
UNSPSC	39122216
Code de catégorie granulaire IDEA (IGCC)	5212 >> Push button for distribution board
E-Number (Finland)	2313536
E-Number (Norway)	4372707
E-Number (Sweden)	3711514

Catégories

Produits basse tension → Produits de Contrôle, Protection et sécurité machines → Unités de commande et de signalisation → Compact Range → CE Compact Emergency Stops and Machine Stops

