

PRODUCT-DETAILS

RT/U30.0.1-825

RT/U30.0.1-825 RoomTouch 5 -825



Informations générales

Extension du type de produit	RT/U30.0.1-825
Code de produit	2TMA200050B0005
EAN	6955891816190
Description courte	RT/U30.0.1-825 RoomTouch 5 -825

Description longue	<p>Multifunctional HD IPS KNX touchdisplay as a room control element for visualisation and control of all functions in a KNX system. For the display and intuitive control of the following standard KNX functions: Switching, rocker switch, dimming (4-bit and 8-bit), slider, blind, RGBW control element, room temperature control element, Split Unit control element, step switch, scene switch, display element or audio control element. Additional functions: 20 fault and alarm messages, 10 logic functions, 10 timers each with 6 switching times, 4 scene actuators, 1 room temperature controller and individual pages can be protected with a PIN code. Status display, display of date and time, as well as inside and outside temperature. Installed temperature sensor, proximity sensor and brightness sensor. With a push-button/switch input and external temperature sensor input. Page display with a maximum of 30 touch surfaces on 6 or 10 pages (dependent on the mounting method). Viewing angle display: 160° - 160°. Mounting via a separate flush-mounted box. External power supply: 20-32 VDC (SELV).</p>
--------------------	--

Installation

Instructions et manuels	2TMU190000M0049
-------------------------	-----------------

Technique

Fiche produit, informations	No document needed
-----------------------------	--------------------

techniques

Auxiliary Voltage AC/DC	20 V AC/DC 32 V AC/DC
Compatible Bus Systems	KNX (TP)
Product Range	KNX
Type de montage	Flush Mounted
RAL Number	Similar to RAL 9005
Couleur	glass black
Taille d'écran	5 in
Application Function	Blind / Shutter / Shading Control Electrical Load and Light Control Data Communication / Multimedia Room Climate Control Safety and Security

Environnement

Statut RoHS	Following EU Directive 2011/65/EU
Informations RoHS	9AKK107680A8249
REACH Declaration	2CKA309999E9999
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

Dimensions

Poids net	366 g
-----------	-------

Certificats et Déclarations (Numéro de document)

Déclaration de Conformité - CE	9AKK107680A8247
--------------------------------	-----------------

Classifications

ETIM 8	EC001585 - Multi operating device for bus system
ETIM 9	EC001585 - Multi operating device for bus system
Catégorie DEEE	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer
CN8	8537 10 91
eClass	V11.0 : 27143101

Accessories

Identifiant	Description	Type	Quantity	Unit Of Measure
2CKA006300A1611	TZW/U.0.1.CK Anti-theft protection tool	TZW/U.0.1.CK	1	piece
2CKA006220A0721	DP4-T-1 Temperature Sensor	DP4-T-1	1	piece
2CDG120037R0011	CP-D24/2.5 priOn Power Supply, 24 V DC, 2.5 A, MDRC	CP-D24/2.5	1	piece
2TMA200160B0003	BOX/U5.1 Mounting box 5Inch FM	BOX/U5.1	1	piece

Catégories

Produits basse tension → Home and Building Automation → KNX → Visualisation, Display and Signalling → Touch Panels

