

PRODUCT-DETAILS

AF30Z-30-00-21

AF30Z-30-00-21 24-60V50/60HZ 20-60VDC

Contacteur



Informations générales

| | |
|------------------------------|--|
| Extension du type de produit | AF30Z-30-00-21 |
| Code de produit | 1SBL276001R2100 |
| EAN | 3471523114418 |
| Description courte | AF30Z-30-00-21 24-60V50/60HZ 20-60VDC Contacteur |

| | |
|--------------------|--|
| Description longue | <p>The AF30Z-30-00-21 is a 3 pole - 690 V IEC or 600 UL contactor with screw terminals, controlling motors up to 15 kW / 400 V AC (AC-3) or 20 hp / 480 V UL and switching power circuits up to 50 A (AC-1) or 50 A UL general use. Thanks to the AF technology, the contactor has a wide control voltage range (24-60 V 50/60 Hz and 20-60 V DC), managing large control voltage variations, reducing panel energy consumptions and ensuring distinct operations in unstable networks. Furthermore, surge protection is built-in, offering a compact solution. AF contactors have a block type design, can be easily extended with add-on auxiliary contact blocks and an additional wide range of accessories.</p> |
|--------------------|--|

Commande

| | |
|------------------|----------|
| Quantité minimum | 1 pièce |
| Code douanier | 85364900 |

Downloads Préférés

| | |
|-------------------------|-----------------|
| Instructions et manuels | 1SBC101027M6801 |
| CAD Dimensional Drawing | 2CDC001079B0201 |

Dimensions

| | |
|----------------------|---------|
| Produit Largeur Net | 45 mm |
| Produit Longueur Net | 86 mm |
| Produit Hauteur Net | 86 mm |
| Poids net | 0.35 kg |

Technique

| | |
|--|---|
| Number of Main Contacts NO | 3 |
| Number of Main Contacts NC | 0 |
| Number of Auxiliary Contacts NO | 0 |
| Number of Auxiliary Contacts NC | 0 |
| Normes et standards | IEC/EN 60947-1, IEC/EN 60947-4-1, UL 60947-4-1, CSA C22.2 No. 60947-4-1 |
| Tension | Circuit principal 690 V |
| Fréquence assignée (f) | Circuit de commande 50 / 60 Hz Circuit principal 50 / 60 Hz |
| Courant thermique conventionnel à l'air libre (I_{th}) | acc. to IEC 60947-4-1, Open Contactors $\Theta = 40^\circ\text{C}$ 50 A |
| Courant assignée d'emploi AC-1 (I_e) | (690 V) 40 °C 50 A (690 V) 60 °C 42 A (690 V) 70 °C 37 A |
| Courant assignée d'emploi AC-3 (I_e) | (415 V) 60 °C 32 A (440 V) 60 °C 32 A (500 V) 60 °C 28 A (690 V) 60 °C 21 A (380 / 400 V) 60 °C 32 A (220 / 230 / 240 V) 60 °C 33 A |
| Courant assignée d'emploi AC-3e (I_e) | (415 V) 60 °C 32 A (440 V) 60 °C 32 A (500 V) 60 °C 28 A (690 V) 60 °C 21 A (380 / 400 V) 60 °C 32 A (220 / 230 / 240 V) 60 °C 33 A |
| Puissance assignée d'emploi AC-3 (P_e) | (400 V) 15 kW (415 V) 15 kW (440 V) 18.5 kW (500 V) 18.5 kW (690 V) 18.5 kW (380 / 400 V) 15 kW (220 / 230 / 240 V) 9 kW |
| Puissance assignée d'emploi AC-3e (P_e) | (415 V) 15 kW (440 V) 18.5 kW (500 V) 18.5 kW (690 V) 18.5 kW (380 / 400 V) 15 kW (220 / 230 / 240 V) 9 kW |
| Courant assigné de courte durée admissible (I_{cw}) | at 40 °C Ambient Temp, in Free Air, from a Cold State 10 s 350 A at 40 °C Ambient Temp, in Free Air, from a Cold State 15 min 50 A at 40 °C Ambient Temp, in Free Air, from a Cold State 1 min 150 A at 40 °C Ambient Temp, in Free Air, from a Cold State 1 s 700 A at 40 °C Ambient Temp, in Free Air, from a Cold State 30 s 225 A |
| Maximum Breaking Capacity | cos phi=0.45 (cos phi=0.35 for $I_e > 100$ A) at 440 V 500 A cos phi=0.45 (cos phi=0.35 for $I_e > 100$ A) at 690 V 200 A |
| Maximum Electrical Switching Frequency | (AC-1) 600 cycles per hour (AC-2 / AC-4) 150 cycles per hour (AC-3) 1200 cycles per hour |
| Courant assignée d'emploi DC-1 (I_e) | (110 V) 2 Poles in Series, 40 °C 50 A (110 V) 2 Poles in Series, 60 °C 42 A (110 V) 2 Poles in Series, 70 °C 37 A (110 V) 3 Poles in Series, 40 °C 50 A |

| | |
|--|--|
| | (110 V) 3 Poles in Series, 60 °C 42 A (110 V) 3 Poles in Series, 70 °C 37 A (220 V) 3 Poles in Series, 40 °C 50 A (220 V) 3 Poles in Series, 60 °C 42 A (220 V) 3 Poles in Series, 70 °C 37 A (72 V) 1-Pole, 40 °C 50 A (72 V) 1-Pole, 60 °C 42 A (72 V) 1-Pole, 70 °C 37 A (72 V) 2 Poles in Series, 40 °C 50 A (72 V) 2 Poles in Series, 60 °C 42 A (72 V) 2 Poles in Series, 70 °C 37 A (72 V) 3 Poles in Series, 40 °C 50 A (72 V) 3 Poles in Series, 60 °C 42 A (72 V) 3 Poles in Series, 70 °C 37 A |
| Courant assignée d'emploi DC-3 (I_{θ}) | (110 V) 2 Poles in Series, 40 °C 50 A (110 V) 2 Poles in Series, 60 °C 42 A (110 V) 2 Poles in Series, 70 °C 37 A (110 V) 3 Poles in Series, 40 °C 50 A (110 V) 3 Poles in Series, 60 °C 42 A (110 V) 3 Poles in Series, 70 °C 37 A (220 V) 3 Poles in Series, 40 °C 50 A (220 V) 3 Poles in Series, 60 °C 42 A (220 V) 3 Poles in Series, 70 °C 37 A (72 V) 1-Pole, 40 °C 50 A (72 V) 1-Pole, 60 °C 42 A (72 V) 1-Pole, 70 °C 37 A (72 V) 2 Poles in Series, 40 °C 50 A (72 V) 2 Poles in Series, 60 °C 42 A (72 V) 2 Poles in Series, 70 °C 37 A (72 V) 3 Poles in Series, 40 °C 50 A (72 V) 3 Poles in Series, 60 °C 42 A (72 V) 3 Poles in Series, 70 °C 37 A |
| Courant assignée d'emploi DC-5 (I_{θ}) | (110 V) 2 Poles in Series, 40 °C 50 A (110 V) 2 Poles in Series, 60 °C 42 A (110 V) 2 Poles in Series, 70 °C 37 A (110 V) 3 Poles in Series, 40 °C 50 A (110 V) 3 Poles in Series, 60 °C 42 A (110 V) 3 Poles in Series, 70 °C 37 A (220 V) 3 Poles in Series, 40 °C 25 A (220 V) 3 Poles in Series, 60 °C 25 A (220 V) 3 Poles in Series, 70 °C 25 A (72 V) 1-Pole, 40 °C 25 A (72 V) 1-Pole, 60 °C 25 A (72 V) 1-Pole, 70 °C 25 A (72 V) 2 Poles in Series, 40 °C 50 A (72 V) 2 Poles in Series, 60 °C 42 A (72 V) 2 Poles in Series, 70 °C 37 A (72 V) 3 Poles in Series, 40 °C 50 A (72 V) 3 Poles in Series, 60 °C 42 A (72 V) 3 Poles in Series, 70 °C 37 A |
| Tension assignée d'isolement (U_i) | acc. to IEC 60947-4-1 690 V acc. to UL/CSA 600 V |
| Tension assignée de tenue aux chocs (U_{imp}) | 6 kV |
| Maximum Mechanical Switching Frequency | 3600 cycles per hour |
| Rated Control Circuit Voltage (U_c) | 50 Hz 24 ... 60 V 60 Hz 24 ... 60 V DC Operation 20 ... 60 V |
| Durée de fonctionnement nominale | Entre la mise hors tension de la bobine et la fermeture du contact NC (normally closed) 13 ... 98 ms Entre la mise hors tension de la bobine et l'ouverture du contact NO (normally open) 11 ... 95 ms Entre la mise sous tension de la bobine et l'ouverture du contact NC 38 ... 90 ms Entre la mise sous tension de la bobine et la fermeture du contact NO 40 ... 95 ms |
| Montage sur rail DIN | TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715 |
| Mounting by Screws (not supplied) | 2 x M4 screws placed diagonally |
| Connecting Capacity Main Circuit | Flexible with Ferrule 1/2x 1.5 ... 10 mm ² Flexible with Insulated Ferrule 1x 1.5 ... 10 mm ² Flexible with Insulated Ferrule 2x 1.5 ... 4 mm ² Rigid Solid 1/2x 2.5 ... 4 mm ² Rigid Stranded 1/2x 2.5 ... 10 mm ² |

| | |
|--|--|
| Connecting Capacity Control Circuit | Flexible with Ferrule 1/2x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 2x 0.75 ... 1.5 mm ² Rigid Solid 1/2x 1 ... 2.5 mm ² Rigid Stranded 1/2x 1 ... 2.5 mm ² |
| Wire Stripping Length | Control Circuit 10 mm Main Circuit 14 mm |
| Indice de protection | acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP20 acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP20 |
| Type de borne | Screw Terminals |

Technique UL/CSA

| | |
|---|--|
| Maximum Operating Voltage UL/CSA | Circuit principal 600 V |
| General Use Rating UL/CSA | (600 V AC) 50 A |
| Puissance nominale UL/CSA | (120 V AC) Single Phase 2 hp (200 ... 208 V AC) Three Phase 10 hp (220 ... 240 V AC) Three Phase 10 hp (240 V AC) Single Phase 5 hp (440 ... 480 V AC) Three Phase 20 hp (550 ... 600 V AC) Three Phase 25 hp |
| Connecting Capacity Main Circuit UL/CSA | Rigid Solid 1/2x 14-10 AWG Rigid Stranded 1/2x 14-8 AWG |
| Connecting Capacity Control Circuit UL/CSA | Rigid Solid 1/2x 18-14 AWG Rigid Stranded 1/2x 18-14 AWG |
| Tightening Torque UL/CSA | Control Circuit 11 in-lb Main Circuit 22 in-lb |

Environnement

| | |
|---|--|
| Température de l'air ambiant | Close to Contactor Fitted with Thermal O/L Relay -25 ... 60 °C Close to Contactor without Thermal O/L Relay -40 ... 70 °C Close to Contactor for Storage -60 ... +80 °C |
| Climatic Withstand | Category B according to IEC 60947-1 Annex Q |
| Altitude de fonctionnement maximale autorisée | Without Derating 3000 m |
| REACH Declaration | 2CMT2021-006202 |
| Résistance aux chocs selon CEI 60068-2-27 | Closed, Shock Direction: B1 25 g Open, Shock Direction: B1 5 g Shock Direction: A 30 g Shock Direction: B2 15 g Shock Direction: C1 25 g Shock Direction: C2 25 g |
| Resistance to Vibrations acc. to IEC 60068-2-6 | 5 ... 300 Hz 4 g closed position / 2 g open position |
| Informations RoHS | 2CMT2021-006277 |
| Statut RoHS | Following EU Directive 2011/65/EU |

Certificats et Déclarations (Numéro de document)

| | |
|------------------------------------|--|
| Certificat ABS | ABS_20-2060694-PDA |
| Certificat BV | BV_2634H24898C0 |
| CB Certificate | CB_SE-96552M1 |
| CCC Certificate | CCC_2010010304445623 |
| CQC Certificate | CQC2010010304445623 CQC2020010304294316 |
| Declaration of Conformity - CCC | 2020980304001254 2020980304001052 |

| | |
|-------------------------------------|------------------------------------|
| Déclaration de Conformité - CE | 1SBD250000U1000 |
| Declaration of Conformity - UKCA | 1SBD250031U1000 |
| Certificat DNV | DNV_TAE00001AF-4 |
| EAC Certificate | EAC_RU_FRME77B03447 |
| Certificat GOST | GOST_POCCFR.ME77.B07175.pdf |
| KC Certificate | KC_HW02016-15001C |
| Certificat LR | LRS_LR2002723TA-02 |
| Certificat RINA | RINA_ELE240318XG |
| Certificat RMRS | RMRS_1802705280 |
| Certificat UL | UL-US-2150887-5 UL-CA-2142658-5 |
| UL Listing Card | E312527 |

Emballage

| | |
|--------------------------------|---------------|
| Emballage Niveau 1 Unités | box 1 pièce |
| Emballage Niveau 1 Largeur | 87 mm |
| Emballage Niveau 1 Longueur | 87 mm |
| Emballage Niveau 1 Hauteur | 47 mm |
| Emballage Niveau 1 Poids | 0.35 kg |
| Emballage Niveau 1 EAN | 3471523114418 |
| Emballage Niveau 2 Unités | box 21 pièce |
| Emballage Niveau 2 Largeur | 250 mm |
| Emballage Niveau 2 Longueur | 300 mm |
| Emballage Niveau 2 Hauteur | 315 mm |
| Emballage Niveau 2 Poids | 15.75 kg |
| Emballage Niveau 3 Unités | 1080 pièce |

Classifications

| | |
|---|---|
| Code de classification d'objet | Q |
| ETIM 4 | EC000066 - Magnet contactor, AC-switching |
| ETIM 5 | EC000066 - Magnet contactor, AC-switching |
| ETIM 6 | EC000066 - contacteur de puissance pour commutation de courant alternatif |
| ETIM 7 | EC000066 - Power contactor, AC switching |
| ETIM 8 | EC000066 - Power contactor, AC switching |
| eClass | V11.0 : 27371003 |
| UNSPSC | 39121529 |
| Code de catégorie granulaire IDEA (IGCC) | 4758 >> Iec Contactors |
| E-Number (Finland) | 3706294 |
| E-Number (Sweden) | 3211380 |

