

PRODUCT-DETAILS

CM-MSS.51P

CM-MSS.51P Therm. motor protec. relay 2x1c/o, 24-240VAC/DC



Informations générales

Extension du type de produit	CM-MSS.51P
Code de produit	1SVR740712R1300
EAN	4013614496554
Description courte	CM-MSS.51P Therm. motor protec. relay 2x1c/o, 24-240VAC/DC

Description longue

The CM-MSS.51P belongs to the CM thermistor motor protection relay range. It operates with a rated control supply voltage of 24 - 240 V AC / DC and has a 2 c/o (SPDT) output with contacts rated at 250 V / 4 A. It features two sensor circuit to monitor PTC temperature sensors (single or accumulative evaluation, configurable) and works according to the closed-circuit principle. The sensor circuits of this CM-MSS.51P are short-circuit (configurable), as well as interrupted-wire monitored and can be reset automatically, manually or remotely after the failure has been removed. This protection relay is certified according to the ATEX directive 94/9/EC and is equipped with a reset / test button. The non-volatile fault storage, the short circuit detection and the accumulative evaluation can be enabled/disabled via DIP switches. A sealable transparent cover for protection against unauthorized changes is available as accessory. The device offers maintenance free Easy Connect Technology with push-in terminals.

Commande

EAN	4013614496554
Quantité minimum	1 pièce
Code douanier	85364900

Downloads Préférés

Fiche produit, informations techniques	2CDC112214D0201
Instructions et manuels	1SVC730700M1000 1SVC730700M0000
Ex Operating Instructions	1SVC730640M9000
CAD Dimensional Drawing	2CDC001079B0201

Dimensions

Produit Largeur Net	22.5 mm
Produit Hauteur Net	85.6 mm
Produit Longueur Net	103.7 mm
Poids net	0.135 kg

Technique

Fonction	2 sensor circuits Auto, manual or remote reset ATEX approved Dynamic interrupted wire detection Short-circuit detection, configurable Non-volatile fault storage, configurable Single or accumulative evaluation, configurable
Rated Control Supply Voltage (U_s)	24 ... 240 V AC/DC
Tension	Circuit auxiliaire 250 V AC
Fréquence assignée (f)	Supply Circuit 15 ... 400 Hz
Sortie	2 x 1 c/o or 1 x 2 c/o contacts, configurable
Type de borne	Screwless Terminals
Rated Operational Current AC-12 (I_e)	(230 V) 4 A
Courant assignée d'emploi AC-15 (I_e)	(230 V) 3 A
Rated Operational Current DC-12 (I_e)	(24 V) 4 A
Courant assignée d'emploi DC-13 (I_e)	(24 V) 2 A
Minimum Switching Capacity	24 V 10 mA
Tension assignée de tenue aux chocs (U_{imp})	Output Circuit 1 / Output Circuit 2 4 kV Output Circuit 4 kV
Tension assignée d'isolement (U_i)	Measuring Circuit / Output Circuit 300 V Output Circuit 1 / Output Circuit 2 300 V Supply Circuit / Measuring Circuit 300 V Supply Circuit / Output Circuit 300 V
Indice de protection	Housing IP50 Terminals IP20
Catégorie de Surtension	III
Degré de pollution	3
Dispositif de protection contre les courts-circuits	Output Circuit NC - F Type Fuses 6 A Output Circuit NO - F Type Fuses 10 A
Electrical Durability	AC-12 100000 cycle
Durabilité mécanique	30000000 cycle
Connecting Capacity	Flexible 2x 0.5 ... 1.5 mm ² Rigid 2x 0.5 ... 1.5 mm ²
Wire Stripping Length	8 mm
Type d'encastrement	1 ... 6

Montage sur rail DIN

TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715
TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715

Normes et standards

CAN/CSA C22.2 No.14
EN 50495
IEC/EN 63000
IEC/EN 60079-7
IEC/EN 60947-5-1
IEC/EN 60947-8
UL 508

Technique UL/CSA

Maximum Operating Voltage UL/CSA	Output Circuit 300 V AC
Contact Rating UL/CSA	B300
Connecting Capacity UL/CSA	Flexible 2x 18-16 AWG Rigid 2x 20-16 AWG
Pilot Duty UL/CSA	B300
Flammability According to UL94	V-0

Environnement

Température de l'air ambiant	Operation -25 ... +60 °C Storage -40 ... +85 °C
Altitude de fonctionnement maximale autorisée	Without Derating 2000 m
REACH Declaration	1SVD981001-4501
Informations RoHS	1SVD981007
Statut RoHS	Following EU Directive 2011/65/EU

Valeur Circulaire

Instructions relatives à la fin de vie	1SAC200290H0001
--	-----------------

Certificats et Déclarations (Numéro de document)

Certificat ATEX	EU Type Examination Certificate_TPS_18_ATEX_044254_0018_X
CB Certificate	CB_DK-40837-UL
CCC Certificate	CCC_2005010303165479
CQC Certificate	CQC2005010303165479
Certificat ecULus	cULus508_20140912-E140448
Declaration of Conformity - CCC	2020980303000194
Déclaration de Conformité - CE	1SVD981007
Declaration of Conformity - UKCA	1SVD981007-10
DNV GL Certificate	DNVGL_TAE00003W4
EAC Certificate	EAC_RU_C-DE.ME77.B.01825

Emballage

Emballage Niveau 1

box 1 pièce

Unités	
Emballage Niveau 1 Largeur	97 mm
Emballage Niveau 1 Longueur	30 mm
Emballage Niveau 1 Hauteur	109 mm
Emballage Niveau 1 Poids	0.161 kg
Emballage Niveau 1 EAN	4013614496554

Classifications

Code de classification d'objet	B
ETIM 7	EC002568 - Relay for thermistor protection (PTC)
ETIM 8	EC002568 - Relay for thermistor protection (PTC)
ETIM 9	EC002568 - Relay for thermistor protection (PTC)
eClass	V11.0 : 27371503
UNSPSC	39122331
E-Number (Finland)	2712513
E-Number (Sweden)	3860739

Catégories

Produits basse tension → Produits de Contrôle, Protection et sécurité machines → Relais électroniques → Relais de protection des moteurs à thermistances

