

## PRODUCT-DETAILS

# E 9F22 GG50

## E 9F22 GG50 Fuse link



### Informations générales

|                              |                                                                    |
|------------------------------|--------------------------------------------------------------------|
| Extension du type de produit | E 9F22 GG50                                                        |
| Code de produit              | 2CSM259393R1801                                                    |
| EAN                          | 8012542593935                                                      |
| Description courte           | E 9F22 GG50 Fuse link                                              |
| Description longue           | E 9F22 GG50 is a 22x58 mm cylindrical fuse for circuits protection |

### Technique

|                            |                                                                                                |
|----------------------------|------------------------------------------------------------------------------------------------|
| Normes et standards        | IEC 60269-2                                                                                    |
| Tension nominale ( $U_r$ ) | 690 V                                                                                          |
| Courant nominal ( $I_n$ )  | 50 A                                                                                           |
| Maximum Breaking Capacity  | 120 kA                                                                                         |
| Power Loss                 | at Rated Operating Conditions per Pole 5.3 W                                                   |
| Type de fusible            | gG                                                                                             |
| Type de libération         | gG: Used in general protection of cables and lines in installation and industrial applications |
| Matériau Construction      | Ceramic                                                                                        |
| Taille de fusible          | 22x58                                                                                          |

Contact Material

copper silver plated (Cu/Ag)

## Environnement

|                                             |                                                                        |
|---------------------------------------------|------------------------------------------------------------------------|
| Statut RoHS                                 | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |
| Informations RoHS                           | 9AKK106713A5625                                                        |
| REACH Declaration                           | 9AKK108467A9482                                                        |
| Informations environnementales              | See RoHS Information                                                   |
| Conflict Minerals Reporting Template (CMRT) | 9AKK108468A3363                                                        |

## Dimensions

|                      |                 |
|----------------------|-----------------|
| Produit Largeur Net  | 0.002 m         |
| Produit Hauteur Net  | 0.006 m         |
| Produit Longueur Net | 0.002 m         |
| Poids net            | 0.048 kg        |
| Schéma dimensionnel  | 9AKK108466A8534 |

## Commande

|                           |              |
|---------------------------|--------------|
| Quantité minimum          | 10 pièce     |
| Emballage Niveau 1 Unités | box 10 pièce |
| Emballage Niveau 1 Poids  | 0.05 kg      |

## Certificats et Déclarations (Numéro de document)

|                                |                 |
|--------------------------------|-----------------|
| Cut-off Current Characteristic | 9AKK108466A9076 |
| Déclaration de Conformité - CE | 9AKK106713A5625 |
| I <sup>pt</sup> Characteristic | 9AKK108467A0132 |

## Installation

|                         |                    |
|-------------------------|--------------------|
| Instructions et manuels | No document needed |
|-------------------------|--------------------|

## Downloads Préférés

|                                        |                 |
|----------------------------------------|-----------------|
| Fiche produit, informations techniques | 9AKK107991A8329 |
| Cut-off Current Characteristic         | 9AKK108466A9076 |
| I <sup>pt</sup> Characteristic         | 9AKK108467A0132 |
| Time-Current                           | 9AKK108467A0152 |

Characteristic Curve

Classifications

|                                |                                                            |
|--------------------------------|------------------------------------------------------------|
| ETIM 8                         | EC002704 - Cylindrical fuse                                |
| ETIM 9                         | EC002704 - Cylindrical fuse                                |
| Catégorie DEEE                 | 5. Small Equipment (No External Dimension More Than 50 cm) |
| WEEE B2C / B2B                 | Business To Business                                       |
| CN8                            | 85361050                                                   |
| eClass                         | V11.0 : 27142002                                           |
| Code de classification d'objet | F                                                          |

Catégories

Produits basse tension → Appareillage modulaire et parafoudres → Protection and Safety Devices → Cylindrical and D0 Fuses

